

Revision Date: 06-Jun-2024

Revision Number: 1

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name Product Code Alternate Product Code Product Class Color Recommended use Restrictions on use

Manufacturer Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 Phone: 1-866-708-9180 www.benjaminmoore.com

# HP ACRYLIC DTM ENAMEL SEMI-GLOSS - BLACK HP3310-80 UA9080

UA9080 Water thinned paint Black Paint No information available

> Emergency Telephone CHEMTREC: +1 703-741-5970 / 1-800-424-9300 +1 703-527-3887 (outside US & Canada)

2. HAZARDS IDENTIFICATION

# **Classification**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

	Carcinogenicity	Category 2
--	-----------------	------------

# Label elements

Warning		
Hazard statements		
Suspected of causing cancer		
Appearance liquid	Odor	little or no odor

#### **Precautionary Statements - Prevention**

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required

**Precautionary Statements - Response** IF exposed or concerned: Get medical advice/attention

Precautionary Statements - Storage Store locked up

**Precautionary Statements - Disposal** Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC) Not applicable

Other information

No information available

**WARNING:** This product contains isothiazolinone compounds at levels of <0.1%. These substances are biocides commonly found in most paints and a variety of personal care products as a preservative. Certain individuals may be sensitive or allergic to these substances, even at low levels.

# 3. COMPOSITION INFORMATION ON COMPONENTS

Chemical name	CAS No.	Weight-%
Ethylene glycol mono-2-ethylhexyl ether	1559-35-9	1 - 5
Kaolin	1332-58-7	1 - 5
Carbon black	1333-86-4	1 - 5
Zinc phosphate	7779-90-0	0.5 - 1
Ammonium hydroxide	1336-21-6	0.1 - 0.5

4. FIRST AID MEASURES			
General Advice No hazards which require special first aid measures.			
Eye Contact	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.		
Skin Contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.		
Inhalation	Move to fresh air. If symptoms persist, call a physician.		
Ingestion	Clean mouth with water and afterwards drink plenty of water. Consult a physician if necessary.		

Notes To Physician Treat symptomatically.   5. FIRE-FIGHTING MEASURES   Suitable Extinguishing Media Use extinguishing measures that are appropriate	
Suitable Extinguishing Media Use extinguishing measures that are approp	
circumstances and the surrounding environr	
Protective equipment and precautions for firefighters As in any fire, wear self-contained breathing pressure-demand, MSHA/NIOSH (approved and full protective gear.	
Specific Hazards Arising From The Chemical Closed containers may rupture if exposed to extreme heat.	o fire or
Sensitivity to mechanical impact No	
Sensitivity to static discharge No	
Flash Point Data250Flash point (°F)250Flash Point (°C)121MethodPMCC	
Flammability Limits In Air	
Lower flammability limit:Not applicableUpper flammability limit:Not applicable	
NFPA Health hazards 1 Flammability 1 Stability 0 Special: 0 Not Applicable NFPA Legend 0 - Not Hazardous 1 - Slightly	

- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.		
Other Information	Prevent further leakage or spillage if safe to do so.		
Environmental precautions	See Section 12 for additional Ecological Information.		
Methods for Cleaning Up	Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.		
	7. HANDLING AND STORAGE		
Handling	Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.		
Handling Storage	sanding dust. In case of insufficient ventilation, wear suitable respiratory		

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### **Exposure Limits**

Chemical name	ACGIH TLV	OSHA PEL
Kaolin	TWA: 2 mg/m <sup>3</sup> particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter	15 mg/m³ - TWA 5 mg/m³ - TWA
Carbon black	TWA: 3 mg/m <sup>3</sup> inhalable particulate matter	3.5 mg/m³ - TWA
Ammonium hydroxide	STEL: 35 ppm TWA: 25 ppm	-

#### Legend

ACGIH - American Conference of Governmental Industrial Hygienists Exposure Limits OSHA - Occupational Safety & Health Administration Exposure Limits N/E - Not Established

Engineering Measures	Ensure adequate ventilation, especially in confined areas.	
Personal Protective Equipment Eye/Face Protection Skin Protection Respiratory Protection	Safety glasses with side-shields. Protective gloves and impervious clothing. In case of insufficient ventilation wear suitable respiratory equipment.	
Hygiene Measures	Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.	

# 9. PHYSICAL AND CHEMICAL PROPERTIES

#### Appearance

liquid

Odor **Odor Threshold** Density (lbs./gal) **Specific Gravity** bН Viscosity (cps) Solubility(ies) Water solubility **Evaporation Rate** Vapor pressure @20 °C (kPa) **Relative vapor density** Wt. % Solids Vol. % Solids Wt. % Volatiles Vol. % Volatiles VOC Regulatory Limit (g/L) **Boiling Point (°F) Boiling Point (°C)** Freezing point (°F) Freezing Point (°C) Flash point (°F) Flash Point (°C) Method Flammability (solid, gas) Upper flammability limit: Lower flammability limit: Autoignition Temperature (°F) Autoignition Temperature (°C) **Decomposition Temperature (°F) Decomposition Temperature (°C)** Partition coefficient

little or no odor No information available 8.5 - 8.9 1.01 - 1.07 No information available 40 - 50 35 - 45 50 - 60 55 - 65 < 100 212 100 32 0 250 121 PMCC Not applicable Not applicable Not applicable No information available No information available No information available No information available No information available

**10. STABILITY AND REACTIVITY** 

Reactivity	Not Applicable
Chemical Stability	Stable under normal conditions.
Conditions to avoid	Prevent from freezing.
Incompatible Materials	No materials to be especially mentioned.
Hazardous Decomposition Products	None under normal use.
Possibility of hazardous reactions	None under normal conditions of use.

# 11. TOXICOLOGICAL INFORMATION

**Product Information** 

Information on likely routes of exposure			
Principal Routes of Exposure	Eye contact, skin contact and inhalation.		
Acute Toxicity			
Product Information	No information available		
Symptoms related to the physic	cal, chemical and toxicological characteristics		
Symptoms	No information available		
Delayed and immediate effects	as well as chronic effects from short and long-term exposure		
Eye contact	May cause slight irritation.		
Skin contact	Substance may cause slight skin irritation. Prolonged or repeated contact may dry		
	skin and cause irritation.		
Inhalation	May cause irritation of respiratory tract.		
Ingestion	Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.		
Sensitization	No information available		
Neurological Effects Mutagenic Effects	No information available. No information available.		
Reproductive Effects	No information available.		
Developmental Effects	No information available.		
Target organ effects	No information available.		
STOT - single exposure	No information available.		
STOT - repeated exposure	No information available.		
Other adverse effects	No information available.		
Aspiration Hazard	No information available		

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	66024 mg/kg
ATEmix (inhalation-dust/mist)	299 mg/l

**Component Information** 

Caution - This mixture contains a substance not yet fully tested

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Ethylene glycol mono-2-ethylhexyl ether 1559-35-9	= 3080 mg/kg (Rat)	= 2120 mg/kg (Rabbit)= 2120 µL/kg (Rabbit)	-
Kaolin 1332-58-7	> 5000 mg/kg (Rat)	> 5000 mg/kg (Rat)	-
Carbon black 1333-86-4	> 15400 mg/kg (Rat)	>3 g/kg (Rabbit)	-
Zinc phosphate 7779-90-0	> 5000 mg/kg (Rat)	-	-
Ammonium hydroxide 1336-21-6	= 350 mg/kg (Rat)	-	-

# Chronic Toxicity

#### Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

Chemical name	IARC	NTP	OSHA
	2B - Possible Human		Listed
Carbon black	Carcinogen		

#### Legend

IARC - International Agency for Research on Cancer NTP - National Toxicity Program OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

# **Ecotoxicity Effects**

The environmental impact of this product has not been fully investigated.

#### **Product Information**

#### Acute Toxicity to Fish No information available

#### Acute Toxicity to Aquatic Invertebrates

No information available

#### Acute Toxicity to Aquatic Plants

No information available

#### Persistence / Degradability

No information available.

#### **Bioaccumulation**

No information available.

#### Mobility in Environmental Media

No information available.

#### **Ozone**

Not applicable

# **Component Information**

# Acute Toxicity to Fish

No information available

# Acute Toxicity to Aquatic Invertebrates

No information available

#### Acute Toxicity to Aquatic Plants

No information available

13. DISPOSAL CONSIDERATIONS	
Waste Disposal Method	Dispose of in accordance with federal, state, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.
	14. TRANSPORT INFORMATION
DOT	Not regulated
ICAO / IATA	Not regulated
IMDG / IMO	Not regulated
	15. REGULATORY INFORMATION

#### International Inventories

TSCA: United States	Yes - All components are listed or exempt.
DSL: Canada	Yes - All components are listed or exempt.

# Federal Regulations

#### SARA 311/312 Hazard Categories

Acute health hazard	No
Chronic Health Hazard	Yes
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

None

# Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

None

# **US State Regulations**

California Proposition 65

Pennsylvania

Х

MARNING: This product can expose you to chemicals including Crystalline Silica, which are known to the State of California to cause cancer, and Ethylene glycol, which are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

#### U.S. State Right-to-Know Regulations

Carbon black

Chemical name	Massachusetts
Kaolin	Х

Legend

X - Listed

# **16. OTHER INFORMATION**

**New Jersey** 

Х

Х

#### HMIS

Health hazards	1*
Flammability	1
Reactivity:	0
Personal protection	-

#### **HMIS Legend**

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- Chronic Hazard
- X Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

# **Prepared By**

Product Stewardship Department

	Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 800-225-5554
Revision Date:	06-Jun-2024
Revision Summary	Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

**End of Safety Data Sheet**