



Benjamin Moore®

SAFETY DATA SHEET

Revision Date: 24-Aug-2023

Revision Number: 1

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name HP EPOXY MASTIC - CLEAR BASE
Product Code HP4600-9BFR
Alternate Product Code UF449B
Product Class epoxy
Color Clear
Recommended use Paint
Restrictions on use No information available

Manufactured For

Benjamin Moore & Co., Limited
 8775 Keele Street
 Concord ON L4K 2N1
 Phone: 1-800-361-5898
 www.benjaminmoore.com/en-ca

Manufacturer

Benjamin Moore & Co.
 101 Paragon Drive
 Montvale, NJ 07645
 Phone: 1-866-708-9180
 www.benjaminmoore.com

Emergency Telephone

CHEMTREC: +1 703-741-5970 / 1-800-424-9300
 +1 703-527-3887 (outside US & Canada)
 CANUTEC: 613-996-6666 (Transport Emergency Only)

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the Hazardous Products Regulations (HPR: SOR/2015-17)

| | |
|--|-------------|
| Skin corrosion/irritation | Category 2 |
| Serious eye damage/eye irritation | Category 2A |
| Respiratory sensitization | Category 1 |
| Skin sensitization | Category 1 |
| Germ cell mutagenicity | Category 1B |
| Carcinogenicity | Category 1A |
| Reproductive toxicity | Category 2 |
| Specific target organ toxicity (single exposure) | Category 3 |
| Specific target organ toxicity (repeated exposure) | Category 1 |
| Aspiration hazard | Category 1 |
| Flammable liquids | Category 3 |

Label elements

Danger**Hazard statements**

Causes skin irritation
Causes serious eye irritation
May cause allergy or asthma symptoms or breathing difficulties if inhaled
May cause an allergic skin reaction
May cause genetic defects
May cause cancer
Suspected of damaging fertility or the unborn child
May cause respiratory irritation
May cause drowsiness or dizziness
Causes damage to organs through prolonged or repeated exposure
May be fatal if swallowed and enters airways
Flammable liquid and vapor

**Appearance** liquid**Odor** solvent**Precautionary Statements - Prevention**

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Wash face, hands and any exposed skin thoroughly after handling
In case of inadequate ventilation wear respiratory protection
Contaminated work clothing should not be allowed out of the workplace
Do not breathe dust/fume/gas/mist/vapors/spray
Do not eat, drink or smoke when using this product
Use only outdoors or in a well-ventilated area
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
Keep container tightly closed
Ground and bond container and receiving equipment
Use only non-sparking tools
Take action to prevent static discharges
Keep cool
Wear protective gloves/clothing and eye/face protection

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

Skin

If skin irritation or rash occurs: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
Wash contaminated clothing before reuse

Inhalation

If experiencing respiratory symptoms: Call a POISON CENTER or doctor
IF INHALED: Remove person to fresh air and keep comfortable for breathing

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
Do NOT induce vomiting

Fire

In case of fire: Use CO₂, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up
Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other information

No information available

IMPORTANT: Designed to be mixed with other components. Mixture will have hazards of all components. Before opening packages, read all warning labels. Follow all precautions.

3. COMPOSITION INFORMATION ON COMPONENTS

| Chemical name | CAS No | Weight-% | Hazardous Material Information Review Act registry number (HMIRA registry #) | Date HMIRA filed and date exemption granted (if applicable) |
|--|------------|-------------|--|---|
| Polyamide epoxy | - | 10 - 30% | HMIRC # 03321980 | Filed: March 1, 2019 |
| Zinc phosphate | 7779-90-0 | 10 - 30% | - | - |
| Silica, crystalline | 14808-60-7 | 7 - 13% | - | - |
| Benzyl alcohol | 100-51-6 | 7 - 13% | - | - |
| Talc | 14807-96-6 | 7 - 13% | - | - |
| Xylene | 1330-20-7 | 5 - 10% | - | - |
| Propylene glycol monomethyl ether | 107-98-2 | 1 - 5% | - | - |
| Ethyl benzene | 100-41-4 | 1 - 5% | - | - |
| Triethylenetetramine | 112-24-3 | 1 - 5% | - | - |
| Solvent naphtha, petroleum, light aromatic | 64742-95-6 | 1 - 5% | - | - |
| 1,2,4-Trimethylbenzene | 95-63-6 | 0.5 - 1% | - | - |
| Phenol, 2,4,6-tris[(dimethylamino)methyl]- | 90-72-2 | 0.25 - 0.5% | - | - |
| 1,3,5-Trimethylbenzene | 108-67-8 | 0.1 - 0.25% | - | - |
| Diethylbenzene | 25340-17-4 | 0.1 - 0.25% | - | - |

Confidential Business Information note

*The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

| | |
|--|---|
| General Advice | If symptoms persist, call a physician. Show this safety data sheet to the doctor in attendance. |
| Eye Contact | Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician. |
| Skin Contact | Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician. Wash clothing before reuse. Destroy contaminated articles such as shoes. |
| Inhalation | Move to fresh air. If symptoms persist, call a physician. If not breathing, give artificial respiration. Call a physician immediately. |
| Ingestion | Clean mouth with water and afterwards drink plenty of water. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Consult a physician. |
| Protection Of First-Aiders | Use personal protective equipment. |
| Most Important Symptoms/Effects | May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause allergic skin reaction. |
| Notes To Physician | Treat symptomatically. |

5. FIRE-FIGHTING MEASURES

| | |
|--|---|
| Flammable Properties | Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause flash fire. |
| Suitable Extinguishing Media | Foam, dry powder or water. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. |
| Protective equipment and precautions for firefighters | As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. |
| Hazardous combustion products | Burning may result in carbon dioxide, carbon monoxide and other combustion products of varying composition which may be toxic and/or irritating. |
| Specific Hazards Arising From The Chemical | Flammable. Flash back possible over considerable distance. Keep product and empty container away from heat and sources of ignition. Closed containers may rupture if exposed to fire or extreme heat. Thermal decomposition can lead to release of irritating gases and vapors. |
| Sensitivity to mechanical impact | No |

| | |
|--|-------------------|
| Sensitivity to static discharge | Yes |
| Flash Point Data | |
| Flash point (°F) | 80 |
| Flash Point (°C) | 27 |
| Method | PMCC |
| Flammability Limits In Air | |
| Lower flammability limit: | No data available |
| Upper flammability limit: | No data available |
| NFPA | |
| Health hazards | 2 |
| Flammability | 3 |
| Stability | 0 |
| Special: | Not Applicable |

NFPA Legend
 0 - Not Hazardous
 1 - Slightly
 2 - Moderate
 3 - High
 4 - Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6. ACCIDENTAL RELEASE MEASURES

| | |
|----------------------------------|---|
| Personal Precautions | Remove all sources of ignition. Take precautions to prevent flashback. Ground and bond all containers and handling equipment. Take precautionary measures against static discharges. Ensure adequate ventilation. Avoid contact with skin, eyes and clothing. Use personal protective equipment. |
| Other Information | Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages cannot be contained. |
| Environmental precautions | See Section 12 for additional Ecological Information. |
| Methods for Cleaning Up | Dam up. Soak up with inert absorbent material. Use a non-sparking or explosion proof means to transfer material to a sealed, appropriate container for disposal. Clean contaminated surface thoroughly. |

7. HANDLING AND STORAGE

Handling

Avoid contact with skin, eyes and clothing. Wear personal protective equipment. Do not breathe vapors or spray mist. Use only in ventilated areas. Prevent vapor build-up by providing adequate ventilation during and after use.

Take precautionary measures against static discharges. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Ignition and/or flash back may occur.

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat. Keep away from open flames, hot surfaces and sources of ignition. Keep in properly labeled containers. Keep out of the reach of children.

Incompatible Materials

Incompatible with strong acids and bases and strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits

| Chemical name | ACGIH TLV | Alberta | British Columbia | Ontario | Quebec |
|-----------------------------------|--|--|---------------------------------|--|--|
| Silica, crystalline | TWA: 0.025 mg/m ³ respirable particulate matter | TWA: 0.025 mg/m ³ | TWA: 0.025 mg/m ³ | TWA: 0.10 mg/m ³ | TWA: 0.1 mg/m ³ |
| Talc | TWA: 2 mg/m ³ particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter | 2 mg/m ³ - TWA | 2 mg/m ³ - TWA | 2 mg/m ³ - TWA | 2 mg/m ³ - TWAEV |
| Xylene | TWA: 20 ppm | 100 ppm - TWA 434 mg/m ³ - TWA 150 ppm - STEL 651 mg/m ³ - STEL | 100 ppm - TWA 150 ppm - STEL | 100 ppm - TWA 150 ppm - STEL | 100 ppm - TWAEV 434 mg/m ³ - TWAEV 150 ppm - STEV 651 mg/m ³ - STEV |
| Propylene glycol monomethyl ether | STEL: 100 ppm TWA: 50 ppm | 100 ppm - TWA 369 mg/m ³ - TWA 150 ppm - STEL 553 mg/m ³ - STEL | 50 ppm - TWA 100 ppm - STEL | 50 ppm - TWA 100 ppm - STEL | 100 ppm - TWAEV 369 mg/m ³ - TWAEV 150 ppm - STEV 553 mg/m ³ - STEV |
| Ethyl benzene | Ototoxicant - potential to cause hearing disorders TWA: 20 ppm | 100 ppm - TWA 434 mg/m ³ - TWA 125 ppm - STEL 543 mg/m ³ - STEL | 20 ppm - TWA | 20 ppm - TWA | 100 ppm - TWAEV 434 mg/m ³ - TWAEV 125 ppm - STEV 543 mg/m ³ - STEV |
| Triethylenetetramine | - | - | - | 0.5 ppm - TWA 3 mg/m ³ - TWA Danger of cutaneous absorption | - |
| 1,2,4-Trimethylbenzene | TWA: 10 ppm | - | - | - | - |
| 1,3,5-Trimethylbenzene | TWA: 25 ppm | - | - | - | - |

Legend

ACGIH - American Conference of Governmental Industrial Hygienists
 Alberta - Alberta Occupational Exposure Limits
 British Columbia - British Columbia Occupational Exposure Limits
 Ontario - Ontario Occupational Exposure Limits
 Quebec - Quebec Occupational Exposure Limits
 N/E - Not established

Engineering Measures

Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment**Eye/Face Protection**

Tightly fitting safety goggles If splashes are likely to occur, wear: Safety glasses with side-shields

Skin Protection

Protective gloves and impervious clothing.

Respiratory Protection

Use only with adequate ventilation. In operations where exposure limits are exceeded, use a NIOSH approved respirator that has been selected by a technically qualified person for the specific work conditions. When spraying the product or applying in confined areas, wear a NIOSH approved respirator specified for paint spray or organic vapors.

Hygiene Measures

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|--------------------------------------|--------------------------|
| Appearance | liquid |
| Odor | solvent |
| Odor Threshold | No information available |
| Density (lbs./gal) | 10.9 - 11.3 |
| Specific Gravity | 1.30 - 1.36 |
| pH | No information available |
| Viscosity (cps) | No information available |
| Solubility(ies) | No information available |
| Water solubility | No information available |
| Evaporation Rate | No information available |
| Vapor pressure @20 °C (kPa) | No information available |
| Relative vapor density | No information available |
| Wt. % Solids | 80 - 90 |
| Vol. % Solids | 70 - 80 |
| Wt. % Volatiles | 10 - 20 |
| Vol. % Volatiles | 20 - 30 |
| VOC Regulatory Limit (g/L) | < 250 |
| Boiling Point (°F) | 248 |
| Boiling Point (°C) | 120 |
| Freezing point (°F) | No information available |
| Freezing Point (°C) | No information available |
| Flash point (°F) | 80 |
| Flash Point (°C) | 27 |
| Method | PMCC |
| Flammability (solid, gas) | Not applicable |
| Upper flammability limit: | Not applicable |
| Lower flammability limit: | Not applicable |
| Autoignition Temperature (°F) | No information available |

| | |
|--------------------------------|--------------------------|
| Autoignition Temperature (°C) | No information available |
| Decomposition Temperature (°F) | No information available |
| Decomposition Temperature (°C) | No information available |
| Partition coefficient | No information available |

10. STABILITY AND REACTIVITY

| | |
|------------------------------------|---|
| Reactivity | Not Applicable |
| Chemical Stability | Stable under normal conditions. Hazardous polymerisation does not occur. |
| Conditions to avoid | Keep away from open flames, hot surfaces, static electricity and sources of ignition. Sparks. Elevated temperature. |
| Incompatible Materials | Incompatible with strong acids and bases and strong oxidizing agents. |
| Hazardous Decomposition Products | Thermal decomposition can lead to release of irritating gases and vapors. |
| Possibility of hazardous reactions | None under normal conditions of use. |

11. TOXICOLOGICAL INFORMATION

Product Information Information on likely routes of exposure

Principal Routes of Exposure Eye contact, skin contact and inhalation.

Acute Toxicity Product Information

Repeated or prolonged exposure to organic solvents may lead to permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling vapors may be harmful or fatal.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

| | |
|---------------------|--|
| Eye contact | Contact with eyes may cause irritation. |
| Skin contact | May cause skin irritation and/or dermatitis. Prolonged skin contact may defat the skin and produce dermatitis. |
| Inhalation | Harmful by inhalation. High vapor / aerosol concentrations are irritating to the eyes, nose, throat and lungs and may cause headaches, dizziness, drowsiness, unconsciousness, and other central nervous system effects. |
| Ingestion | Harmful if swallowed. Ingestion may cause irritation to mucous membranes. Small amounts of this product |

Sensitization**Neurological Effects****Mutagenic Effects****Reproductive Effects****Developmental Effects****Target organ effects****STOT - single exposure****STOT - repeated exposure****Other adverse effects****Aspiration Hazard**

aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury, possibly progressing to death.

Respiratory sensitizer. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

No information available.

No information available.

Possible risk of impaired fertility. Possible risk of harm to the unborn child.

No information available.

Respiratory system, Eyes, Lungs.

May cause disorder and damage to the, Respiratory system.

Causes damage to organs through prolonged or repeated exposure if inhaled, Central nervous system, Causes damage to organs through prolonged or repeated exposure.

No information available.

May be harmful if swallowed and enters airways. Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury, possibly progressing to death.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

| | |
|--------------------------------------|------------|
| ATEmix (oral) | 3192 mg/kg |
| ATEmix (inhalation-dust/mist) | 7.4 mg/l |
| ATEmix (inhalation-vapor) | 232.1 mg/l |

Component Information

Caution - This mixture contains a substance not yet fully tested

| Chemical name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|--|----------------------|--------------------------|-----------------------------------|
| Polyamide epoxy | < 2000 mg/kg | >2000 mg/kg | = 5.0 mg/L (Rat) 4 h |
| Zinc phosphate 7779-90-0 | > 5000 mg/kg (Rat) | - | - |
| Benzyl alcohol 100-51-6 | = 1230 mg/kg (Rat) | = 2 g/kg (Rabbit) | = 8.8 mg/L (Rat) 4 h |
| Xylene 1330-20-7 | = 3500 mg/kg (Rat) | > 4350 mg/kg (Rabbit) | = 29.08 mg/L (Rat) 4 h |
| Propylene glycol monomethyl ether 107-98-2 | = 5000 mg/kg (Rat) | = 13 g/kg (Rabbit) | > 7559 ppm (Rat) 6 h |
| Ethyl benzene 100-41-4 | = 3500 mg/kg (Rat) | = 15400 mg/kg (Rabbit) | = 17.4 mg/L (Rat) 4 h |
| Triethylenetetramine 112-24-3 | = 2500 mg/kg (Rat) | = 550 mg/kg (Rabbit) | - |
| Solvent naphtha, petroleum, light aromatic 64742-95-6 | = 8400 mg/kg (Rat) | > 2000 mg/kg (Rabbit) | = 3400 ppm (Rat) 4 h |
| 1,2,4-Trimethylbenzene 95-63-6 | = 3280 mg/kg (Rat) | > 3160 mg/kg (Rabbit) | = 18 g/m ³ (Rat) 4 h |
| Phenol, 2,4,6-tris[(dimethylamino)methyl]- 90-72-2 | = 1200 mg/kg (Rat) | = 1280 mg/kg (Rat) | - |
| 1,3,5-Trimethylbenzene | = 5000 mg/kg (Rat) | - | = 24 g/m ³ (Rat) 4 h |

| | | | |
|------------------------------|----------------------|-------------------------|---|
| 108-67-8 | | | |
| Diethylbenzene 25340-17-4 | = 2050 mg/kg (Rat) | > 5000 mg/kg (Rabbit) | - |

Chronic Toxicity

Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

| Chemical name | IARC | NTP |
|---------------------|--------------------------------|-------|
| Silica, crystalline | 1 - Human Carcinogen | Known |
| Ethyl benzene | 2B - Possible Human Carcinogen | |

• Crystalline Silica has been determined to be carcinogenic to humans by IARC (1) when in respirable form. Risk of cancer depends on duration and level of inhalation exposure to spray mist or dust from sanding the dried paint.

Legend

IARC - International Agency for Research on Cancer

NTP - National Toxicity Program

OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

Product Information

Acute Toxicity to Fish

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

Persistence / Degradability

No information available.

Bioaccumulation

There is no data for this product.

Mobility in Environmental Media

No information available.

Ozone

Not applicable

Component Information

Acute Toxicity to FishXylene

LC50: 13.5 mg/L (Rainbow Trout - 96 hr.)

Ethyl benzene

LC50: 12.1 mg/L (Fathead Minnow - 96 hr.)

Acute Toxicity to Aquatic InvertebratesEthyl benzene

EC50: 1.8 mg/L (Daphnia magna - 48 hr.)

Acute Toxicity to Aquatic PlantsEthyl benzene

EC50: 4.6 mg/L (Green algae (Scenedesmus subspicatus), 72 hrs.)

13. DISPOSAL CONSIDERATIONS**Waste Disposal Method**

Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

Empty Container Warning

Emptied containers may retain product residue. Follow label warnings even after container is emptied. Residual vapors may explode on ignition.

14. TRANSPORT INFORMATION**TDG**

| | |
|-----------------------------------|-----------------------|
| Proper Shipping Name | Paint |
| Transport hazard class(es) | 3 |
| UN-No | UN1263 |
| Packing Group | III |
| Description | UN1263, Paint, 3, III |

ICAO / IATA

Contact the preparer for further information.

IMDG / IMO

Contact the preparer for further information.

15. REGULATORY INFORMATION**International Inventories****TSCA: United States**

Yes - All components are listed or exempt.

DSL: Canada

Yes - All components are listed or exempt.

National Pollutant Release Inventory (NPRI)**NPRI Parts 1- 4**

This product contains the following Parts 1-4 NPRI chemicals:

| <u>Chemical name</u> | <u>CAS No</u> | <u>Weight-%</u> | <u>NPRI Parts 1- 4</u> |
|------------------------|---------------|-----------------|------------------------|
| Xylene | 1330-20-7 | 5 - 10% | Listed |
| Ethyl benzene | 100-41-4 | 1 - 5% | Listed |
| 1,2,4-Trimethylbenzene | 95-63-6 | 0.5 - 1% | Listed |

NPRI Part 5

This product contains the following NPRI Part 5 Chemicals:

| <u>Chemical name</u> | <u>CAS No</u> | <u>Weight-%</u> | <u>NPRI Part 5</u> |
|--|---------------|-----------------|--------------------|
| Xylene | 1330-20-7 | 5 - 10% | Listed |
| Solvent naphtha, petroleum, light aromatic | 64742-95-6 | 1 - 5% | Listed |
| 1,2,4-Trimethylbenzene | 95-63-6 | 0.5 - 1% | Listed |
| 1,3,5-Trimethylbenzene | 108-67-8 | 0.1 - 0.25% | Listed |

WHMIS Regulatory Status

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR

16. OTHER INFORMATION**HMIS**

| | |
|----------------------------|----|
| Health hazards | 2* |
| Flammability | 3 |
| Reactivity: | 0 |
| Personal protection | - |

HMIS Legend

- 0 - Minimal Hazard
- 1 - Slight Hazard
- 2 - Moderate Hazard
- 3 - Serious Hazard
- 4 - Severe Hazard
- * - Chronic Hazard

X - Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada at http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked_questions-questions_posees-eng.php.

Prepared By Product Stewardship Department
Benjamin Moore & Co.
101 Paragon Drive
Montvale, NJ 07645
800-225-5554

Revision Date: 24-Aug-2023
Reason for revision Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

End of Safety Data Sheet