



# Benjamin Moore®

## SAFETY DATA SHEET

Revision date 17-Feb-2026

Revision Number 2

### 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Name** HP EPOXY MASTIC - CLEAR BASE  
**Product Code** HP4600-9B  
**Alternate Product Code** UA449B  
**Product Class** epoxy  
**Color** Clear  
**Recommended use** Paint  
**Restrictions on use** No information available

**Manufacturer**  
 Benjamin Moore & Co.  
 101 Paragon Drive  
 Montvale, NJ 07645  
 Phone: 1-866-708-9180  
 www.benjaminmoore.com

**Emergency Telephone**  
 CHEMTREC: +1 703-741-5970 / 1-800-424-9300  
 +1 703-527-3887 (outside US & Canada)

### 2. HAZARDS IDENTIFICATION

**Classification**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Respiratory sensitization	Category 1
Skin sensitization	Category 1
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1A
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 1
Aspiration hazard	Category 1
Flammable liquids	Category 3

**Label elements**

**Danger**

**Hazard statements**  
 Causes skin irritation

Causes serious eye irritation  
May cause allergy or asthma symptoms or breathing difficulties if inhaled  
May cause an allergic skin reaction  
May cause genetic defects  
May cause cancer  
Suspected of damaging fertility or the unborn child  
May cause respiratory irritation. May cause drowsiness or dizziness  
Causes damage to organs through prolonged or repeated exposure  
May be fatal if swallowed and enters airways  
Flammable liquid and vapor



**Appearance** liquid

**Odor** solvent

#### **Precautionary Statements - Prevention**

Obtain special instructions before use  
Do not handle until all safety precautions have been read and understood  
Use personal protective equipment as required  
Wash face, hands and any exposed skin thoroughly after handling  
In case of inadequate ventilation wear respiratory protection  
Contaminated work clothing must not be allowed out of the workplace  
Do not breathe dust  
Do not eat, drink or smoke when using this product  
Use only outdoors or in a well-ventilated area  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
Keep container tightly closed  
Ground and bond container and receiving equipment  
Use only non-sparking tools  
Take action to prevent static discharges  
Keep cool  
Wear protective gloves, protective clothing, eye protection and face protection

#### **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

##### **Eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

##### **Skin**

If skin irritation or rash occurs: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

##### **Inhalation**

If experiencing respiratory symptoms: Call a POISON CENTER or doctor

IF INHALED: Remove person to fresh air and keep comfortable for breathing

**Ingestion**

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

**Fire**

In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Precautionary Statements - Storage**

Store locked up

Store in a well-ventilated place. Keep container tightly closed

**Precautionary Statements - Disposal**

Dispose of contents and container in accordance with local, regional, national, and international regulations as applicable

**Hazards not otherwise classified (HNOC)**

Not applicable

**Other information**

No information available

**IMPORTANT:** Designed to be mixed with other components. Mixture will have hazards of all components. Before opening packages, read all warning labels. Follow all precautions.

### 3. COMPOSITION INFORMATION ON COMPONENTS

Chemical name	CAS No.	Weight-%
Polyamide epoxy	-	20 - 25
Silica, crystalline	14808-60-7	10 - 15
Benzyl alcohol	100-51-6	10 - 15
Talc	14807-96-6	10 - 15
Xylene	1330-20-7	5 - 10
Propylene glycol monomethyl ether	107-98-2	1 - 5
Ethyl benzene	100-41-4	1 - 5
Triethylenetetramine	112-24-3	1 - 5
Solvent naphtha, petroleum, light aromatic	64742-95-6	1 - 5
1,2,4-Trimethylbenzene	95-63-6	0.5 - 1
Phenol, 2,4,6-tris[(dimethylamino)methyl]-	90-72-2	0.1 - 0.5
1,3,5-Trimethylbenzene	108-67-8	0.1 - 0.5
Diethylbenzene	25340-17-4	0.1 - 0.5

### 4. FIRST AID MEASURES

**Description of first aid measures****General Advice**

If symptoms persist, call a physician. Show this safety data sheet to the doctor in attendance.

**Eye Contact**

Immediately flush with plenty of water. After initial flushing, remove any contact

	lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.
<b>Skin Contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician. Wash clothing before reuse. Destroy contaminated articles such as shoes.
<b>Inhalation</b>	Move to fresh air. If symptoms persist, call a physician. If not breathing, give artificial respiration. Call a physician immediately.
<b>Ingestion</b>	Clean mouth with water and afterwards drink plenty of water. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Consult a physician.
<b>Protection Of First-Aiders</b>	Use personal protective equipment.
<b>Most Important Symptoms/Effects</b>	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause allergic skin reaction.
<b>Notes To Physician</b>	Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

<b>Flammable Properties</b>	Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause flash fire.
<b>Suitable Extinguishing Media</b>	Foam, dry powder or water. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
<b>Protective equipment and precautions for firefighters</b>	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.
<b>Hazardous combustion products</b>	Burning may result in carbon dioxide, carbon monoxide and other combustion products of varying composition which may be toxic and/or irritating.
<b>Special Provisions</b>	Flammable. Flash back possible over considerable distance. Keep product and empty container away from heat and sources of ignition. Closed containers may rupture if exposed to fire or extreme heat. Thermal decomposition can lead to release of irritating gases and vapors.
<b>Sensitivity to mechanical impact</b>	No
<b>Sensitivity to static discharge</b>	Yes
<b>Flash Point Data</b>	
Flash point (°F)	80
Flash Point (°C)	27
Method	PMCC

**Flammability Limits In Air**

**Lower flammability limit:** No data available  
**Upper flammability limit:** No data available

**NFPA**

**Health hazards** 2  
**Flammability** 3  
**Stability** 0  
**Special:** Not Applicable

**NFPA Legend**

- 0 - Not Hazardous
- 1 - Slightly
- 2 - Moderate
- 3 - High
- 4 - Severe

*The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.*

*Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at [www.nfpa.org](http://www.nfpa.org).*

**6. ACCIDENTAL RELEASE MEASURES**

<b>Personal Precautions</b>	Remove all sources of ignition. Take precautions to prevent flashback. Ground and bond all containers and handling equipment. Take precautionary measures against static discharges. Ensure adequate ventilation. Avoid contact with skin, eyes and clothing. Use personal protective equipment.
<b>Other Information</b>	Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages cannot be contained.
<b>Environmental precautions</b>	See Section 12 for additional Ecological Information.
<b>Methods for Cleaning Up</b>	Dam up. Soak up with inert absorbent material. Use a non-sparking or explosion proof means to transfer material to a sealed, appropriate container for disposal. Clean contaminated surface thoroughly.

**7. HANDLING AND STORAGE**

<b>Handling</b>	<p>Avoid contact with skin, eyes and clothing. Wear personal protective equipment. Do not breathe vapors or spray mist. Use only in ventilated areas. Prevent vapor build-up by providing adequate ventilation during and after use.</p> <p>Take precautionary measures against static discharges. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Ignition and/or flash back may</p>
-----------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

occur.

**Storage** Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat. Keep away from open flames, hot surfaces and sources of ignition. Keep in properly labeled containers. Keep out of the reach of children.

**Incompatible Materials** Incompatible with strong acids and bases and strong oxidizing agents.

**Technical measures/Precautions** Ensure adequate ventilation. Use only where airflow will keep vapors from building up in or near the work area in adjoining rooms. Comply with all national, state, and local codes pertaining to the storage, handling, dispensing and disposal of flammable liquids.

Dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. All equipment should be non-sparking and explosion proof. Use explosion proof electrical equipment for ventilation, lighting and material handling.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Exposure Limits**

Chemical name	ACGIH TLV	OSHA PEL
Silica, crystalline	TWA: 0.025 mg/m <sup>3</sup> respirable particulate matter	TWA: 50 µg/m <sup>3</sup> TWA: 50 µg/m <sup>3</sup> excludes construction work, agricultural operations, and exposures that result from the processing of sorptive clays (vacated) TWA: 0.1 mg/m <sup>3</sup> respirable dust : (250)/(%SiO <sub>2</sub> + 5) mppcf TWA respirable fraction : (10)/(%SiO <sub>2</sub> + 2) mg/m <sup>3</sup> TWA respirable fraction
Talc	TWA: 2 mg/m <sup>3</sup> respirable particulate matter containing no Asbestos and <1% Crystalline silica	TWA: 20 mppcf if 1% Quartz or more, use Quartz limit (vacated) TWA: 2 mg/m <sup>3</sup> respirable dust <1% Crystalline silica, containing no Asbestos TWA: 20 mppcf if 1% Quartz or more, use Quartz limit
Xylene	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m <sup>3</sup> (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m <sup>3</sup>
Propylene glycol monomethyl ether	TWA: 50 ppm STEL: 100 ppm	(vacated) TWA: 100 ppm (vacated) TWA: 360 mg/m <sup>3</sup> (vacated) STEL: 150 ppm (vacated) STEL: 540 mg/m <sup>3</sup>
Ethyl benzene	TWA: 20 ppm pOt	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m <sup>3</sup>

		(vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m <sup>3</sup>
1,2,4-Trimethylbenzene	TWA: 10 ppm	(vacated) TWA: 25 ppm (vacated) TWA: 125 mg/m <sup>3</sup>
1,3,5-Trimethylbenzene	TWA: 10 ppm	(vacated) TWA: 25 ppm (vacated) TWA: 125 mg/m <sup>3</sup>

**Legend**

ACGIH - American Conference of Governmental Industrial Hygienists Exposure Limits

OSHA - Occupational Safety & Health Administration Exposure Limits

N/E - Not Established

**Appropriate engineering controls**

**Engineering Measures**                      Ensure adequate ventilation, especially in confined areas.

**Personal protective equipment**

**Eye/Face Protection**                      Safety glasses with side-shields. If splashes are likely to occur, wear:. Tightly fitting safety goggles.

**Skin Protection**                              Long sleeved clothing. Protective gloves.

**Respiratory Protection**                      Use only with adequate ventilation. In operations where exposure limits are exceeded, use a NIOSH approved respirator that has been selected by a technically qualified person for the specific work conditions. When spraying the product or applying in confined areas, wear a NIOSH approved respirator specified for paint spray or organic vapors.

**Hygiene Measures**                              Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>Appearance</b>	liquid
<b>Odor</b>	solvent
<b>Odor threshold</b>	No information available
<b>Density (lbs./gal)</b>	10.9 - 11.3
<b>Specific Gravity</b>	1.30 - 1.36
<b>pH</b>	No information available
<b>Viscosity (cps)</b>	No information available
<b>Solubility(ies)</b>	No information available
<b>Water solubility</b>	No information available
<b>Evaporation Rate</b>	No information available
<b>Vapor pressure @20 °C (kPa)</b>	No information available
<b>Relative vapor density</b>	No information available
<b>Wt. % Solids</b>	80 - 90
<b>Vol. % Solids</b>	70 - 80
<b>Wt. % Volatiles</b>	10 - 20
<b>Vol. % Volatiles</b>	20 - 30
<b>VOC Regulatory Limit (g/L)</b>	< 250
<b>Boiling Point (°F)</b>	248
<b>Boiling Point (°C)</b>	120
<b>Freezing point (°F)</b>	No information available
<b>Freezing Point (°C)</b>	No information available

Flash point (°F)	80
Flash Point (°C)	27
Method	PMCC
Flammability	Not applicable
Upper flammability limit:	No data available
Lower flammability limit:	No data available
Autoignition Temperature (°F)	No information available
Autoignition Temperature (°C)	No information available
Decomposition Temperature (°F)	No information available
Decomposition Temperature (°C)	No information available
Partition coefficient	No information available

## 10. STABILITY AND REACTIVITY

Reactivity	No data available
Chemical Stability	Stable under normal conditions. Hazardous polymerisation does not occur.
Conditions to avoid	Keep away from open flames, hot surfaces, static electricity and sources of ignition. Sparks. Elevated temperature.
Incompatible Materials	Incompatible with strong acids and bases and strong oxidizing agents.
Hazardous decomposition products	Thermal decomposition can lead to release of irritating gases and vapors.
Possibility of hazardous reactions	None under normal conditions of use.

## 11. TOXICOLOGICAL INFORMATION

### Product Information

### Information on likely routes of exposure

**Principal Routes of Exposure** Eye contact, skin contact and inhalation.

### Acute Toxicity

**Product Information** Repeated or prolonged exposure to organic solvents may lead to permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling vapors may be harmful or fatal.

### Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** No information available

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Eye contact** Contact with eyes may cause irritation.

<b>Skin contact</b>	May cause skin irritation and/or dermatitis. Prolonged skin contact may defat the skin and produce dermatitis.
<b>Ingestion</b>	Harmful if swallowed. Ingestion may cause irritation to mucous membranes. Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury, possibly progressing to death.
<b>Inhalation</b>	Harmful by inhalation. High vapor / aerosol concentrations are irritating to the eyes, nose, throat and lungs and may cause headaches, dizziness, drowsiness, unconsciousness, and other central nervous system effects.
<b>Sensitization</b>	Respiratory sensitizer May cause allergy or asthma symptoms or breathing difficulties if inhaled May cause an allergic skin reaction
<b>Neurological effects</b>	No information available.
<b>Mutagenic Effects</b>	No information available.
<b>Reproductive Effects</b>	Possible risk of impaired fertility. Possible risk of harm to the unborn child.
<b>Developmental toxicity</b>	No information available.
<b>Target organ effects</b>	Respiratory system. Eyes. Lungs.
<b>STOT - repeated exposure</b>	Causes damage to organs through prolonged or repeated exposure if inhaled, Central nervous system, Causes damage to organs through prolonged or repeated exposure.
<b>STOT - single exposure</b>	May cause disorder and damage to the, Respiratory system.
<b>Other adverse effects</b>	No information available.
<b>Aspiration Hazard</b>	May be harmful if swallowed and enters airways. Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury, possibly progressing to death.

**Numerical measures of toxicity**

The following ATE values have been calculated for the mixture

<b>ATEmix (oral)</b>	3478 mg/kg
<b>ATEmix (inhalation-dust/mist)</b>	11.3 mg/L
<b>ATEmix (inhalation-vapor)</b>	716 mg/L

**Component Information**

Caution - This mixture contains a substance not yet fully tested

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Polyamide epoxy	< 2000 mg/kg	>2000 mg/kg	= 5.0 mg/L ( Rat ) 4 h
Benzyl alcohol 100-51-6	= 1230 mg/kg ( Rat )	= 2 g/kg ( Rabbit )	> 4178 mg/m <sup>3</sup> ( Rat ) 4 h
Talc 14807-96-6	> 5000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	-
Xylene 1330-20-7	= 3500 mg/kg ( Rat ) = 4820 mg/kg ( Rat )	> 4350 mg/kg ( Rabbit ) > 2000 mg/kg ( Rabbit )	= 29.08 mg/L ( Rat ) 4 h > 5.04 mg/L ( Rat ) 4 h
Propylene glycol monomethyl ether 107-98-2	= 5000 mg/kg ( Rat )	= 13 g/kg ( Rabbit )	> 7559 ppm ( Rat ) 6 h
Ethyl benzene 100-41-4	= 3500 mg/kg ( Rat ) = 4820 mg/kg ( Rat )	= 15400 mg/kg ( Rabbit ) > 2000 mg/kg ( Rabbit )	= 17.4 mg/L ( Rat ) 4 h > 5.04 mg/L ( Rat ) 4 h
Triethylenetetramine 112-24-3	= 1716.2 mg/kg ( Rat )	= 1720 mg/kg ( Rabbit ) = 1465.4 mg/kg ( Rabbit )	-

		1000 - 2000 mg/kg ( Rat )	
Solvent naphtha, petroleum, light aromatic 64742-95-6	= 8400 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	= 3400 ppm ( Rat ) 4 h
1,2,4-Trimethylbenzene 95-63-6	= 3280 mg/kg ( Rat ) > 3492 mg/kg ( Rat ) = 6984 mg/kg ( Rat ) = 8970 mg/kg ( Rat )	> 3440 mg/kg ( Rat ) > 3160 mg/kg ( Rabbit )	= 18 g/m <sup>3</sup> ( Rat ) 4 h > 6193 mg/m <sup>3</sup> ( Rat ) 4 h
Phenol, 2,4,6-tris[(dimethylamino)methyl]- 90-72-2	= 1200 mg/kg ( Rat )	= 1280 mg/kg ( Rat )	-
1,3,5-Trimethylbenzene 108-67-8	> 3492 mg/kg ( Rat ) = 6984 mg/kg ( Rat ) = 8970 mg/kg ( Rat )	> 3160 mg/kg ( Rabbit )	= 24 g/m <sup>3</sup> ( Rat ) 4 h > 6193 mg/m <sup>3</sup> ( Rat ) 4 h
Diethylbenzene 25340-17-4	= 2050 mg/kg ( Rat )	> 5000 mg/kg ( Rabbit )	> 2100 ppm ( Rat ) 7 h

### Chronic Toxicity

### Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:

Chemical name	IARC	NTP	OSHA
Silica, crystalline	Group 1 - Carcinogenic to humans	Known Human Carcinogen	X
Talc			X
Xylene	Group 3 - Unclassifiable as to carcinogenicity in humans		
Ethyl benzene	Group 2B - Possibly carcinogenic to humans		X

• Crystalline Silica has been determined to be carcinogenic to humans by IARC (1) when in respirable form. Risk of cancer depends on duration and level of inhalation exposure to spray mist or dust from sanding the dried paint.

### Legend

IARC - International Agency for Research on Cancer

NTP - National Toxicity Program

OSHA - Occupational Safety & Health Administration

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

**Product Information****Acute Toxicity to Fish**

No information available

**Acute Toxicity to Aquatic Invertebrates**

No information available

**Acute Toxicity to Aquatic Plants**

No information available

**Persistence and degradability**

No information available.

**Bioaccumulation**

There is no data for this product.

**Mobility**

No information available.

**Hazardous to the ozone layer**

Not classified

**Component Information****Acute Toxicity to Fish**Xylene

LC50: 13.5 mg/L (Rainbow Trout - 96 hr.)

Ethyl benzene

LC50: 12.1 mg/L (Fathead Minnow - 96 hr.)

**Acute Toxicity to Aquatic Invertebrates**Ethyl benzene

EC50: 1.8 mg/L (Daphnia magna - 48 hr.)

**Acute Toxicity to Aquatic Plants**Ethyl benzene

EC50: 4.6 mg/L (Green algae (Scenedesmus subspicatus), 72 hrs.)

**13. DISPOSAL CONSIDERATIONS****Waste Disposal Method**


Dispose of in accordance with federal, state, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

**Empty Container Warning**

Emptied containers may retain product residue. Follow label warnings even after container is emptied. Residual vapors may explode on ignition.



**US State Regulations****California Proposition 65**

 **WARNING:** This product can expose you to chemicals including Crystalline Silica, which are known to the State of California to cause cancer, and Toluene which are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**U.S. State Right-to-Know Regulations**

Chemical name	Massachusetts	New Jersey	Pennsylvania
Zinc phosphate		X	X
Silica, crystalline	X	X	X
Benzyl alcohol	X		X
Talc	X	X	X
Xylene	X	X	X
Propylene glycol monomethyl ether	X	X	X
Ethyl benzene	X	X	X

**Legend**

X - Listed

**16. OTHER INFORMATION****HMIS**

Health hazards	2*
Flammability	3
Reactivity:	0
Personal protection	-

**HMIS Legend**

- 0 - Minimal Hazard
- 1 - Slight Hazard
- 2 - Moderate Hazard
- 3 - Serious Hazard
- 4 - Severe Hazard
- \* - Chronic Hazard

X - Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN.

PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**Prepared By** Product Stewardship Department  
Benjamin Moore & Co.  
101 Paragon Drive  
Montvale, NJ 07645  
800-225-5554

**Revision date** 17-Feb-2026  
**Revision Note** Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

**End of Safety Data Sheet**