



SAFETY DATA SHEET

Revision Date: 24-May-2016

Revision Number: 1

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name RUBBER-BASED SWIMMING POOL PAINT SATIN WHITE
Product Code RP-2710F
Alternate Product Code XF0701
Product Class SOLVENT THINNED PAINT
Color White
Recommended use Paint
Restrictions on use No information available

Manufactured For

Benjamin Moore & Co., Limited
8775 Keele Street
Concord ON L4K 2N1
Phone: 1-800-361-5898
insl-x.ca

Manufacturer

Benjamin Moore & Co.
101 Paragon Drive
Montvale, NJ 07645
Phone: 800-225-5554
insl-x.com

Emergency Telephone Number(s)

CANUTEC: 613-996-6666

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the Hazardous Products Regulations (HPR: SOR/2015-17)

Skin corrosion/irritation	Category 2
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1B
Specific target organ toxicity (repeated exposure)	Category 2
Flammable liquids	Category 3

Label elements

Danger

Hazard statements

Causes skin irritation
May cause genetic defects
May cause cancer
May cause damage to organs through prolonged or repeated exposure
Flammable liquid and vapor



Appearance liquid

Odor solvent

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Wash face, hands and any exposed skin thoroughly after handling
Do not breathe dust/fume/mist/vapors/spray
Keep away from heat/sparks/open flames/hot surfaces, no smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Use explosion-proof electrical/ventilating/lighting/equipment
Use only non-sparking tools
Take precautionary measures against static discharge

Precautionary Statements - Response

If exposed or concerned get medical attention

Skin

If skin irritation occurs get medical attention
If on skin (or hair) take off immediately all contaminated clothing. Rinse skin with water
Wash contaminated clothing before reuse

Fire

In case of fire use CO₂, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up
Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other information

No information available

3. COMPOSITION INFORMATION ON COMPONENTS

Chemical Name	CAS-No	Weight % (max)
Nepheline syenite	37244-96-5	30 - 60%
Xylene	1330-20-7	7 - 13%
Titanium dioxide	13463-67-7	7 - 13%
Solvent naphtha (petroleum), heavy aromatic	64742-94-5	1 - 5%
Ethyl benzene	100-41-4	1 - 5%
Chlorinated paraffin	63449-39-8	1 - 5%
4-Chlorobenzotrifluoride	98-56-6	1 - 5%
Silica, amorphous	7631-86-9	0.5 - 1%

Naphthalene	91-20-3	0.5 - 1%
Naphtha (petroleum), hydrosulfurized heavy	64742-82-1	0.1 - 0.25%

4. FIRST AID MEASURES

General Advice	If symptoms persist, call a physician. Show this safety data sheet to the doctor in attendance.
Eye Contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.
Skin Contact	Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
Inhalation	Move to fresh air. If symptoms persist, call a physician. If not breathing, give artificial respiration. Call a physician immediately.
Ingestion	Clean mouth with water and afterwards drink plenty of water. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Consult a physician.
Protection Of First-Aiders	Use personal protective equipment.
Most Important Symptoms/Effects	No information available.
Notes To Physician	Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Flammable Properties	Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause flash fire.
Suitable Extinguishing Media	Foam, dry powder or water. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Protective Equipment And Precautions For Firefighters	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.
Hazardous Combustion Products	Burning may result in carbon dioxide, carbon monoxide and other combustion products of varying composition which may be toxic and/or irritating.
Specific Hazards Arising From The Chemical	Flammable. Flash back possible over considerable distance. Keep product and empty container away from heat and sources of ignition. Closed containers may

rupture if exposed to fire or extreme heat. Thermal decomposition can lead to release of irritating gases and vapors.

Sensitivity To Mechanical Impact

No

Sensitivity To Static Discharge

Yes

Flash Point Data

Flash Point (°F)

80

Flash Point (°C)

27

Flash Point Method

PMCC

Flammability Limits In Air

Lower Explosion Limit

Not available

Upper Explosion Limit

Not available

NFPA Health: 2 Flammability: 3 Instability: 0 Special: Not Applicable

NFPA Legend

- 0 - Not Hazardous
- 1 - Slightly
- 2 - Moderate
- 3 - High
- 4 - Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

Remove all sources of ignition. Take precautions to prevent flashback. Ground and bond all containers and handling equipment. Take precautionary measures against static discharges. Ensure adequate ventilation. Avoid contact with skin, eyes and clothing. Use personal protective equipment.

Other Information

Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages cannot be contained.

Environmental Precautions

See Section 12 for additional Ecological Information.

Methods For Clean-Up

Dam up. Soak up with inert absorbent material. Use a non-sparking or explosion proof means to transfer material to a sealed, appropriate container for disposal. Clean contaminated surface thoroughly.

7. HANDLING AND STORAGE

Handling

Avoid contact with skin, eyes and clothing. Wear personal protective equipment. Do not breathe vapors or spray mist. Use only in ventilated areas. Prevent vapor build-up by providing adequate ventilation during and after use.

Take precautionary measures against static discharges. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Ignition and/or flash back may occur.

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat. Keep away from open flames, hot surfaces and sources of ignition. Keep in properly labeled containers. Keep out of the reach of children.

Incompatible Materials

Incompatible with strong acids and bases and strong oxidizing agents.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits

Chemical Name	ACGIH	Alberta	British Columbia	Ontario	Quebec
Nepheline syenite	N/E	N/E	N/E	10 mg/m ³ - TWA	N/E
Xylene	100 ppm - TWA 150 ppm - STEL	100 ppm - TWA 434 mg/m ³ - TWA 150 ppm - STEL 651 mg/m ³ - STEL	100 ppm - TWA 150 ppm - STEL	100 ppm - TWA 150 ppm - STEL	100 ppm - TWAEV 434 mg/m ³ - TWAEV 150 ppm - STEV 651 mg/m ³ - STEV
Titanium dioxide	10 mg/m ³ - TWA	10 mg/m ³ - TWA	10 mg/m ³ - TWA 3 mg/m ³ - TWA	10 mg/m ³ - TWA	10 mg/m ³ - TWAEV
Ethyl benzene	20 ppm - TWA	100 ppm - TWA 434 mg/m ³ - TWA 125 ppm - STEL 543 mg/m ³ - STEL	20 ppm - TWA	20 ppm - TWA	100 ppm - TWAEV 434 mg/m ³ - TWAEV 125 ppm - STEV 543 mg/m ³ - STEV
4-Chlorobenzotrifluoride	2.5 mg/m ³ - TWA	2.5 mg/m ³ - TWA	2.5 mg/m ³ - TWA	2.5 mg/m ³ - TWA	2.5 mg/m ³ - TWAEV
Naphthalene	10 ppm - TWA Skin	10 ppm - TWA 52 mg/m ³ - TWA 15 ppm - STEL 79 mg/m ³ - STEL Substance may be readily absorbed through intact skin	10 ppm - TWA 15 ppm - STEL Skin absorption can contribute to overall exposure.	10 ppm - TWA 15 ppm - STEL Danger of cutaneous absorption	10 ppm - TWAEV 52 mg/m ³ - TWAEV 15 ppm - STEV 79 mg/m ³ - STEV

Legend

ACGIH - American Conference of Governmental Industrial Hygienists
Alberta - Alberta Occupational Exposure Limits
British Columbia - British Columbia Occupational Exposure Limits
Ontario - Ontario Occupational Exposure Limits
Quebec - Quebec Occupational Exposure Limits
N/E - Not established

Engineering Measures

Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/Face Protection

Safety glasses with side-shields. If splashes are likely to occur, wear: Tightly fitting safety goggles

Skin Protection

Protective gloves and impervious clothing.

Respiratory Protection

Use only with adequate ventilation. In operations where exposure limits are exceeded, use a NIOSH approved respirator that has been selected by a technically qualified person for the specific work conditions. When spraying the product or applying in confined areas, wear a NIOSH approved respirator specified for paint spray or organic vapors.

Hygiene Measures

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	liquid
Odor	solvent
Odor Threshold	No information available
Density (lbs/gal)	12.8 - 12.9
Specific Gravity	1.53 - 1.55
pH	No information available
Viscosity (cps)	No information available
Solubility	No information available
Water Solubility	No information available
Evaporation Rate	No information available
Vapor Pressure	No information available
Vapor Density	No information available
Wt. % Solids	70 - 80
Vol. % Solids	55 - 65
Wt. % Volatiles	20 - 30
Vol. % Volatiles	35 - 45
VOC Regulatory Limit (g/L)	< 340
Boiling Point (°F)	279
Boiling Point (°C)	137
Freezing Point (°F)	No information available
Freezing Point (°C)	No information available
Flash Point (°F)	80
Flash Point (°C)	27
Flash Point Method	PMCC
Flammability (solid, gas)	Not applicable
Upper Explosion Limit	Not applicable
Lower Explosion Limit	Not applicable
Autoignition Temperature (°F)	No information available
Autoignition Temperature (°C)	No information available
Decomposition Temperature (°F)	No information available
Decomposition Temperature (°C)	No information available
Partition Coefficient (n-octanol/water)	No information available

10. STABILITY AND REACTIVITY

Reactivity	Not Applicable
Chemical Stability	Stable under normal conditions. Hazardous polymerisation does not occur.
Conditions To Avoid	Keep away from open flames, hot surfaces, static electricity and sources of ignition. Sparks. Elevated temperature.
Incompatible Materials	Incompatible with strong acids and bases and strong oxidizing agents.
Hazardous Decomposition Products	Thermal decomposition can lead to release of irritating gases and vapors.
Possibility Of Hazardous Reactions	None under normal conditions of use.

11. TOXICOLOGICAL INFORMATION

Product Information

Information on likely routes of exposure

Principal Routes of Exposure

Eye contact, skin contact and inhalation.

Acute Toxicity

Product Information

Repeated or prolonged exposure to organic solvents may lead to permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling vapors may be harmful or fatal.

Information on toxicological effects

Symptoms

No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Eye contact

Contact with eyes may cause irritation.

Skin contact

May cause skin irritation and/or dermatitis. Prolonged skin contact may defat the skin and produce dermatitis.

Inhalation

Harmful by inhalation. High vapor / aerosol concentrations are irritating to the eyes, nose, throat and lungs and may cause headaches, dizziness, drowsiness, unconsciousness, and other central nervous system effects.

Ingestion

Harmful if swallowed. Ingestion may cause irritation to mucous membranes. Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury, possibly progressing to death.

Sensitization:

No information available.

Neurological Effects

No information available.

Mutagenic Effects	No information available.
Reproductive Effects	No information available.
Developmental Effects	No information available.
Target Organ Effects	No information available.
STOT - single exposure	May cause disorder and damage to the. Respiratory system.
STOT - repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Other adverse effects	No information available.
Aspiration Hazard	May be harmful if swallowed and enters airways. Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury, possibly progressing to death.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	14904 mg/kg
ATEmix (dermal)	6607 mg/kg
ATEmix (inhalation-dust/mist)	9.6 mg/L

Component

Xylene

LD50 Oral: 4300 mg/kg (Rat)
LD50 Dermal: > 1700 mg/kg (Rabbit)
LC50 Inhalation (Vapor): 5000 ppm (Rat, 4 hr.)

Titanium dioxide

LD50 Oral: > 10000 mg/kg (Rat)
Solvent naphtha (petroleum), heavy aromatic
LD50 Dermal: > 2 mL/kg (Rabbit)
LC50 Inhalation (Vapor): > 590 mg/m³ (Rat, 4 hr.)

Ethyl benzene

LD50 Oral: mg/kg (Rat)
LD50 Dermal: > mg/kg (Rabbit)
LC50 Inhalation (Vapor): mg/m³ (Rat, 2 hr.)

Chlorinated paraffin

LD50 Oral: 26100 mg/kg (Rat)
LD50 Dermal: > 10 mL/kg (Rabbit)

4-Chlorobenzotrifluoride

LD50 Oral: (Rat) mg/kg
LD50 Dermal: mg/kg (Rabbit)
LC50 Inhalation (Vapor): mg/L (Rat, 4 hr.)

Silica, amorphous

LD50 Oral: > 5000 mg/kg (Rat)
LD50 Dermal: 2,000 mg/kg (Rabbit)
LC50 Inhalation (Dust): > 2 mg/L

Naphthalene

LD50 Oral: 969 mg/kg (Rat)
LD50 Dermal: > 20,000 mg/kg (Rabbit)
LC50 Inhalation (Vapor): > 340 mg/m³ (Rat, 1 hr.)

Chronic Toxicity

Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:

Chemical Name	IARC	NTP	OSHA Carcinogen
Titanium dioxide	2B - Possible Human Carcinogen		Listed
Ethyl benzene	2B - Possible Human Carcinogen		Listed
Chlorinated paraffin	2B - Possible Human Carcinogen		Listed
Silica, amorphous		Reasonably Anticipated Human Carcinogen	Listed
Naphthalene	2B - Possible Human Carcinogen	Reasonably Anticipated Human Carcinogen	Listed

Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

Legend

IARC - International Agency for Research on Cancer

NTP - National Toxicity Program

OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

Product Information

Acute Toxicity to Fish

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

Persistence / Degradability

No information available.

Bioaccumulation / Accumulation

No information available.

Mobility in Environmental Media

No information available.

Ozone

No information available

Component

Acute Toxicity to Fish

Xylene

LC50: 13.5 mg/L (Rainbow Trout - 96 hr.)

Titanium dioxide

LC50: > 1000 mg/L (Fathead Minnow - 96 hr.)

Ethyl benzene

LC50: 12.1 mg/L (Fathead Minnow - 96 hr.)

Acute Toxicity to Aquatic Invertebrates

Ethyl benzene

EC50: 1.8 mg/L (Daphnia magna - 48 hr.)

Acute Toxicity to Aquatic Plants

Ethyl benzene

EC50: 4.6 mg/L (Green algae (Scenedesmus subspicatus), 72 hrs.)

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method

Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

Empty Container Warning

Emptied containers may retain product residue. Follow label warnings even after container is emptied. Residual vapors may explode on ignition.

14. TRANSPORT INFORMATION

TDG

Proper Shipping Name

Paint

Hazard Class

3

UN-No

UN1263

Packing Group

III

Description

UN1263, Paint, 3, III

ICAO / IATA

Contact the preparer for further information.

IMDG / IMO

Contact the preparer for further information.

15. REGULATORY INFORMATION

International Inventories

TSCA: United States Yes - All components are listed or exempt.
DSL: Canada Yes - All components are listed or exempt.

National Pollutant Release Inventory (NPRI)

NPRI Parts 1- 4

This product contains the following Parts 1-4 NPRI chemicals:

<u>Chemical Name</u>	<u>CAS-No</u>	<u>Weight % (max)</u>	<u>NPRI Parts 1- 4</u>
Xylene	1330-20-7	7 - 13%	Listed
Solvent naphtha (petroleum), heavy aromatic	64742-94-5	1 - 5%	Listed
Ethyl benzene	100-41-4	1 - 5%	Listed
4-Chlorobenzotrifluoride	98-56-6	1 - 5%	Listed
Naphthalene	91-20-3	0.5 - 1%	Listed

NPRI Part 5

This product contains the following NPRI Part 5 Chemicals:

<u>Chemical Name</u>	<u>CAS-No</u>	<u>Weight % (max)</u>	<u>NPRI Part 5</u>
Xylene	1330-20-7	7 - 13%	Listed
Solvent naphtha (petroleum), heavy aromatic	64742-94-5	1 - 5%	Listed

WHMIS Regulatory Status

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

16. OTHER INFORMATION

HMIS - Health: 2* Flammability: 3 Reactivity: 0 PPE: -

HMIS Legend

- 0 - Minimal Hazard
- 1 - Slight Hazard
- 2 - Moderate Hazard
- 3 - Serious Hazard
- 4 - Severe Hazard
- * - Chronic Hazard

X - Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @ http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked_questions-questions_posees-eng.php.

Prepared By Product Stewardship Department
Benjamin Moore & Co.
101 Paragon Drive
Montvale, NJ 07645
855-724-6802

Revision Date: 24-May-2016
Reason For Revision Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

END OF SAFETY DATA SHEET