



Revision Date: 13-Jul-2018 Revision Number: 3

## 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name
Product Code
Alternate Product Code

Alternate Product Code Product Class

Color

Recommended use

Restrictions on use

MOISTURE TOLERANT QUICK SET EPOXY SEALER CLEAR

V156-00

V15600 SEALER Clear

Industrial paint

No information available

Manufacturer

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 Phone: 1-866-708-9180

corotechcoatings.com

**Emergency Telephone** 

CHEMTREC (US): 800-424-9300

CHEMTREC (outside US): (703)-527-3887

## 2. HAZARDS IDENTIFICATION

### Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

| Skin corrosion/irritation | Category 2 |
|---------------------------|------------|
| Skin sensitization        | Category 1 |

### Label elements

### Warning

#### Hazard statements

Causes skin irritation

May cause an allergic skin reaction



Revision Date: 13-Jul-2018

Appearance liquid Odor solvent

#### **Precautionary Statements - Prevention**

Wash face, hands and any exposed skin thoroughly after handling Wear protective gloves/protective clothing/eye protection/face protection Avoid breathing dust/fume/gas/mist/vapors/spray Contaminated work clothing should not be allowed out of the workplace

#### Skin

IF ON SKIN: Wash with plenty of soap and water Take off contaminated clothing and wash before reuse If skin irritation or rash occurs: Get medical advice/attention

### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

### Hazards not otherwise classified (HNOC)

Not applicable

#### Other information

No information available

#### Other hazards

**IMPORTANT:** Designed to be mixed with other components. Mixture will have hazards of all components. Before opening packages, read all warning labels. Follow all precautions.

**CAUTION:** All floor coatings may become slippery when wet. Where non-skid characteristics are desired, use an appropriate anti-slip aggregate.

## 3. COMPOSITION INFORMATION ON COMPONENTS

| Chemical name                     | CAS No.   | Weight-% |
|-----------------------------------|-----------|----------|
| Propylene glycol monomethyl ether | 107-98-2  | 5        |
| Tetraethylenepentamine            | 112-57-2  | 0.5      |
| Pentaethylenehexamine             | 4067-16-7 | 0.5      |
| Diethylenetriamine                | 111-40-0  | 0.5      |

### 4. FIRST AID MEASURES

**General Advice** No hazards which require special first aid measures.

Eye Contact Rinse thoroughly with plenty of water for at least 15 minutes and consult a

physician.

**Skin Contact** Wash off immediately with soap and plenty of water while removing all

contaminated clothes and shoes.

**Inhalation** Move to fresh air. If symptoms persist, call a physician.

**Ingestion** Clean mouth with water and afterwards drink plenty of water. Consult a physician

V156-00 - MOISTURE TOLERANT QUICK SET EPOXY SEALER CLEAR

if necessary.

Most Important Symptoms/Effects May cause allergic skin reaction.

Notes To Physician Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

**Protective Equipment And Precautions For** 

**Firefighters** 

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent)

Revision Date: 13-Jul-2018

and full protective gear.

Specific Hazards Arising From The Chemical Closed containers may rupture if exposed to fire or

extreme heat.

Sensitivity To Mechanical Impact No

Sensitivity To Static Discharge No

**Flash Point Data** 

Flash Point (°F) 212
Flash Point (°C) 100
Method PMCC

Flammability Limits In Air

Lower flammability limit:

Upper flammability limit:

Not applicable

Not applicable

NFPA Health: 1 Flammability: 1 Instability: 0 Special: Not Applicable

## **NFPA Legend**

- 0 Not Hazardous
- 1 Slightly
- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal Precautions** Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.

**Other Information** Prevent further leakage or spillage if safe to do so.

**Environmental precautions** See Section 12 for additional Ecological Information.

Methods for Cleaning Up Soak up with inert absorbent material. Sweep up and shovel into suitable

containers for disposal.

7. HANDLING AND STORAGE

**Handling** Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or

sanding dust. In case of insufficient ventilation, wear suitable respiratory

Revision Date: 13-Jul-2018

equipment.

**Storage** Keep container tightly closed. Keep out of the reach of children.

Incompatible Materials No information available

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Exposure Limits**

| Chemical name                     | ACGIH TLV                      | OSHA PEL |
|-----------------------------------|--------------------------------|----------|
| Propylene glycol monomethyl ether | 50 ppm - TWA<br>100 ppm - STEL | N/E      |
| Diethylenetriamine                | 1 ppm - TWA<br>Skin            | N/E      |

Legend

ACGIH - American Conference of Governmental Industrial Hygienists Exposure Limits

OSHA - Occupational Safety & Health Administration Exposure Limits

N/E - Not Established

Engineering Measures Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

**Eye/Face Protection** Safety glasses with side-shields.

**Skin Protection** Protective gloves and impervious clothing.

**Respiratory Protection** In case of insufficient ventilation wear suitable respiratory equipment.

**Hygiene Measures** Avoid contact with skin, eyes and clothing. Remove and wash contaminated

clothing before re-use. Wash thoroughly after handling.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance liquid
Odor solvent

Odor Threshold No information available

 Density (lbs/gal)
 8.4 - 8.5

 Specific Gravity
 1.00 - 1.02

pH No information available
Viscosity (cps) No information available
Solubility(ies) No information available
Water solubility No information available
Evaporation Rate No information available
Vapor pressure @20 °C (kPa) No information available

Vapor density

No information available

V156-00 - MOISTURE TOLERANT QUICK SET EPOXY SEALER CLEAR

Revision Date: 13-Jul-2018

 Wt. % Solids
 10 - 20

 Vol. % Solids
 10 - 20

 Wt. % Volatiles
 80 - 90

 Vol. % Volatiles
 80 - 90

 VOC Regulatory Limit (g/L)
 <100</td>

 Boiling Point (°F)
 212

 Boiling Point (°C)
 100

Freezing Point (°F)

No information available

Freezing Point (°C)

No information available

 Flash Point (°F)
 212

 Flash Point (°C)
 100

 Method
 PMCC

Flammability (solid, gas)
Upper flammability limit:
Not applicable
Not applicable
Not applicable

Autoignition Temperature (°F)No information availableAutoignition Temperature (°C)No information availableDecomposition Temperature (°F)No information availableDecomposition Temperature (°C)No information availablePartition coefficientNo information available

### 10. STABILITY AND REACTIVITY

Reactivity Not Applicable

Chemical Stability Stable under normal conditions.

Conditions to avoid Prevent from freezing.

**Incompatible Materials**No materials to be especially mentioned.

Hazardous Decomposition Products

None under normal use.

Possibility of hazardous reactions

None under normal conditions of use.

### 11. TOXICOLOGICAL INFORMATION

### **Product Information**

Information on likely routes of exposure

**Principal Routes of Exposure** Eye contact, skin contact and inhalation.

**Acute Toxicity** 

Product Information No information available

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

V156-00 - MOISTURE TOLERANT QUICK SET EPOXY

**SEALER CLEAR** 

Revision Date: 13-Jul-2018

**Eye contact** May cause slight irritation.

**Skin contact** Substance may cause slight skin irritation. Prolonged or repeated contact may dry

skin and cause irritation.

**Inhalation** May cause irritation of respiratory tract.

**Ingestion** Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Sensitization May cause sensitization by skin contact

No information available. **Neurological Effects** No information available. **Mutagenic Effects Reproductive Effects** No information available. **Developmental Effects** No information available. Target organ effects No information available. STOT - single exposure No information available. STOT - repeated exposure No information available. Other adverse effects No information available. No information available **Aspiration Hazard** 

#### Numerical measures of toxicity

# The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 136508 mg/kg
ATEmix (dermal) 354920 mg/kg
ATEmix (inhalation-dust/mist) 1490.7 mg/L
ATEmix (inhalation-vapor) 932.6 mg/L

#### **Component Information**

Propylene glycol monomethyl ether LD50 Oral: 6,600 mg/kg (Rat) LD50 Dermal: 13,000 mg/kg (Rabbit) LC50 Inhalation (Vapor): 10,000 ppm (Rat)

Tetraethylenepentamine LD50 Oral: 3990 mg/kg (Rat) LD50 Dermal: 660 μL/kg (Rabbit)

Pentaethylenehexamine LD50 Oral: 1600 mg/kg (Rat)

Sensitization May cause sensitization by skin contact

Diethylenetriamine

LD50 Oral: 1080 mg/kg (Rat) LD50 Dermal: 1090 mg/kg (Rabbit)

Sensitization May cause sensitization by skin contact Respiratory sensitizer

### Carcinogenicity

There are no known carcinogenic chemicals in this product above reportable levels.

## 12. ECOLOGICAL INFORMATION

## **Ecotoxicity Effects**

The environmental impact of this product has not been fully investigated.

#### **Product Information**

V156-00 - MOISTURE TOLERANT QUICK SET EPOXY SEALER CLEAR

Revision Date: 13-Jul-2018

#### **Acute Toxicity to Fish**

No information available

## **Acute Toxicity to Aquatic Invertebrates**

No information available

#### **Acute Toxicity to Aquatic Plants**

No information available

#### Persistence / Degradability

No information available.

#### **Bioaccumulation**

No information available.

#### **Mobility in Environmental Media**

No information available.

#### Ozone

No information available

### **Component Information**

## **Acute Toxicity to Fish**

No information available

### **Acute Toxicity to Aquatic Invertebrates**

No information available

# **Acute Toxicity to Aquatic Plants**

No information available

| 12 | DISDOSAL | CONSIDERATIONS |
|----|----------|----------------|
|    |          |                |

Waste Disposal Method

Dispose of in accordance with federal, state, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

## 14. TRANSPORT INFORMATION

**DOT** Not regulated

ICAO / IATA Not regulated

IMDG / IMO Not regulated

## 15. REGULATORY INFORMATION

## **International Inventories**

V156-00 - MOISTURE TOLERANT QUICK SET EPOXY

**SEALER CLEAR** 

Revision Date: 13-Jul-2018

**TSCA: United States** Yes - All components are listed or exempt. **DSL: Canada** Yes - All components are listed or exempt.

## Federal Regulations

#### SARA 311/312 hazardous categorization

| Acute health hazard               | Yes |
|-----------------------------------|-----|
| Chronic Health Hazard             | No  |
| Fire hazard                       | No  |
| Sudden release of pressure hazard | No  |
| Reactive Hazard                   | No  |

### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

None

# Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

None

# **US State Regulations**

## **California Proposition 65**



MARNING: Cancer and Reproductive Harm– www.P65warnings.ca.gov

### State Right-to-Know

| Chemical name                     | Massachusetts | New Jersey | Pennsylvania |
|-----------------------------------|---------------|------------|--------------|
| Propylene glycol monomethyl ether | X             | X          | X            |
| Acetic acid                       | X             | X          | X            |

### Legend

X - Listed

## 16. OTHER INFORMATION

HMIS -Health: 1 Flammability: 1 Reactivity: 0 PPE: -

## **HMIS Legend**

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard

### V156-00 - MOISTURE TOLERANT QUICK SET EPOXY **SEALER CLEAR**

Revision Date: 13-Jul-2018

#### \* - Chronic Hazard

X - Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

**Prepared By Product Stewardship Department** 

> Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645

800-225-5554

**Revision Date:** 13-Jul-2018 **Revision Summary** Not available

## Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

**END OF SAFETY DATA SHEET**