



Revision Date: 06-Jul-2018

**Revision Number: 5** 

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name Product Code Alternate Product Code Product Class Color Recommended use Restrictions on use

# Manufacturer

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 Phone: 1-866-708-9180 corotechcoatings.com

# QUICK DRY ACRYLIC SPRAY DTM LIGHT GRAY

V300-71 V30071 WATER THINNED PAINT Gray Industrial paint No information available

Emergency Telephone

CHEMTREC (US): 800-424-9300 CHEMTREC (outside US): (703)-527-3887

2. HAZARDS IDENTIFICATION

# **Classification**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Carcinogenicity	Category 2

# Label elements

# Warning

Hazard statements Suspected of causing cancer



### Appearance liquid

Odor little or no odor

#### **Precautionary Statements - Prevention**

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required

# Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

# **Precautionary Statements - Storage**

Store locked up

# **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

# Hazards not otherwise classified (HNOC)

Not applicable

#### Other information

No information available

# Other hazards

**CAUTION:** All floor coatings may become slippery when wet. Where non-skid characteristics are desired, use an appropriate anti-slip aggregate.

# 3. COMPOSITION INFORMATION ON COMPONENTS

Chemical name	CAS No.	Weight-%
Titanium dioxide	13463-67-7	15
2-Butoxyethanol	111-76-2	5
Propanoic acid, 2-methyl-, monoester with 2,2,4-trimethyl-1,3-pentanediol	25265-77-4	5
Carbon black	1333-86-4	0.5
Ammonia	7664-41-7	0.5

4. FIRST AID MEASURES		
General Advice	No hazards which require special first aid measures.	
Eye Contact	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.	
Skin Contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.	
Inhalation	Move to fresh air. If symptoms persist, call a physician.	
Ingestion	Clean mouth with water and afterwards drink plenty of water. Consult a physician if necessary.	
Most Important	None known.	

Symptoms/Effects			
Notes To Physician Treat	symptomatically.		
5. F	FIRE-FIGHTII	NG MEASURES	
Suitable Extinguishing Media			sures that are appropriate to local surrounding environment.
Protective Equipment And Precautions Firefighters	1		f-contained breathing apparatus HA/NIOSH (approved or equivalent)
Specific Hazards Arising From The Chemical		Closed containers may rupture if exposed to fire or extreme heat.	
Sensitivity To Mechanical Impact	I	No	
Sensitivity To Static Discharge	I	No	
Flash Point Data Flash Point (°F) Flash Point (°C) Method	I	Not applicable Not applicable Not applicable	
Flammability Limits In Air			
Lower flammability limit: Upper flammability limit:		Not applicable Not applicable	
NFPA Health: 1 Flamm	mability: 0	Instability: 0	Special: Not Applicable
NFPA Legend 0 - Not Hazardous 1 - Slightly 2 - Moderate			

- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

# 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.
Other Information	Prevent further leakage or spillage if safe to do so.
Environmental precautions	See Section 12 for additional Ecological Information.
Methods for Cleaning Up	Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

# 7. HANDLING AND STORAGE

Handling	Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.
Storage	Keep container tightly closed. Keep out of the reach of children.
Incompatible Materials	No information available

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

# **Exposure Limits**

Chemical name	ACGIH TLV	OSHA PEL
Titanium dioxide	10 mg/m <sup>3</sup> - TWA	15 mg/m³ - TWA
2-Butoxyethanol	20 ppm - TWA	50 ppm - TWA 240 mg/m <sup>3</sup> - TWA prevent or reduce skin absorption
Carbon black	3 mg/m³ - TWA	3.5 mg/m <sup>3</sup> - TWA
Ammonia	25 ppm - TWA 35 ppm - STEL	50 ppm - TWA 35 mg/m³ - TWA

# Legend

ACGIH - American Conference of Governmental Industrial Hygienists Exposure Limits OSHA - Occupational Safety & Health Administration Exposure Limits N/E - Not Established

Engineering Measures	Ensure adequate ventilation, especially in confined areas.	
Personal Protective Equipment Eye/Face Protection Skin Protection Respiratory Protection	Safety glasses with side-shields. Protective gloves and impervious clothing. In case of insufficient ventilation wear suitable respiratory equipment.	
Hygiene Measures	Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.	

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Odor
Odor Threshold
Density (Ibs/gal)
Specific Gravity
рН
Viscosity (cps)
Solubility(ies)
Water solubility
Evaporation Rate
Vapor pressure @20 °C (kPa)
Vapor density
Wt. % Solids

liquid little or no odor No information available 9.3 - 9.4 1.11 - 1.13 No information available 40 - 50

# V300-71 - QUICK DRY ACRYLIC SPRAY DTM LIGHT GRAY

Vol. % Solids	30 - 40
Wt. % Volatiles	50 - 60
Vol. % Volatiles	60 - 70
VOC Regulatory Limit (g/L)	<100
Boiling Point (°F)	212
Boiling Point (°C)	100
Freezing Point (°F)	32
Freezing Point (°C)	0
Flash Point (°F)	Not applicable
Flash Point (°C)	Not applicable
Method	Not applicable
Flammability (solid, gas)	Not applicable
Upper flammability limit:	Not applicable
Lower flammability limit:	Not applicable
Autoignition Temperature (°F)	No information available
Autoignition Temperature (°C)	No information available
Decomposition Temperature (°F)	No information available
Decomposition Temperature (°C)	No information available
Partition coefficient	No information available

# **10. STABILITY AND REACTIVITY**

Reactivity	Not Applicable
Chemical Stability	Stable under normal conditions.
Conditions to avoid	Prevent from freezing.
Incompatible Materials	No materials to be especially mentioned.
Hazardous Decomposition Products	None under normal use.
Possibility of hazardous reactions	None under normal conditions of use.

11. TOXICOLOGICAL INFORMATION

Product Information		
Information on likely routes of exposure		
Principal Routes of Exposure	Eye contact, skin contact and inhalation.	
Acute Toxicity		
Product Information	No information available	
Symptoms related to the physical, chemical and toxicological characteristics		
Symptoms	No information available	
Delayed and immediate effects as well as chronic effects from short and long-term exposure		
Eye contact	May cause slight irritation.	

Skin contact	Substance may cause slight skin irritation. Prolonged or repeated contact may dry skin and cause irritation.
Inhalation	May cause irritation of respiratory tract.
Ingestion	Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Sensitization	No information available
Neurological Effects	No information available.
Mutagenic Effects	No information available.
Reproductive Effects	No information available.
Developmental Effects	No information available.
Target organ effects	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	No information available.
Other adverse effects	No information available.
Aspiration Hazard	No information available

# Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	20409 mg/kg
ATEmix (dermal)	61277 mg/kg
ATEmix (inhalation-dust/mist)	390.1 mg/L
ATEmix (inhalation-vapor)	646 mg/L

# **Component Information**

Titanium dioxide LD50 Oral: > 10000 mg/kg (Rat) 2-Butoxyethanol LD50 Oral: 470 mg/kg (Rat) LD50 Dermal: 220 mg/kg (Rabbit) LC50 Inhalation (Vapor): 450 ppm (Rat, 4 hr.) <u>Carbon black</u> LD50 Oral: > 15400 mg/kg (Rat) LD50 Dermal: > 3000 mg/kg (Rabbit) <u>Ammonia</u> LC50 Inhalation (Vapor): 2000 ppm (Rat, 4 hr.)

# Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

Chemical name	IARC	NTP	OSHA
	2B - Possible Human		Listed
Titanium dioxide	Carcinogen		
	2B - Possible Human		Listed
Carbon black	Carcinogen		

• Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

# Legend

IARC - International Agency for Research on Cancer NTP - National Toxicity Program

OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

# **Ecotoxicity Effects**

The environmental impact of this product has not been fully investigated.

# **Product Information**

#### Acute Toxicity to Fish No information available

# Acute Toxicity to Aquatic Invertebrates

No information available

# Acute Toxicity to Aquatic Plants

No information available

# Persistence / Degradability

No information available.

# **Bioaccumulation**

No information available.

# Mobility in Environmental Media

No information available.

# <u>Ozone</u>

No information available

# **Component Information**

# Acute Toxicity to Fish

<u>Titanium dioxide</u> LC50: > 1000 mg/L (Fathead Minnow - 96 hr.) <u>2-Butoxyethanol</u> LC50: 1490 mg/L (Bluegill sunfish - 96 hr.)

# Acute Toxicity to Aquatic Invertebrates

No information available

# Acute Toxicity to Aquatic Plants

No information available

# **13. DISPOSAL CONSIDERATIONS**

# **Waste Disposal Method** Dispose of in accordance with federal, state, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

	14. TRANSPORT INFORMATION	
DOT	Not regulated	
ICAO / IATA	Not regulated	
IMDG / IMO	Not regulated	
	15. REGULATORY INFORMATION	

# International Inventories

TSCA: United States	Yes - All components are listed or exempt.
DSL: Canada	No - Not all of the components are listed.
	One or more component is listed on NDSL.

# Federal Regulations

SARA 311/312 hazardous categorization	
Acute health hazard	No
Chronic Health Hazard	Yes
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

# **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical name	CAS No.	Weight-%	CERCLA/SARA 313
			(de minimis concentration)
2-Butoxyethanol	111-76-2	5	1.0

# Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

None

# **US State Regulations**

# **California Proposition 65**

MARNING: Cancer and Reproductive Harm– www.P65warnings.ca.gov

# State Right-to-Know

# V300-71 - QUICK DRY ACRYLIC SPRAY DTM LIGHT GRAY

Chemical name	Massachusetts	New Jersey	Pennsylvania
Titanium dioxide	Х	X	Х
2-Butoxyethanol	Х	Х	Х
Carbon black	Х	Х	Х

#### Legend

X - Listed

# 16. OTHER INFORMATION

HMIS	-	Heal

lealth: 1\*

Flammability: 0

Reactivity: 0

PPE: -

# HMIS Legend

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- \* Chronic Hazard

X - Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Prepared By	Product Stewardship Department Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 800-225-5554
Revision Date:	06-Jul-2018
Revision Summary	Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

END OF SAFETY DATA SHEET