



Revision Date: 11-Oct-2023 Revision Number: 2

### 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name BENJAMIN MOORE COROTECH ACRYLIC SEMI-GLOSS DTM

**WALMART CAPE MAY COBBLESTONE** 

Product Code V331-43
Alternate Product Code V33143

Product Class Water thinned paint

**Color** Gray

Recommended use Industrial paint

**Restrictions on use**No information available

Manufacturer

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 Phone: 1-866-708-9180

www.benjaminmoore.com/Corotech

**Emergency Telephone** 

CHEMTREC: +1 703-741-5970 / 1-800-424-9300 +1 703-527-3887 (outside US & Canada)

## 2. HAZARDS IDENTIFICATION

### Classification

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

## Label elements

Not a hazardous substance or mixture according to the Globally Harmonized System (GHS)

Appearance liquid

Odor little or no odor

### Hazards not otherwise classified (HNOC)

Not applicable

### Other information

No information available

**WARNING:** This product contains isothiazolinone compounds at levels of <0.1%. These substances are biocides commonly found in most paints and a variety of personal care products as a preservative. Certain individuals may be sensitive or allergic to these substances, even at low levels.

#### 3. COMPOSITION INFORMATION ON COMPONENTS

Chemical name	CAS No	Weight-%
Titanium dioxide	13463-67-7	15 - 20
Kaolin	1332-58-7	5 - 10
Diethylene glycol monoethyl ether	111-90-0	1 - 5
Propanoic acid, 2-methyl-, monoester with 2,2,4-trimethyl-1,3-pentanediol	25265-77-4	1 - 5
Ethanol, 2-(2-butoxyethoxy)-	112-34-5	1 - 5
Zinc phosphate	7779-90-0	0.1 - 0.5
Zinc oxide	1314-13-2	0.1 - 0.5
Ammonium hydroxide	1336-21-6	0.1 - 0.5

### 4. FIRST AID MEASURES

**General Advice** No hazards which require special first aid measures.

Eye Contact Rinse thoroughly with plenty of water for at least 15 minutes and consult a

physician.

Skin Contact Wash off immediately with soap and plenty of water while removing all

contaminated clothes and shoes.

**Inhalation** Move to fresh air. If symptoms persist, call a physician.

**Ingestion** Clean mouth with water and afterwards drink plenty of water. Consult a physician if

necessary.

Most Important Symptoms/Effects None known.

Notes To Physician Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

**Protective equipment and precautions for firefighters** As in any fire, wear self-contained breathing apparatus

pressure-demand, MSHA/NIOSH (approved or equivalent)

Revision Date: 11-Oct-2023

and full protective gear.

Specific Hazards Arising From The Chemical Closed containers may rupture if exposed to fire or

extreme heat.

Revision Date: 11-Oct-2023

Sensitivity to mechanical impact No

Sensitivity to static discharge No

**Flash Point Data** 

Flash point (°F)

Flash Point (°C)

Method

Not applicable

Not applicable

Flammability Limits In Air

Lower flammability limit:

Upper flammability limit:

Not applicable
Not applicable

**NFPA** 

Health hazards 1
Flammability 0
Stability 0

Special: Not Applicable

#### NFPA Legend

0 - Not Hazardous

- 1 Slightly
- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

# 6. ACCIDENTAL RELEASE MEASURES

**Personal Precautions** Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.

**Other Information** Prevent further leakage or spillage if safe to do so.

**Environmental precautions** See Section 12 for additional Ecological Information.

**Methods for Cleaning Up**Soak up with inert absorbent material. Sweep up and shovel into suitable

containers for disposal.

## 7. HANDLING AND STORAGE

Handling Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or

sanding dust. In case of insufficient ventilation, wear suitable respiratory

equipment.

**Storage** Keep container tightly closed. Keep out of the reach of children.

Incompatible Materials No information available

Revision Date: 11-Oct-2023

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## **Exposure Limits**

Chemical name	ACGIH TLV	OSHA PEL
Titanium dioxide	TWA: 0.2 mg/m³ nanoscale respirable particulate matter	15 mg/m³ - TWA
	TWA: 2.5 mg/m³ finescale respirable	
	particulate matter	
Kaolin	TWA: 2 mg/m³ particulate matter	15 mg/m³ - TWA
	containing no asbestos and <1%	5 mg/m <sup>3</sup> - TWA
	crystalline silica, respirable particulate	
	matter	
Ethanol, 2-(2-butoxyethoxy)-	TWA: 10 ppm inhalable fraction and	-
	vapor	
Zinc oxide	STEL: 10 mg/m³ respirable particulate	5 mg/m³ - TWA
	matter	15 mg/m³ - TWA
	TWA: 2 mg/m³ respirable particulate	
	matter	
	TWA: 0.5 mg/m³ Ba As Barium soluble	
	compounds [RR-00049-7]	
Ammonium hydroxide	STEL: 35 ppm	-
	TWA: 25 ppm	

Legend

ACGIH - American Conference of Governmental Industrial Hygienists Exposure Limits

OSHA - Occupational Safety & Health Administration Exposure Limits

N/E - Not Established

**Engineering Measures** Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

**Eye/Face Protection** Safety glasses with side-shields.

**Skin Protection** Protective gloves and impervious clothing.

**Respiratory Protection** In case of insufficient ventilation wear suitable respiratory equipment.

Hygiene Measures Avoid contact with skin, eyes and clothing. Remove and wash contaminated

clothing before re-use. Wash thoroughly after handling.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance liquid

Odor little or no odor

Odor Threshold No information available

**Density (lbs./gal)** 10.2 - 10.6 **Specific Gravity** 1.22 - 1.27

pHNo information availableViscosity (cps)No information availableSolubility(ies)No information availableWater solubilityNo information availableEvaporation RateNo information available

V331-43 - BENJAMIN MOORE COROTECH ACRYLIC SEMI-GLOSS DTM WALMART CAPE MAY COBBLESTONE

Revision Date: 11-Oct-2023

Vapor pressure @20 °C (kPa)No information availableRelative vapor densityNo information available

Wt. % Solids 50 - 60 Vol. % Solids 40 - 50 Wt. % Volatiles 40 - 50 50 - 60 Vol. % Volatiles VOC Regulatory Limit (g/L) < 250 **Boiling Point (°F)** 212 **Boiling Point (°C)** 100 Freezing point (°F) 32 Freezing Point (°C)

Flash point (°F)

Flash Point (°C)

Method

Flammability (solid, gas)

Upper flammability limit:

Lower flammability limit:

Not applicable

Not applicable

Not applicable

Not applicable

Autoignition Temperature (°F)No information availableAutoignition Temperature (°C)No information availableDecomposition Temperature (°C)No information availablePartition coefficientNo information available

## 10. STABILITY AND REACTIVITY

Reactivity Not Applicable

Chemical Stability Stable under normal conditions.

Conditions to avoid Prevent from freezing.

Incompatible Materials No materials to be especially mentioned.

Hazardous Decomposition Products

None under normal use.

Possibility of hazardous reactions None under normal conditions of use.

# 11. TOXICOLOGICAL INFORMATION

#### **Product Information**

Information on likely routes of exposure

**Principal Routes of Exposure** Eye contact, skin contact and inhalation.

**Acute Toxicity** 

Product Information No information available

Symptoms related to the physical, chemical and toxicological characteristics

V331-43 - BENJAMIN MOORE COROTECH ACRYLIC SEMI-GLOSS DTM WALMART CAPE MAY COBBLESTONE

Revision Date: 11-Oct-2023

**Symptoms** No information available

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Eye contact** May cause slight irritation.

**Skin contact**Substance may cause slight skin irritation. Prolonged or repeated contact may dry

skin and cause irritation.

**Inhalation** May cause irritation of respiratory tract.

**Ingestion** Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Sensitization No information available No information available. **Neurological Effects** No information available. **Mutagenic Effects Reproductive Effects** No information available. **Developmental Effects** No information available. No information available. **Target organ effects** STOT - single exposure No information available. STOT - repeated exposure No information available. Other adverse effects No information available. No information available **Aspiration Hazard** 

#### Numerical measures of toxicity

### The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 20371 mg/kg ATEmix (inhalation-dust/mist) 107.4 mg/l

<u>Component Information</u> Caution - This mixture contains a substance not yet fully tested

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-
Kaolin 1332-58-7	> 5000 mg/kg (Rat)	> 5000 mg/kg (Rat)	-
Diethylene glycol monoethyl ether 111-90-0	= 10502 mg/kg (Rat)	= 9143 mg/kg ( Rabbit )	> 5240 mg/m³ (Rat) 4 h
Propanoic acid, 2-methyl-, monoester with 2,2,4-trimethyl-1,3-pentanediol 25265-77-4	= 3200 mg/kg(Rat)	> 15200 mg/kg(Rat)	-
Ethanol, 2-(2-butoxyethoxy)- 112-34-5	= 5660 mg/kg (Rat)	= 2700 mg/kg ( Rabbit )	-
Zinc phosphate 7779-90-0	> 5000 mg/kg (Rat)	-	-
Zinc oxide 1314-13-2	> 5000 mg/kg (Rat)	-	-
Ammonium hydroxide 1336-21-6	= 350 mg/kg (Rat)	-	-

#### **Chronic Toxicity**

#### Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

Chemical name	IARC	NTP	OSHA
	2B - Possible Human		Listed

### V331-43 - BENJAMIN MOORE COROTECH ACRYLIC SEMI-GLOSS DTM WALMART CAPE MAY COBBLESTONE

Titanium dioxide	Carcinogen	

Revision Date: 11-Oct-2023

• Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

#### Legend

IARC - International Agency for Research on Cancer NTP - National Toxicity Program OSHA - Occupational Safety & Health Administration

# 12. ECOLOGICAL INFORMATION

# **Ecotoxicity Effects**

The environmental impact of this product has not been fully investigated.

### **Product Information**

### **Acute Toxicity to Fish**

No information available

### **Acute Toxicity to Aquatic Invertebrates**

No information available

#### **Acute Toxicity to Aquatic Plants**

No information available

#### Persistence / Degradability

No information available.

#### **Bioaccumulation**

There is no data for this product.

#### **Mobility in Environmental Media**

No information available.

#### **Ozone**

Not applicable

### **Component Information**

## **Acute Toxicity to Fish**

Titanium dioxide

LC50: > 1000 mg/L (Fathead Minnow - 96 hr.)

#### **Acute Toxicity to Aquatic Invertebrates**

Ethanol, 2-(2-butoxyethoxy)-

EC50: 100 mg/L (Daphnia - 48 hr.)

#### **Acute Toxicity to Aquatic Plants**

No information available

### 13. DISPOSAL CONSIDERATIONS

#### Waste Disposal Method

Dispose of in accordance with federal, state, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

Revision Date: 11-Oct-2023

## 14. TRANSPORT INFORMATION

**DOT** Not regulated

ICAO / IATA Not regulated

IMDG / IMO Not regulated

### 15. REGULATORY INFORMATION

# **International Inventories**

**TSCA: United States**Yes - All components are listed or exempt.
Yes - All components are listed or exempt.

# Federal Regulations

#### SARA 311/312 Hazard Categories

Acute health hazard No
Chronic Health Hazard No
Fire hazard No
Sudden release of pressure hazard No
Reactive Hazard No

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No	Weight-%	CERCLA/SARA 313 (de minimis concentration)
Diethylene glycol monoethyl ether	111-90-0	1 - 5	1.0
Ethanol, 2-(2-butoxyethoxy)-	112-34-5	1 - 5	1.0

### Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

Revision Date: 11-Oct-2023

Chemical name	CAS No	Weight-%	<u>Hazardous Air Pollutant</u> (HAP)
Diethylene glycol monoethyl ether	111-90-0	1 - 5	Listed
Ethanol, 2-(2-butoxyethoxy)-	112-34-5	1 - 5	Listed

# **US State Regulations**

### **California Proposition 65**

MARNING: This product can expose you to chemicals including Titanium dioxide, which are known to the State of California to cause cancer, and Ethylene glycol which are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

### U.S. State Right-to-Know Regulations

Chemical name	Massachusetts	New Jersey	Pennsylvania
Water			X
Titanium dioxide	X	X	X
Kaolin	X	X	X
Diethylene glycol monoethyl ether		X	X
Ethanol, 2-(2-butoxyethoxy)-		X	X

#### Legend

X - Listed

## 16. OTHER INFORMATION

#### **HMIS**

**Health hazards Flammability** 0 Reactivity: 0 Personal protection

### **HMIS Legend**

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- \* Chronic Hazard
- X Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

Revision Date: 11-Oct-2023

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Prepared By Product Stewardship Department

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645

800-225-5554

Revision Date: 11-Oct-2023 Revision Summary Not available

#### Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

**End of Safety Data Sheet**