



Revision Date: 05-Jun-2020 Revision Number: 2

## 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name COROTECH COMMAND WATERBORNE ACRYLIC URETHANE

**GLOSS WHITE** 

Product Code V39001FR

Alternate Product Code A39001

Product Class Water thinned paint

**Color** White **Recommended use** Paint

Restrictions on use No information available

**Manufactured For** 

Benjamin Moore & Co., Limited

8775 Keele Street Concord ON L4K 2N1 Phone: 1-800-361-5898

www.benjaminmoore.ca/corotech

Manufacturer

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645

Phone: 1-866-708-9180

www.benjaminmoore.com/Corotech

**Emergency Telephone** 

CANUTEC: 613-996-6666

# 2. HAZARDS IDENTIFICATION

#### Classification

This chemical is considered hazardous by the Hazardous Products Regulations (HPR: SOR/2015-17)

| Skin sensitization     | Category 1A |
|------------------------|-------------|
| Germ cell mutagenicity | Category 1B |
| Reproductive toxicity  | Category 1B |

#### Label elements

| Danger |  |  |  |
|--------|--|--|--|
|        |  |  |  |

Revision Date: 05-Jun-2020

#### **Hazard statements**

May cause an allergic skin reaction May cause genetic defects May damage fertility or the unborn child



Appearance liquid Odor little or no odor

#### **Precautionary Statements - Prevention**

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Avoid breathing dust/fume/gas/mist/vapors/spray
Contaminated work clothing should not be allowed out of the workplace
Wear protective gloves

### **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

#### Skin

IF ON SKIN: Wash with plenty of soap and water

If skin irritation or rash occurs: Get medical advice/attention

Wash contaminated clothing before reuse

# **Precautionary Statements - Storage**

Store locked up

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### Other information

No information available

#### Other hazards

**CAUTION:** All floor coatings may become slippery when wet. Where non-skid characteristics are desired, use an appropriate anti-slip aggregate.

## 3. COMPOSITION INFORMATION ON COMPONENTS

|   | Chemical name    | CAS No.    | Weight-% | Hazardous Material<br>Information Review Act | Date HMIRA filed and date exemption granted |
|---|------------------|------------|----------|--|---|
|   |                  |            |          | registry number                              | (if applicable)                             |
|   |                  |            |          | (HMIRA registry #)                           |   |
| I | Titanium dioxide | 13463-67-7 | 10 - 30% | -  | -   |

| Dipropylene glycol monomethyl ether  | 34590-94-8  | 1 - 5%      | - | - |
|--|-------------|-------------|---|---|
| Silica amorphous   | 7631-86-9   | 1 - 5%      | - | - |
| Alcohols, C12 - 14, ethoxylated  | 68439-50-9  | 0.25 - 0.5% | - | - |
| Ammonium hydroxide   | 1336-21-6   | 0.25 - 0.5% | - | - |
| Poly(oxy-1,2-ethanediyl),<br>.alpha[3-[3-(2H-benzotriazol-2-<br>yl)-5-(1,1-dimethylethyl)-4-hydro<br>xyphenyl]-1-oxopropyl]omega<br>hydroxy-   | 104810-48-2 | 0.1 - 0.25% | - | - |
| Ammonia  | 7664-41-7   | 0.1 - 0.25% | - | - |
| Poly(oxy-1,2-ethanediyl), .alpha[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydro xyphenyl]-1-oxopropyl]omega [3-[3-(2H-benzotriazol-2-yl)-5-(1, 1-dimethylethyl)-4-hydroxyphen yl]-1-oxoprop | 104810-47-1 | 0.1 - 0.25% | - | - |
| Decanedioic acid,<br>bis(1,2,2,6,6-pentamethyl-4-pip<br>eridinyl) ester  | 41556-26-7  | 0.1 - 0.25% | - | - |
| Carbamic acid,<br>1H-benzimidazol-2-yl-, methyl<br>ester   | 10605-21-7  | 0.1 - 0.25% | - | - |

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret

#### 4. FIRST AID MEASURES

General Advice If symptoms persist, call a physician. Show this safety data

sheet to the doctor in attendance.

**Eye Contact**Rinse thoroughly with plenty of water for at least 15

minutes and consult a physician.

Skin Contact Wash off immediately with soap and plenty of water while

removing all contaminated clothes and shoes. If skin irritation persists, call a physician. Wash clothing before reuse. Destroy contaminated articles such as shoes.

Revision Date: 05-Jun-2020

**Inhalation** Move to fresh air. If symptoms persist, call a physician.

Ingestion Clean mouth with water and afterwards drink plenty of

water. Consult a physician if necessary.

Most Important Symptoms/Effects May cause allergic skin reaction.

Notes To Physician Treat symptomatically.

# 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

**Protective equipment and precautions for firefighters** As in any fire, wear self-contained breathing apparatus

pressure-demand, MSHA/NIOSH (approved or equivalent)

Revision Date: 05-Jun-2020

and full protective gear.

Specific Hazards Arising From The Chemical Closed containers may rupture if exposed to fire or

extreme heat.

Sensitivity to mechanical impact No

Sensitivity to static discharge No

**Flash Point Data** 

Flash point (°F) 250
Flash Point (°C) 121
Method PMCC

Flammability Limits In Air

Lower flammability limit:Not applicableUpper flammability limit:Not applicable

NFPA Health: 2 Flammability: 1 Instability: 0 Special: Not Applicable

#### NFPA Legend

0 - Not Hazardous

- 1 Slightly
- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

#### 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Avoid contact with skin, eyes and clothing. Ensure

adequate ventilation.

**Other Information** Prevent further leakage or spillage if safe to do so.

**Environmental precautions**See Section 12 for additional Ecological Information.

Methods for Cleaning Up Soak up with inert absorbent material. Sweep up and

shovel into suitable containers for disposal.

## 7. HANDLING AND STORAGE

Handling Avoid contact with skin, eyes and clothing. Avoid breathing

vapors, spray mists or sanding dust. In case of insufficient

ventilation, wear suitable respiratory equipment.

Storage Keep container tightly closed. Keep out of the reach of

children.

**Incompatible Materials** 

No information available

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### **Exposure Limits**

| Chemical name      | ACGIH TLV                 | Alberta                     | British Columbia           | Ontario                    | Quebec                       |
|--------------------|---------------------------|-----------------------------|----------------------------|----------------------------|------------------------------|
| Titanium dioxide   | TWA: 10 mg/m <sup>3</sup> | 10 mg/m³ - TWA              | 10 mg/m <sup>3</sup> - TWA | 10 mg/m <sup>3</sup> - TWA | 10 mg/m <sup>3</sup> - TWAEV |
|                    |                           |                             | 3 mg/m³ - TWA              |                            |                              |
| Dipropylene glycol | STEL: 150 ppm             | 100 ppm - TWA               | 100 ppm - TWA              | 100 ppm - TWA              | 100 ppm - TWAEV              |
| monomethyl ether   | TWA: 100 ppm              | 606 mg/m³ - TWA             | 150 ppm - STEL             | 150 ppm - STEL             | 606 mg/m³ - TWAEV            |
|                    | S*                        | 150 ppm - STEL              | Skin absorption can        | Danger of cutaneous        | 150 ppm - STEV               |
|                    |                           | 909 mg/m³ - STEL            | contribute to overall      | absorption                 | 909 mg/m³ - STEV             |
|                    |                           | Substance may be            | exposure.                  |                            | Skin absorption can          |
|                    |                           | readily absorbed            |                            |                            | contribute to overall        |
|                    |                           | through intact skin         |                            |                            | exposure.                    |
| Ammonia            | STEL: 35 ppm              | 25 ppm - TWA                | 25 ppm - TWA               | 25 ppm - TWA               | 25 ppm - TWAEV               |
|                    | TWA: 25 ppm               | 17 mg/m³ - TWA              | 35 ppm - STEL              | 35 ppm - STEL              | 17 mg/m³ - TWAEV             |
|                    |                           | 35 ppm - STEL               |                            |                            | 35 ppm - STEV                |
|                    |                           | 24 mg/m <sup>3</sup> - STEL |                            |                            | 24 mg/m <sup>3</sup> - STEV  |

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

Alberta - Alberta Occupational Exposure Limits

British Columbia - British Columbia Occupational Exposure Limits

Ontario - Ontario Occupational Exposure Limits Quebec - Quebec Occupational Exposure Limits

N/E - Not established

**Engineering Measures** 

Personal Protective Equipment

Eye/Face Protection Skin Protection

**Respiratory Protection** 

Ensure adequate ventilation, especially in confined areas.

Revision Date: 05-Jun-2020

Safety glasses with side-shields.

Protective gloves and impervious clothing.

Use only with adequate ventilation. In operations where exposure limits are exceeded, use a NIOSH approved respirator that has been selected by a technically qualified person for the specific work conditions. When spraying the product or applying in confined areas, wear a NIOSH approved respirator specified for paint spray or organic

vapors.

**Hygiene Measures** Avoid contact with skin, eyes and clothing. Remove and

wash contaminated clothing before re-use. Wash

thoroughly after handling.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance** 

Odor

Odor Threshold

Density (lbs/gal) Specific Gravity

рΗ

liquid little or no odor

No information available

10.25 - 10.35 1.23 - 1.25

No information available

Revision Date: 05-Jun-2020

Viscosity (cps)No information availableSolubility(ies)No information availableWater solubilityNo information availableEvaporation RateNo information availableVapor pressureNo information availableVapor densityNo information available

Wt. % Solids 45 - 55 Vol. % Solids 30 - 40 45 - 55 Wt. % Volatiles 60 - 70Vol. % Volatiles VOC Regulatory Limit (g/L) < 150 **Boiling Point (°F)** 212 **Boiling Point (°C)** 100 Freezing point (°F) 32 Freezing Point (°C) 0 Flash point (°F) 250 Flash Point (°C) 121 **PMCC** Method

Flammability (solid, gas)
Upper flammability limit:
Not applicable
Not applicable
Not applicable

Autoignition Temperature (°F)No information availableAutoignition Temperature (°C)No information availableDecomposition Temperature (°F)No information availableDecomposition Temperature (°C)No information availablePartition coefficientNo information available

## 10. STABILITY AND REACTIVITY

Reactivity Not Applicable

Chemical Stability Stable under normal conditions.

Conditions to avoid Prevent from freezing.

Incompatible Materials No materials to be especially mentioned.

Hazardous Decomposition Products

None under normal use.

Possibility of hazardous reactions None under normal conditions of use.

#### 11. TOXICOLOGICAL INFORMATION

**Product Information** 

Information on likely routes of exposure

Principal Routes of Exposure Eye contact, skin contact and inhalation.

**Acute Toxicity** 

Product Information No information available

#### Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Eye contact May cause slight irritation

**Skin contact** Substance may cause slight skin irritation. Prolonged or

repeated contact may dry skin and cause irritation.

Revision Date: 05-Jun-2020

**Inhalation** May cause irritation of respiratory tract.

**Ingestion** Ingestion may cause gastrointestinal irritation, nausea,

vomiting and diarrhea.

**Sensitization** May cause an allergic skin reaction.

Neurological Effects No information available.

Mutagenic EffectsSuspected of causing genetic defects.Reproductive EffectsMay damage fertility or the unborn child.

Developmental EffectsNo information available.Target organ effectsNo information available.STOT - single exposureNo information available.STOT - repeated exposureNo information available.Other adverse effectsNo information available.Aspiration HazardNo information available.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 24941 mg/kg ATEmix (inhalation-dust/mist) 370.6 mg/L

## **Component Information**

| Chemical name   | Oral LD50                                    | Dermal LD50  | Inhalation LC50        |
|---|--|--|------------------------|
| Titanium dioxide<br>13463-67-7  | > 10000 mg/kg (Rat)                          | -  | -                      |
| Dipropylene glycol monomethyl<br>ether<br>34590-94-8                                  | = 5.35 g/kg(Rat)                             | = 9500 mg/kg(Rabbit)                                       | -                      |
| Silica amorphous<br>7631-86-9   | = 7900 mg/kg (Rat)                           | > 2000 mg/kg (Rabbit)                                      | > 2.2 mg/L (Rat)1 h    |
| Ammonium hydroxide<br>1336-21-6   | = 350 mg/kg (Rat)                            | -  | -                      |
| Ammonia<br>7664-41-7  | = 350 mg/kg (Rat)                            | -  | = 2000 ppm ( Rat ) 4 h |
| Decanedioic acid,<br>bis(1,2,2,6,6-pentamethyl-4-piperidi<br>nyl) ester<br>41556-26-7 | = 2615 mg/kg ( Rat )                         | -  | -                      |
| Carbamic acid,<br>1H-benzimidazol-2-yl-, methyl ester<br>10605-21-7                   | > 5050 mg/kg ( Rat )<br>= 6400 mg/kg ( Rat ) | > 10000 mg/kg(Rabbit)= 2 g/kg(<br>Rat)= 8500 mg/kg(Rabbit) | -                      |

#### **Chronic Toxicity**

### Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

Revision Date: 05-Jun-2020

| Chemical name    | IARC                           | NTP |
|------------------|--------------------------------|-----|
|                  | 2B - Possible Human Carcinogen |     |
| Titanium dioxide |                                |     |

• Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

#### Legend

IARC - International Agency for Research on Cancer NTP - National Toxicity Program OSHA - Occupational Safety & Health Administration

## 12. ECOLOGICAL INFORMATION

# **Ecotoxicity Effects**

The environmental impact of this product has not been fully investigated.

## **Product Information**

# **Acute Toxicity to Fish**

No information available

#### **Acute Toxicity to Aquatic Invertebrates**

No information available

#### **Acute Toxicity to Aquatic Plants**

No information available

#### Persistence / Degradability

No information available.

#### **Bioaccumulation**

There is no data for this product.

#### **Mobility in Environmental Media**

No information available.

#### **Ozone**

No information available

#### **Component Information**

#### **Acute Toxicity to Fish**

Titanium dioxide

LC50: > 1000 mg/L (Fathead Minnow - 96 hr.)
Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester

LC50: 1.5 mg/L (Rainbow Trout - 96 hr.)

#### **Acute Toxicity to Aquatic Invertebrates**

Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester LC50: 0.22 mg/L (water flea - 48 hr.)

#### **Acute Toxicity to Aquatic Plants**

No information available

#### 13. DISPOSAL CONSIDERATIONS

**Waste Disposal Method** 

Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

Revision Date: 05-Jun-2020

# 14. TRANSPORT INFORMATION

**TDG** Not regulated

ICAO / IATA Not regulated

IMDG / IMO Not regulated

## 15. REGULATORY INFORMATION

#### **International Inventories**

**TSCA: United States** Yes - All components are listed or exempt. No - Not all of the components are listed. **DSL: Canada** 

One or more component is listed on NDSL.

# National Pollutant Release Inventory (NPRI)

#### NPRI Parts 1-4

This product contains the following Parts 1-4 NPRI chemicals:

Chemical name Weight-% NPRI Parts 1-4 CAS No. Ammonia 7664-41-7 0.1 - 0.25% Listed

#### **NPRI Part 5**

This product contains the following NPRI Part 5 Chemicals:

None

Revision Date: 05-Jun-2020

#### **WHMIS Regulatory Status**

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

#### 16. OTHER INFORMATION

HMIS -Health: 2\* Flammability: 1 Reactivity: 0 PPE: -

#### **HMIS Legend**

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- \* Chronic Hazard
- X Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada at http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked questions-questions posees-eng.php.

Prepared By Product Stewardship Department

> Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645

800-225-5554

**Revision Date:** 05-Jun-2020 Reason for revision Not available

#### Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

**End of Safety Data Sheet**