



Revision Date: 05-Jun-2020

**Revision Number:** 1

1. PRODUCT AND COMPANY IDENTIFICATION

**GLOSS SAFETY YELLOW** 

**V39010FR** A39010

Yellow

Paint

Water thinned paint

No information available

COROTECH COMMAND WATERBORNE ACRYLIC URETHANE

Product Name

Product Code Alternate Product Code Product Class Color Recommended use Restrictions on use

# Manufactured For

Benjamin Moore & Co., Limited 8775 Keele Street Concord ON L4K 2N1 Phone: 1-800-361-5898 www.benjaminmoore.ca/corotech

## **Manufacturer**

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 Phone: 1-866-708-9180 www.benjaminmoore.com/Corotech

Emergency Telephone CANUTEC: 613-996-6666

2. HAZARDS IDENTIFICATION

## **Classification**

This chemical is considered hazardous by the Hazardous Products Regulations (HPR: SOR/2015-17)

Skin sensitization	Category 1A
Germ cell mutagenicity	Category 1B
Reproductive toxicity	Category 1B

## Label elements

### Danger

#### Hazard statements

May cause an allergic skin reaction May cause genetic defects May damage fertility or the unborn child



Odor little or no odor

## **Precautionary Statements - Prevention**

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Avoid breathing dust/fume/gas/mist/vapors/spray Contaminated work clothing should not be allowed out of the workplace Wear protective gloves

### **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention Skin IF ON SKIN: Wash with plenty of soap and water

If skin irritation or rash occurs: Get medical advice/attention Wash contaminated clothing before reuse

## **Precautionary Statements - Storage**

Store locked up

## **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### Other information

No information available

## Other hazards

**CAUTION:** All floor coatings may become slippery when wet. Where non-skid characteristics are desired, use an appropriate anti-slip aggregate.

Chemical name	CAS No.	Weight-%	Hazardous Material	Date HMIRA filed and
		_	Information Review Act	date exemption granted
			registry number	(if applicable)
			(HMIRA registry #)	
Dipropylene glycol monomethyl	34590-94-8	1 - 5%	-	-

# 3. COMPOSITION INFORMATION ON COMPONENTS

ether				
Titanium dioxide	13463-67-7	1 - 5%	-	-
Zinc phosphate	7779-90-0	0.5 - 1%	-	-
Alcohols, C12 - 14, ethoxylated	68439-50-9	0.25 - 0.5%	-	-
Ammonium hydroxide	1336-21-6	0.25 - 0.5%	-	-
Poly(oxy-1,2-ethanediyl), .alpha[3-[3-(2H-benzotriazol-2- yl)-5-(1,1-dimethylethyl)-4-hydro xyphenyl]-1-oxopropyl]omega hydroxy-	104810-48-2	0.1 - 0.25%	-	-
Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester	10605-21-7	0.1 - 0.25%	-	-
Poly(oxy-1,2-ethanediyl), .alpha[3-[3-(2H-benzotriazol-2- yl)-5-(1,1-dimethylethyl)-4-hydro xyphenyl]-1-oxopropyl]omega [3-[3-(2H-benzotriazol-2-yl)-5-(1, 1-dimethylethyl)-4-hydroxyphen yl]-1-oxoprop	104810-47-1	0.1 - 0.25%	-	-
Decanedioic acid, bis(1,2,2,6,6-pentamethyl-4-pip eridinyl) ester	41556-26-7	0.1 - 0.25%	-	-
Ammonia	7664-41-7	0.1 - 0.25%	-	-

\*The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST A	D MEASURES	
General Advice	If symptoms persist, call a physician. Show this safety data sheet to the doctor in attendance.	
Eye Contact	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.	
Skin Contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician. Wash clothing before reuse. Destroy contaminated articles such as shoes.	
Inhalation	Move to fresh air. If symptoms persist, call a physician.	
Ingestion	Clean mouth with water and afterwards drink plenty of water. Consult a physician if necessary.	
Most Important Symptoms/Effects	May cause allergic skin reaction.	
Notes To Physician	Treat symptomatically.	
5. FIRE-FIGHTING MEASURES		

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Protective equipment and precautions for firefighters	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.
Specific Hazards Arising From The Chemical	Closed containers may rupture if exposed to fire or extreme heat.
Sensitivity to mechanical impact	No
Sensitivity to static discharge	No
Flash Point Data Flash point (°F) Flash Point (°C) Method	250 121 PMCC
Flammability Limits In Air	
Lower flammability limit: Upper flammability limit:	Not applicable Not applicable
NFPA Health: 2 Flammability: 1	Instability: 0 Special: Not Applicable
<b>NFPA Legend</b> 0 - Not Hazardous 1 - Slightly	

- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

## 6. ACCIDENTAL RELEASE MEASURES

Personal PrecautionsAvoid contact with skin, eyes and clothing. Ensure<br/>adequate ventilation.Other InformationPrevent further leakage or spillage if safe to do so.Environmental precautionsSee Section 12 for additional Ecological Information.Methods for Cleaning UpSoak up with inert absorbent material. Sweep up and<br/>shovel into suitable containers for disposal.

7. HANDLING AND STORAGE

Handling	Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.	
Storage	Keep container tightly closed. Keep out of the reach of	

children.

#### **Incompatible Materials**

No information available

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Exposure Limits**

Chemical name	ACGIH TLV	Alberta	British Columbia	Ontario	Quebec
Dipropylene glycol	STEL: 150 ppm	100 ppm - TWA	100 ppm - TWA	100 ppm - TWA	100 ppm - TWAEV
monomethyl ether	TWA: 100 ppm	606 mg/m <sup>3</sup> - TWA	150 ppm - STEL	150 ppm - STEL	606 mg/m <sup>3</sup> - TWAEV
-	S*	150 ppm - STEL	Skin absorption can	Danger of cutaneous	150 ppm - STEV
		909 mg/m <sup>3</sup> - STEL	contribute to overall	absorption	909 mg/m <sup>3</sup> - STEV
		Substance may be	exposure.		Skin absorption can
		readily absorbed	-		contribute to overall
		through intact skin			exposure.
Titanium dioxide	TWA: 10 mg/m <sup>3</sup>	10 mg/m <sup>3</sup> - TWA	10 mg/m <sup>3</sup> - TWA	10 mg/m <sup>3</sup> - TWA	10 mg/m <sup>3</sup> - TWAEV
	-	•	3 mg/m <sup>3</sup> - TWA	•	•
Ammonia	STEL: 35 ppm	25 ppm - TWA	25 ppm - TWA	25 ppm - TWA	25 ppm - TWAEV
	TWA: 25 ppm	17 mg/m <sup>3</sup> - TWA	35 ppm - STEL	35 ppm - STEL	17 mg/m <sup>3</sup> - TWAEV
		35 ppm - STEL			35 ppm - STEV
		24 mg/m <sup>3</sup> - STEL			24 mg/m <sup>3</sup> - STEV

#### Legend

ACGIH - American Conference of Governmental Industrial Hygienists Alberta - Alberta Occupational Exposure Limits British Columbia - British Columbia Occupational Exposure Limits Ontario - Ontario Occupational Exposure Limits Quebec - Quebec Occupational Exposure Limits N/E - Not established

#### **Engineering Measures**

#### Personal Protective Equipment Eye/Face Protection Skin Protection Respiratory Protection

Ensure adequate ventilation, especially in confined areas.

Safety glasses with side-shields.

Protective gloves and impervious clothing. Use only with adequate ventilation. In operations where exposure limits are exceeded, use a NIOSH approved respirator that has been selected by a technically qualified person for the specific work conditions. When spraying the product or applying in confined areas, wear a NIOSH approved respirator specified for paint spray or organic vapors.

#### Hygiene Measures

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Odor Odor Threshold Density (Ibs/gal) Specific Gravity pH liquid little or no odor No information available 9.0 - 9.1 1.08 - 1.10 No information available Viscosity (cps) Solubility(ies) Water solubility **Evaporation Rate** Vapor pressure Vapor density Wt. % Solids Vol. % Solids Wt. % Volatiles Vol. % Volatiles VOC Regulatory Limit (g/L) **Boiling Point (°F) Boiling Point (°C)** Freezing point (°F) Freezing Point (°C) Flash point (°F) Flash Point (°C) Method Flammability (solid, gas) Upper flammability limit: Lower flammability limit: Autoignition Temperature (°F) Autoignition Temperature (°C) **Decomposition Temperature (°F)** Decomposition Temperature (°C) Partition coefficient

No information available 35 - 45 30 - 40 55 - 65 60 - 70 < 150 212 100 32 0 250 121 PMCC Not applicable Not applicable Not applicable No information available No information available No information available No information available No information available

# **10. STABILITY AND REACTIVITY**

Reactivity	Not Applicable
Chemical Stability	Stable under normal conditions.
Conditions to avoid	Prevent from freezing.
Incompatible Materials	No materials to be especially mentioned.
Hazardous Decomposition Products	None under normal use.
Possibility of hazardous reactions	None under normal conditions of use.

# 11. TOXICOLOGICAL INFORMATION

## Product Information Information on likely routes of exposure

**Principal Routes of Exposure** 

Acute Toxicity Product Information Eye contact, skin contact and inhalation.

No information available

#### Symptoms related to the physical, chemical and toxicological characteristics

Symptoms

No information available

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

Eye contact Skin contact	May cause slight irritation Substance may cause slight skin irritation. Prolonged or
Skin contact	repeated contact may dry skin and cause irritation.
Inhalation	May cause irritation of respiratory tract.
Ingestion	Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Sensitization	May cause an allergic skin reaction.
Neurological Effects	No information available.
Mutagenic Effects	Suspected of causing genetic defects.
Reproductive Effects	May damage fertility or the unborn child.
Developmental Effects	No information available.
Target organ effects	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	No information available.
Other adverse effects	No information available.
Aspiration Hazard	No information available.

Numerical measures of toxicity

#### The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	92610 mg/kg
ATEmix (inhalation-dust/mist)	460.6 mg/L

## **Component Information**

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Dipropylene glycol monomethyl ether 34590-94-8	= 5.35 g/kg (Rat)	= 9500 mg/kg (Rabbit)	-
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-
Zinc phosphate 7779-90-0	> 5000 mg/kg (Rat)	-	-
Ammonium hydroxide 1336-21-6	= 350 mg/kg (Rat)	-	-
Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester 10605-21-7	> 5050 mg/kg (Rat) = 6400 mg/kg (Rat)	> 10000 mg/kg ( Rabbit ) = 2 g/kg ( Rat ) = 8500 mg/kg ( Rabbit )	-
Decanedioic acid, bis(1,2,2,6,6-pentamethyl-4-piperidi nyl) ester 41556-26-7	= 2615 mg/kg (Rat)	-	-
Ammonia 7664-41-7	= 350 mg/kg (Rat)	-	= 2000 ppm (Rat)4 h

## Chronic Toxicity

#### Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

## V39010FR - COROTECH COMMAND WATERBORNE ACRYLIC URETHANE GLOSS SAFETY YELLOW

Chemical name	IARC	NTP
	2B - Possible Human Carcinogen	
Titanium dioxide	_	

• Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

#### Legend

IARC - International Agency for Research on Cancer NTP - National Toxicity Program OSHA - Occupational Safety & Health Administration

**12. ECOLOGICAL INFORMATION** 

## Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

## Product Information

#### Acute Toxicity to Fish No information available

### Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

#### Persistence / Degradability

No information available.

#### **Bioaccumulation**

There is no data for this product.

#### Mobility in Environmental Media

No information available.

#### <u>Ozone</u>

No information available

## **Component Information**

#### Acute Toxicity to Fish

<u>Titanium dioxide</u> LC50: > 1000 mg/L (Fathead Minnow - 96 hr.) <u>Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester</u> LC50: 1.5 mg/L (Rainbow Trout - 96 hr.)

#### Acute Toxicity to Aquatic Invertebrates

Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester LC50: 0.22 mg/L (water flea - 48 hr.)

#### Acute Toxicity to Aquatic Plants

No information available

**13. DISPOSAL CONSIDERATIONS** 

Waste Disposal Method

Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

## **14. TRANSPORT INFORMATION**

TDG	Not regulated
ΙCAO / ΙΑΤΑ	Not regulated
IMDG / IMO	Not regulated

# **15. REGULATORY INFORMATION**

## International Inventories

TSCA: United States	Yes - All components are listed or exempt.
DSL: Canada	No - Not all of the components are listed.
	One or more component is listed on NDSL.

## National Pollutant Release Inventory (NPRI)

NPRI Parts 1-4 This product contains the following Parts 1-4 NPRI chemicals:

Chemical name	CAS No.	Weight-%	NPRI Parts 1-4
Ammonia	7664-41-7	0.1 - 0.25%	Listed

#### **NPRI Part 5**

This product contains the following NPRI Part 5 Chemicals:

None

#### WHMIS Regulatory Status

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

16. OTHER INFORMATION				
HMIS -	Health: 2*	Flammability: 1	Reactivity: 0	PPE: -
Note: The PPE r	zard Ird Iazard zard zard Izard ur supervisor or S.O.P.			pployees from the hazards the material will

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada at

http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked\_questions-questions\_posees-eng.php.

Prepared By	Product Stewardship Department Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 800-225-5554
Revision Date:	05-Jun-2020
Reason for revision	Not available

**Disclaimer** 

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

## **End of Safety Data Sheet**