



Revision Date: 07-Nov-2022

Revision Number: 6

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name Product Code Alternate Product Code Product Class Color Recommended use Restrictions on use

100% SOLIDS EPOXY FLOOR COATING SANDSTONE V430-52

V430-52 V43052 epoxy brown Industrial paint No information available

Manufactured For

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 Phone: 1-866-708-9180 www.benjaminmoore.com/Corotech

Emergency Telephone

CHEMTREC: +1 703-741-5970 / 1-800-424-9300 +1 703-527-3887 (outside US & Canada)

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 1 Sub-category B
Serious eye damage/eye irritation	Category 1
Skin sensitization	Category 1
Carcinogenicity	Category 1A
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 1

Label elements

Danger

Hazard statements

Causes severe skin burns and eye damage

V430-52 - 100% SOLIDS EPOXY FLOOR COATING SANDSTONE

May cause an allergic skin reaction May cause cancer Suspected of damaging fertility or the unborn child May cause respiratory irritation Causes damage to organs through prolonged or repeated exposure



Odor little or no odor

Precautionary Statements - Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Do not breathe dust/fume/gas/mist/vapors/spray Wash face, hands and any exposed skin thoroughly after handling Contaminated work clothing must not be allowed out of the workplace Wear protective gloves Do not eat, drink or smoke when using this product Use only outdoors or in a well-ventilated area

Precautionary Statements - Response

Immediately call a POISON CENTER or doctor/physician

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Immediately call a POISON CENTER or doctor/physician

Skin

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower Wash contaminated clothing before reuse

If skin irritation or rash occurs: Get medical advice/attention

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing Immediately call a POISON CENTER or doctor/physician Call a POISON CENTER or doctor/physician if you feel unwell Ingestion

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other information

No information available

CAUTION: All floor coatings may become slippery when wet. Where non-skid characteristics are desired, use an appropriate anti-slip aggregate.

IMPORTANT: Designed to be mixed with other components. Mixture will have hazards of all components. Before opening packages, read all warning labels. Follow all precautions.

3. COMPOSITION INFORMATION ON COMPONENTS

Chemical name	CAS No	Weight-%
4,4-isopropylidenediphenol-epichlorohydrin	25068-38-6	55 - 60
copolymer		
Silica, crystalline	14808-60-7	10 - 15
Titanium dioxide	13463-67-7	5 - 10
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	68609-97-2	5 - 10
Nonylphenol	84852-15-3	5 - 10

	4. FIRST AID MEASURES
General Advice	No hazards which require special first aid measures.
Eye Contact	Immediate medical attention is required. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes.
Skin Contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician. Wash clothing before reuse. Destroy contaminated articles such as shoes.
Inhalation	Move to fresh air. If symptoms persist, call a physician.
Ingestion	Clean mouth with water and afterwards drink plenty of water. Consult a physician if necessary.
Most Important Symptoms/Effects	May cause allergic skin reaction.
Notes To Physician	Treat symptomatically.
	5. FIRE-FIGHTING MEASURES
Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local

Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Protective equipment and precautions for firefighters	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent)

	and full protective gear.
Specific Hazards Arising From The Chemical	Closed containers may rupture if exposed to fire or extreme heat.
Sensitivity to mechanical impact	No
Sensitivity to static discharge	No
Flash Point Data Flash point (°F) Flash Point (°C) Method	310 154 PMCC
Flammability Limits In Air	
Lower flammability limit: Upper flammability limit:	Not applicable Not applicable
NFPA Health hazards Flammability Stability Special:	2 1 0 Not Applicable
NFPA Legend	

NFPA Legend 0 - Not Hazardous

- 1 Slightly
- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

6. ACCIDENTAL RELEASE MEASURES

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

Personal Precautions	Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.
Other Information	Prevent further leakage or spillage if safe to do so.
Environmental precautions	See Section 12 for additional Ecological Information.
Methods for Cleaning Up	Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.
	7. HANDLING AND STORAGE
Handling	Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.
Storage	Keep container tightly closed. Keep out of the reach of children.

Incompatible Materials

No information available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL
Silica, crystalline	TWA: 0.025 mg/m ³ respirable particulate matter	50 μg/m³ - TWA Respirable crystalline silica 50 μg/m³ - TWA -
Titanium dioxide	TWA: 10 mg/m ³	15 mg/m³ - TWA

Legend

ACGIH - American Conference of Governmental Industrial Hygienists Exposure Limits OSHA - Occupational Safety & Health Administration Exposure Limits N/E - Not Established

Ensure adequate ventilation, especially in confined areas. **Engineering Measures**

Personal	Protective	Equ	uij	pment

Eye/Face Protection	Safety glasses with side-shields.
Skin Protection	Protective gloves and impervious clothing.
Respiratory Protection	In case of insufficient ventilation wear suitable respiratory equipment.
Hygiene Measures	Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Flash Point (°C) Method Flammability (solid, gas) Upper flammability limit: Lower flammability limit: Autoignition Temperature (°F) Autoignition Temperature (°C) Decomposition Temperature (°C) Partition coefficient

154 PMCC Not applicable Not applicable No information available No information available No information available No information available No information available

10. STABILITY AND REACTIVITY

Reactivity	Not Applicable
Chemical Stability	Stable under normal conditions.
Conditions to avoid	Prevent from freezing.
Incompatible Materials	No materials to be especially mentioned.
Hazardous Decomposition Products	None under normal use.
Possibility of hazardous reactions	None under normal conditions of use.

11. TOXICOLOGICAL INFORMATION

Product Information		
Information on likely routes of e	exposure	
Principal Routes of Exposure	Eye contact, skin contact and inhalation.	
Acute Toxicity		
Product Information	No information available	
Symptoms related to the physical, chemical and toxicological characteristics		
Symptoms	No information available	
Delayed and immediate effects as well as chronic effects from short and long-term exposure		
Eye contact Skin contact Inhalation Ingestion Sensitization Neurological Effects Mutagenic Effects Reproductive Effects	Severely irritating to eyes. May cause burns. Risk of serious damage to eyes. Substance may cause slight skin irritation. Prolonged or repeated contact may dry skin and cause irritation. May cause irritation of respiratory tract. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May cause an allergic skin reaction No information available. No information available. Possible risk of impaired fertility. Possible risk of harm to the unborn child.	

Developmental Effects Target organ effects STOT - single exposure STOT - repeated exposure	No information available. No information available. No information available. Causes damage to organs through prolonged or repeated exposure if inhaled. Causes damage to organs through prolonged or repeated exposure if swallowed. liver. blood. Lungs.
Other adverse effects	No information available.
Aspiration Hazard	No information available

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	9345 mg/kg
ATEmix (dermal)	38177 mg/kg

Component Information

Caution - This mixture contains a substance not yet fully tested

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
4,4-isopropylidenediphenol-epichlor	= 11400 mg/kg (Rat)	-	-
ohydrin copolymer			
25068-38-6			
Titanium dioxide	> 10000 mg/kg (Rat)	-	-
13463-67-7			
Oxirane,	= 17100 mg/kg (Rat)	> 3987 mg/kg (Rabbit)	-
mono[(C12-14-alkyloxy)methyl]			
derivs.			
68609-97-2			
Nonylphenol	= 1300 mg/kg (Rat)	= 2000 mg/kg (Rabbit)	-
84852-15-3			

Chronic Toxicity

Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

Chemical name	IARC	NTP	OSHA
	1 - Human Carcinogen	Known Human	Listed
Silica, crystalline	_	Carcinogen	
	2B - Possible Human		Listed
Titanium dioxide	Carcinogen		

Crystalline Silica has been determined to be carcinogenic to humans by IARC (1) when in respirable form. Risk of cancer depends on duration and level of inhalation exposure to spray mist or dust from sanding the dried paint.
Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

Legend

IARC - International Agency for Research on Cancer NTP - National Toxicity Program OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

Product Information

<u>Acute Toxicity to Fish</u> No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

Persistence / Degradability

No information available.

Bioaccumulation

No information available.

Mobility in Environmental Media

No information available.

<u>Ozone</u>

Not applicable

Component Information

Acute Toxicity to Fish

<u>4,4-isopropylidenediphenol-epichlorohydrin copolymer</u> LC50: 1.5 mg/L (Rainbow Trout - 96 hr.) <u>Titanium dioxide</u> LC50: > 1000 mg/L (Fathead Minnow - 96 hr.)

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method

Dispose of in accordance with federal, state, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

14. TRANSPORT INFORMATION

DOT

Not regulated

ICAO / IATA	Not regulated
-------------	---------------

IMDG / IMO

Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA: United States	Yes - All components are listed or exempt.
DSL: Canada	Yes - All components are listed or exempt.

Federal Regulations

SARA 311/312 Hazard	Categories
Acute health hazard	

. . .

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	No
Sudden release of pressure hazar	d No
Reactive Hazard	No

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No	Weight-%	CERCLA/SARA 313
			(de minimis concentration)
Nonylphenol	84852-15-3	5 - 10	1.0

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61) This product contains the following HAPs:

None

US State Regulations

California Proposition 65

MARNING: This product can expose you to chemicals including Titanium dioxide, which are known to the State of California to cause cancer, and Toluene which are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

U.S. State Right-to-Know Regulations

V430-52 - 100% SOLIDS EPOXY FLOOR COATING SANDSTONE

Chemical name	Massachusetts	New Jersey	Pennsylvania
Silica, crystalline	Х	Х	Х
Titanium dioxide	Х	Х	Х

Legend

X - Listed

16. OTHER INFORMATION

HMIS

Health hazards	2*
Flammability	1
Reactivity:	0
Personal protection	-

HMIS Legend

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- Chronic Hazard
- X Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Prepared By	Product Stewardship Department Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 800-225-5554
Revision Date:	07-Nov-2022
Revision Summary	Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of

employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

End of Safety Data Sheet