



Revision Date: 17-Oct-2023

Revision Number: 4

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name Product Code Alternate Product Code Product Class Color Recommended use Restrictions on use

WATERBORNE AMINE EPOXY DEEP BASE

V440-87FR A44087 WATERBORNE EPOXY All Industrial paint No information available

Manufactured For

Benjamin Moore & Co., Limited 8775 Keele Street Concord ON L4K 2N1 Phone: 1-800-361-5898 www.benjaminmoore.ca/corotech

Manufacturer

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 Phone: 1-866-708-9180 www.benjaminmoore.com/Corotech Emergency Telephone

CHEMTREC: +1 703-741-5970 / 1-800-424-9300 +1 703-527-3887 (outside US & Canada) CANUTEC: 613-996-6666 (Transport Emergency Only)

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the Hazardous Products Regulations (HPR: SOR/2015-17)

| Acute toxicity - Oral | Category 4 |
|--|-------------|
| Skin corrosion/irritation | Category 2 |
| Serious eye damage/eye irritation | Category 1 |
| Carcinogenicity | Category 1A |
| Specific target organ toxicity (single exposure) | Category 1 |
| Specific target organ toxicity (repeated exposure) | Category 1 |

Label elements

V440-87FR - WATERBORNE AMINE EPOXY DEEP BASE

Danger

Hazard statements Harmful if swallowed Causes skin irritation Causes serious eye damage May cause cancer Causes damage to organs Causes damage to organs through prolonged or repeated exposure



Odor little or no odor

Precautionary Statements - Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Wash face, hands and any exposed skin thoroughly after handling Do not eat, drink or smoke when using this product Do not breathe dust/fume/gas/mist/vapors/spray

Precautionary Statements - Response

IF exposed: Call a POISON CENTER or doctor **Eyes** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Immediately call a POISON CENTER or doctor/physician

Skin

IF ON SKIN: Wash with plenty of soap and water If skin irritation occurs: Get medical advice/attention Take off contaminated clothing and wash before reuse

Ingestion

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell Rinse mouth

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other information

No information available

V440-87FR - WATERBORNE AMINE EPOXY DEEP BASE

IMPORTANT: Designed to be mixed with other components. Mixture will have hazards of all components. Before opening packages, read all warning labels. Follow all precautions.

CAUTION: All floor coatings may become slippery when wet. Where non-skid characteristics are desired, use an appropriate anti-slip aggregate.

3. COMPOSITION INFORMATION ON COMPONENTS

| Chemical name | CAS No | Weight-% | Hazardous Material Information Review Act registry number (HMIRA registry #) | Date HMIRA filed and date exemption granted (if applicable) |
|--|------------|----------|---|---|
| Aliphatic polyamine | - | 10 - 30% | HMIRC # 9649 | Granted: April 21, 2016 |
| Silica, crystalline | 14808-60-7 | 7 - 13% | - | - |
| Titanium dioxide | 13463-67-7 | 5 - 10% | - | - |
| 2-Propoxyethanol | 2807-30-9 | 3 - 7% | - | - |
| 2-Butoxyethanol | 111-76-2 | 1 - 5% | - | - |
| Dipropylene glycol monomethyl ether | 34590-94-8 | 1 - 5% | - | - |

*The exact percentage (concentration) of composition has been withheld as a trade secret

| 4. FIRST AID MEASURES | | | |
|---------------------------------|--|--|--|
| General Advice | Immediately call a POISON CENTER or doctor/physician. | | |
| Eye Contact | Immediate medical attention is required. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. | | |
| Skin Contact | Immediate medical attention is required. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Wash clothing before reuse. | | |
| Inhalation | Call a physician or poison control center immediately. Move to fresh air. If not breathing, give artificial respiration. | | |
| Ingestion | Never give anything by mouth to an unconscious person. Immediate medical attention is required. Drink 1 or 2 glasses of water. Do not induce vomiting without medical advice. | | |
| Protection Of First-Aiders | Use personal protective equipment. | | |
| Most Important Symptoms/Effects | None known. | | |
| Notes To Physician | Treat symptomatically. | | |
| 5. FIRE-FIGHTING MEASURES | | | |

| Suitable Extinguishing Media | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. |
|--|--|
| Protective equipment and precautions for firefighters | As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. |
| Specific Hazards Arising From The Chemical | Closed containers may rupture if exposed to fire or extreme heat. |
| Sensitivity to mechanical impact | No |
| Sensitivity to static discharge | No |
| Flash Point Data Flash point (°F) Flash Point (°C) Method | Not Applicable Not applicable Not applicable |
| Flammability Limits In Air | |
| Lower flammability limit: Upper flammability limit: | Not applicable Not applicable |
| NFPA Health hazards Flammability Stability Special: | 2 0 0 Not Applicable |
| | |

NFPA Legend

- 0 Not Hazardous
- 1 Slightly
- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6. ACCIDENTAL RELEASE MEASURES

| Personal Precautions | Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. |
|---------------------------|---|
| Other Information | Prevent further leakage or spillage if safe to do so. |
| Environmental precautions | See Section 12 for additional Ecological Information. |
| Methods for Cleaning Up | Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal. |

7. HANDLING AND STORAGE

Handling

Storage

Incompatible Materials

ventilation, wear suitable respiratory equipment. Keep container tightly closed. Keep out of the reach of

Avoid contact with skin, eyes and clothing. Avoid breathing

vapors, spray mists or sanding dust. In case of insufficient

No information available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

children.

Exposure Limits

| Chemical name | ACGIH TLV | Alberta | British Columbia | Ontario | Quebec |
|--|--|---|--|--|---|
| Silica, crystalline | TWA: 0.025 mg/m ³ respirable particulate matter | TWA: 0.025 mg/m ³ | TWA: 0.025 mg/m ³ | TWA: 0.10 mg/m ³ | TWA: 0.1 mg/m ³ |
| Titanium dioxide | TWA: 0.2 mg/m ³ nanoscale respirable particulate matter TWA: 2.5 mg/m ³ finescale respirable particulate matter | 10 mg/m³ - TWA | 10 mg/m³ - TWA 3 mg/m³ - TWA | 10 mg/m³ - TWA | 10 mg/m³ - TWAEV |
| 2-Propoxyethanol | - | - | - | 25 ppm - TWA 110 mg/m ³ - TWA Danger of cutaneous absorption | - |
| 2-Butoxyethanol | TWA: 20 ppm | TWA: 20 ppm TWA: 97 mg/m ³ | TWA: 20 ppm | TWA: 20 ppm | TWA: 20 ppm |
| Dipropylene glycol monomethyl ether | TWA: 50 ppm | 100 ppm - TWA 606 mg/m ³ - TWA 150 ppm - STEL 909 mg/m ³ - STEL Substance may be readily absorbed through intact skin | 100 ppm - TWA 150 ppm - STEL Skin absorption can contribute to overall exposure. | 100 ppm - TWA 150 ppm - STEL Danger of cutaneous absorption | 100 ppm - TWAEV 606 mg/m ³ - TWAEV 150 ppm - STEV 909 mg/m ³ - STEV Skin absorption can contribute to overall exposure. |

<u>Legend</u>

ACGIH - American Conference of Governmental Industrial Hygienists Alberta - Alberta Occupational Exposure Limits British Columbia - British Columbia Occupational Exposure Limits

Ontario - Ontario Occupational Exposure Limits

Quebec - Quebec Occupational Exposure Limits

N/E - Not established

Engineering Measures

Personal Protective Equipment Eye/Face Protection Skin Protection

Respiratory Protection

Hygiene Measures

Ensure adequate ventilation, especially in confined areas.

Safety glasses with side-shields Protective gloves and impervious clothing. In case of insufficient ventilation wear suitable respiratory equipment.

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

Appearance Odor **Odor Threshold** Density (lbs./gal) **Specific Gravity** pН Viscosity (cps) Solubility(ies) Water solubility **Evaporation Rate** Vapor pressure @20 °C (kPa) Relative vapor density Wt. % Solids Vol. % Solids Wt. % Volatiles Vol. % Volatiles VOC Regulatory Limit (g/L) **Boiling Point (°F) Boiling Point (°C)** Freezing point (°F) Freezing Point (°C) Flash point (°F) Flash Point (°C) Method Flammability (solid, gas) Upper flammability limit: Lower flammability limit: Autoignition Temperature (°F) Autoignition Temperature (°C) **Decomposition Temperature (°F) Decomposition Temperature (°C)** Partition coefficient

liauid little or no odor No information available 9.8 - 10.2 1.17 - 1.22 No information available 40 - 50 30 - 40 50 - 60 60 - 70 < 250 212 100 32 0 Not Applicable Not applicable Not applicable Not applicable Not applicable Not applicable No information available No information available No information available No information available No information available

10. STABILITY AND REACTIVITY

| Reactivity | Not Applicable |
|------------------------------------|--|
| Chemical Stability | Stable under normal conditions. |
| Conditions to avoid | Prevent from freezing. |
| Incompatible Materials | No materials to be especially mentioned. |
| Hazardous Decomposition Products | None under normal use. |
| Possibility of hazardous reactions | None under normal conditions of use. |

11. TOXICOLOGICAL INFORMATION

| Product Information Information on likely routes of exposure | |
|---|---|
| Principal Routes of Exposure | Eye contact, skin contact and inhalation. |
| Acute Toxicity Product Information | No information available |
| Symptoms related to the physical, chemical and toxic | ological characteristics |
| Symptoms | No information available |
| Delayed and immediate effects as well as chronic effe | cts from short and long-term exposure |
| Eye contact | Causes eye irritation Risk of serious damage to eyes May cause burns Severely irritating to eyes |
| Skin contact | Irritating to skin. Prolonged skin contact may cause skin irritation and/or dermatitis. May cause burns. |
| Inhalation | Harmful by inhalation. Causes respiratory tract irritation. Vapours may be irritating to eyes, nose, throat, and lungs. May cause additional affects as listed under "Ingestion". |
| Ingestion | Harmful if swallowed. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Can burn mouth, throat, and stomach. |
| Sensitization | No information available. |
| Neurological Effects | No information available. |
| Mutagenic Effects | No information available. |
| Reproductive Effects | No information available. |
| Developmental Effects | No information available. |
| Target organ effects | Liver, Kidney, Respiratory system, Eyes, Skin, Central nervous system, Blood, hematopoietic system, Lungs. |
| STOT - single exposure | May cause disorder and damage to the. Respiratory system. Digestive System. |
| STOT - repeated exposure | Causes damage to organs through prolonged or repeated exposure if inhaled. Causes damage to organs through prolonged or repeated exposure if swallowed. kidney. |
| Other adverse effects | No information available. |
| Aspiration Hazard | No information available. |
| Numerical measures of toxicity | |

The following values are calculated based on chapter 3.1 of the GHS document

| ATEmix (oral) ATEmix (dermal) | 1729 mg/kg 11796 mg/kg |
|----------------------------------|---------------------------|
| ATEmix (inhalation-dust/mist) | 6.3 mg/l |
| ATEmix (inhalation-vapor) | 240.6 mg/l |

Component Information

Caution - This mixture contains a substance not yet fully tested

| Chemical name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|------------------|---------------------|-------------|-----------------|
| Titanium dioxide | > 10000 mg/kg (Rat) | - | - |

| 13463-67-7 | | | |
|--|-------------------|---|---------------------|
| 2-Propoxyethanol 2807-30-9 | = 3089 mg/kg(Rat) | = 870 mg/kg (Rabbit)= 960 µL/kg (Rabbit) | = 1530 ppm (Rat)7 h |
| 2-Butoxyethanol 111-76-2 | = 1300 mg/kg(Rat) | > 2000 mg/kg (Rabbit) | > 4.9 mg/L (Rat) 3H |
| Dipropylene glycol monomethyl ether 34590-94-8 | = 5.35 g/kg (Rat) | = 9500 mg/kg (Rabbit) | - |

Chronic Toxicity

Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

| Chemical name | IARC | NTP |
|---------------------|--------------------------------|-------|
| | 1 - Human Carcinogen | Known |
| Silica, crystalline | | |
| | 2B - Possible Human Carcinogen | |
| Titanium dioxide | _ | |

Crystalline Silica has been determined to be carcinogenic to humans by IARC (1) when in respirable form. Risk of cancer depends on duration and level of inhalation exposure to spray mist or dust from sanding the dried paint.
Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is

bound to other materials, such as paint."

Legend

IARC - International Agency for Research on Cancer NTP - National Toxicity Program OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

Product Information

Acute Toxicity to Fish

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

Persistence / Degradability

No information available.

Bioaccumulation

There is no data for this product.

Mobility in Environmental Media

No information available.

<u>Ozone</u>

Not applicable

Component Information

Acute Toxicity to Fish

<u>Titanium dioxide</u> LC50: > 1000 mg/L (Fathead Minnow - 96 hr.) <u>2-Butoxyethanol</u> LC50: 1490 mg/L (Bluegill sunfish - 96 hr.)

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method

Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

14. TRANSPORT INFORMATION

| TDG | Not regulated |
|-------------|---------------|
| ICAO / IATA | Not regulated |
| IMDG / IMO | Not regulated |

15. REGULATORY INFORMATION

International Inventories

| TSCA: United States | Yes - All components are listed or exempt. |
|---------------------|--|
| DSL: Canada | Yes - All components are listed or exempt. |

National Pollutant Release Inventory (NPRI)

NPRI Parts 1-4

This product contains the following Parts 1-4 NPRI chemicals:

| Chemical name | <u>CAS No</u> | <u>Weight-%</u> | <u>NPRI Parts 1- 4</u> |
|---|-----------------------|-----------------|------------------------|
| 2-Butoxyethanol | 111-76-2 | 1 - 5% | Listed |
| <u>NPRI Part 5</u> This product contains the following N | PRI Part 5 Chemicals: | | |
| <u>Chemical name</u> | <u>CAS No</u> | <u>Weight-%</u> | <u>NPRI Part 5</u> |
| 2-Butoxyethanol | 111-76-2 | 1 - 5% | Listed |

WHMIS Regulatory Status

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR

| 16. | OTHER | INFORMATION |
|-----|-------|-------------|
| | | |

HMIS

| Health hazards | 2* |
|---------------------|----|
| Flammability | 0 |
| Reactivity: | 0 |
| Personal protection | - |

HMIS Legend

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- * Chronic Hazard
- X Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada at

http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked_questions-questions_posees-eng.php.

Prepared By

Product Stewardship Department

| | 101 Paragon Drive Montvale, NJ 07645 800-225-5554 |
|---------------------|---|
| Revision Date: | 17-Oct-2023 |
| Reason for revision | Not available |

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

Benjamin Moore & Co.

End of Safety Data Sheet