



Revision Date: 18-Nov-2019 Revision Number: 2

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name ALIPHATIC ACRYLIC URETHANE GLOSS CATALYST

Product Code V500-90FR

Alternate Product Code
Product Class
Color
CATALYST
Light yellow
Recommended use
CATALYST

Restrictions on useNo information available

Manufactured For

Benjamin Moore & Co., Limited 8775 Keele Street Concord ON L4K 2N1 Phone: 1-800-361-5898 corotechcoatings.ca

<u>Manufacturer</u>

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 Phone: 1-866-708-9180 corotechcoatings.com Emergency Telephone CANUTEC: 613-996-6666

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the Hazardous Products Regulations (HPR: SOR/2015-17)

Acute toxicity - Inhalation (Vapors)	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Respiratory sensitization	Category 1
Skin sensitization	Category 1
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2

Label elements

Revision Date: 18-Nov-2019

Danger

Hazard statements

Harmful if inhaled

May cause allergy or asthma symptoms or breathing difficulties if inhaled

May cause an allergic skin reaction

May cause respiratory irritation

May cause damage to organs through prolonged or repeated exposure



Appearance liquid Odor slight, odorless

Precautionary Statements - Prevention

Use only outdoors or in a well-ventilated area
In case of inadequate ventilation wear respiratory protection
Contaminated work clothing should not be allowed out of the workplace
Wear protective gloves
Do not breathe dust/fume/gas/mist/vapors/spray

Precautionary Statements - Response

Get medical advice/attention if you feel unwell

Skin

IF ON SKIN: Wash with plenty of soap and water

If skin irritation or rash occurs: Get medical advice/attention

Wash contaminated clothing before reuse

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other information

No information available

Other hazards

IMPORTANT: Designed to be mixed with other components. Mixture will have hazards of all components. Before opening packages, read all warning labels. Follow all precautions.

3. COMPOSITION INFORMATION ON COMPONENTS

Chemical name	CAS No.	Weight-%	registry number	Date HMIRA filed and date exemption granted (if applicable)
Hexane, 1,6-diisocyanato-, homopolymer	28182-81-2	60 - 100%	(HMIRA registry #) -	-
Hexamethylene-1,6-diisocyanat e	822-06-0	0.1 - 0.25%	-	-

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

General Advice No hazards which require special first aid measures.

Eye Contact Rinse thoroughly with plenty of water for at least 15

minutes and consult a physician.

Skin Contact Wash off immediately with soap and plenty of water while

> removing all contaminated clothes and shoes. If skin irritation persists, call a physician. Wash clothing before reuse. Destroy contaminated articles such as shoes.

Revision Date: 18-Nov-2019

Inhalation Move to fresh air. If symptoms persist, call a physician.

Clean mouth with water and afterwards drink plenty of Ingestion

water. Consult a physician if necessary.

Most Important Symptoms/Effects May cause allergy or asthma symptoms or breathing

difficulties if inhaled. May cause allergic skin reaction.

Notes To Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Protective equipment and precautions for firefighters As in any fire, wear self-contained breathing apparatus

pressure-demand, MSHA/NIOSH (approved or equivalent)

and full protective gear.

Specific Hazards Arising From The Chemical Closed containers may rupture if exposed to fire or

extreme heat.

Sensitivity to mechanical impact No

V500-90FR - ALIPHATIC ACRYLIC URETHANE GLOSS CATALYST

Sensitivity to static discharge No

Flash Point Data

Flash point (°F) 442.0 Flash Point (°C) 227.8 Method PMCC

Flammability Limits In Air

Lower flammability limit:Not applicableUpper flammability limit:Not applicable

NFPA Health: 2 Flammability: 1 Instability: 1 Special: Not Applicable

NFPA Legend

0 - Not Hazardous

- 1 Slightly
- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Avoid contact with skin, eyes and clothing. Ensure

adequate ventilation.

Other Information Prevent further leakage or spillage if safe to do so.

Environmental precautionsSee Section 12 for additional Ecological Information.

Methods for Cleaning Up Soak up with inert absorbent material. Sweep up and

shovel into suitable containers for disposal.

7. HANDLING AND STORAGE

Handling Avoid contact with skin, eyes and clothing. Avoid breathing

vapors, spray mists or sanding dust. In case of insufficient

Revision Date: 18-Nov-2019

ventilation, wear suitable respiratory equipment.

Storage Keep container tightly closed. Keep out of the reach of

children.

Incompatible Materials No information available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits

Chemical name	ACGIH TLV	Alberta	British Columbia	Ontario	Quebec
Hexamethylene-1,6-diisocyan	0.005 ppm - TWA	0.005 ppm - TWA	0.005 ppm - TWA	0.005 ppm - TWA	0.005 ppm - TWAEV
ate		0.03 mg/m ³ - TWA	0.01 ppm - Ceiling	0.02 ppm - Ceiling	0.034 mg/m ³ - TWAEV
			Sensitizer		

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

Alberta - Alberta Occupational Exposure Limits

British Columbia - British Columbia Occupational Exposure Limits

Ontario - Ontario Occupational Exposure Limits Quebec - Quebec Occupational Exposure Limits

N/E - Not established

Engineering Measures

Ensure adequate ventilation, especially in confined areas.

Revision Date: 18-Nov-2019

Personal Protective Equipment

Eye/Face Protection Safety glasses with side-shields.

Skin Protection Protective gloves and impervious clothing.

Respiratory Protection In case of insufficient ventilation wear suitable respiratory

equipment.

Hygiene Measures Avoid contact with skin, eyes and clothing. Remove and

wash contaminated clothing before re-use. Wash

thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance liquid

Odor slight odorless

Odor Threshold No information available

Density (lbs/gal) 9.7 - 9.8 **Specific Gravity** 1.16 - 1.18

pH No information available

Viscosity (cps)

Solubility(ies)

Water solubility

Evaporation Rate

No information available
No information available
No information available

Evaporation RateNo information availableVapor pressureNo information availableVapor densityNo information available

 Wt. % Solids
 90 - 100

 Vol. % Solids
 90 - 100

 Wt. % Volatiles
 0 - 10

 Vol. % Volatiles
 0 - 10

Vol. % Volatiles 0 - 10
VOC Regulatory Limit (g/L) <250

Boiling Point (°F)

Boiling Point (°C)

Freezing point (°F)

No information available
No information available
No information available
No information available

Flash point (°F) 442.0
Flash Point (°C) 227.8
Method PMCC

Flammability (solid, gas)
Upper flammability limit:
Not applicable
Not applicable
Not applicable

Autoignition Temperature (°F)

No information available

Autoignition Temperature (°C)No information availableDecomposition Temperature (°F)No information availableDecomposition Temperature (°C)No information availablePartition coefficientNo information available

10. STABILITY AND REACTIVITY

Reactivity Not Applicable

Chemical Stability Stable under normal conditions.

Conditions to avoid Prevent from freezing.

Incompatible Materials No materials to be especially mentioned.

Hazardous Decomposition Products

None under normal use.

Possibility of hazardous reactionsNone under normal conditions of use.

11. TOXICOLOGICAL INFORMATION

Product Information

Information on likely routes of exposure

Principal Routes of Exposure Eye contact, skin contact and inhalation.

Acute Toxicity

Product Information No information available

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Eye contact May cause slight irritation

Skin contact Substance may cause slight skin irritation. Prolonged or

repeated contact may dry skin and cause irritation.

Inhalation May cause irritation of respiratory tract.

Ingestion Ingestion may cause gastrointestinal irritation, nausea,

vomiting and diarrhea.

Sensitization Respiratory sensitizer. May cause allergy or asthma

symptoms or breathing difficulties if inhaled. May cause an

Revision Date: 18-Nov-2019

allergic skin reaction.

No information available. **Neurological Effects Mutagenic Effects** No information available. **Reproductive Effects** No information available. **Developmental Effects** No information available. Target organ effects No information available. STOT - single exposure No information available. STOT - repeated exposure No information available. Other adverse effects No information available.

V500-90FR - ALIPHATIC ACRYLIC URETHANE GLOSS CATALYST

Aspiration Hazard

No information available.

Revision Date: 18-Nov-2019

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (inhalation-dust/mist) 4.6 mg/L ATEmix (inhalation-vapor) 11 mg/L

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Hexane, 1,6-diisocyanato-,	-	-	= 18500 mg/m ³ (Rat) 1 h
homopolymer 28182-81-2			
Hexamethylene-1,6-diisocyanate 822-06-0	= 746 mg/kg (Rat)	= 7001 mg/kg (Rat)	= 0.06 mg/L (Rat) 4 h

Carcinogenicity

There are no known carcinogenic chemicals in this product above reportable levels.

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

Product Information

Acute Toxicity to Fish

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

Persistence / Degradability

No information available.

Bioaccumulation

No information available.

Mobility in Environmental Media

No information available.

Ozone

No information available

Component Information

Acute Toxicity to Fish

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

Hexane, 1,6-diisocyanato-, homopolymer

EC50: > 1000 mg/L (Green algae (Scenedesmus subspicatus), 72 hrs.)

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method

Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

Revision Date: 18-Nov-2019

14. TRANSPORT INFORMATION

TDG Not regulated

ICAO / IATA Not regulated

IMDG / IMO Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA: United StatesYes - All components are listed or exempt.

Yes - All components are listed or exempt.

National Pollutant Release Inventory (NPRI)

NPRI Parts 1-4

This product contains the following Parts 1-4 NPRI chemicals:

None

NPRI Part 5

This product contains the following NPRI Part 5 Chemicals:

Revision Date: 18-Nov-2019

None

WHMIS Regulatory Status

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

16. OTHER INFORMATION

HMIS - Health: 2* Flammability: 1 Reactivity: 1 PPE: -

HMIS Legend

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- * Chronic Hazard
- X Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada at

http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked_questions-questions_posees-eng.php.

Prepared By Product Stewardship Department

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645

800-225-5554

Revision Date: 18-Nov-2019 **Reason for revision** Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

Revision Date: 18-Nov-2019

End of Safety Data Sheet