



Revision Date: 31-Jul-2018

Revision Number: 2

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name

Product Code Alternate Product Code Product Class Color Recommended use Restrictions on use

Manufacturer

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 Phone: 1-866-708-9180 corotechcoatings.com

BENJAMIN MOORE COROTECH QUICK-CURE SYSTEM POLYUREA BASECOAT QC TAN V530-53 V53053 SOLVENT THINNED PAINT Beige Industrial paint

Emergency Telephone

No information available

CHEMTREC (US): 800-424-9300 CHEMTREC (outside US): (703)-527-3887

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

| Serious eye damage/eye irritation | Category 2A |
|-----------------------------------|-------------|

Label elements

Warning Hazard statements Causes serious eye irritation

Appearance liquid

Odor characteristic

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling Wear eve/face protection

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

Hazards not otherwise classified (HNOC)

Not applicable

Other information

No information available

Other hazards

IMPORTANT: Designed to be mixed with other components. Mixture will have hazards of all components. Before opening packages, read all warning labels. Follow all precautions.

CAUTION: All floor coatings may become slippery when wet. Where non-skid characteristics are desired, use an appropriate anti-slip aggregate.

3. COMPOSITION INFORMATION ON COMPONENTS

| Chemical name | CAS No. | Weight-% |
|-----------------------------------|------------|----------|
| Kaolin, calcined | 66402-68-4 | 20 |
| Titanium dioxide | 13463-67-7 | 20 |
| Glycidoxy propyl trimethoxysilane | 2530-83-8 | 5 |

4. FIRST AID MEASURES

| General Advice | No hazards which require special first aid measures. |
|------------------------------------|---|
| Eye Contact | Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. |
| Skin Contact | Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. |
| Inhalation | Move to fresh air. If symptoms persist, call a physician. |
| Ingestion | Clean mouth with water and afterwards drink plenty of water. Consult a physician if necessary. |
| Most Important Symptoms/Effects | None known. |

| Notes To Physic | cian | Treat symptomatical | ly. | | |
|--|---------------|---------------------------------|--|--|----|
| | | 5. FIRE-FIGH | TING MEASUR | ES | |
| Suitable Exting | uishing Media | | | measures that are appropria the surrounding environme | |
| Protective Equipment And Precautions For Firefighters | | pressure-demand, | As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. | | |
| Specific Hazards Arising From The Chemical | | Closed containers extreme heat. | Closed containers may rupture if exposed to fire or extreme heat. | | |
| Sensitivity To Mechanical Impact | | No | | | |
| Sensitivity To Static Discharge | | No | No | | |
| Flash Point Data Flash Point (Flash Point (Method | (°F) | | 442.2 227.9 PMCC | | |
| Flammability Li | mits In Air | | | | |
| Lower flamn Upper flamn | | | Not applicable Not applicable | | |
| <u>NFPA</u> Heal | th: 1 | Flammability: 1 | Instability: 0 | Special: Not Applicab | le |
| NFPA Legend 0 - Not Hazardous 1 - Slightly 2 - Moderate | | | | | |

3 - High

4 - Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6. ACCIDENTAL RELEASE MEASURES

| Personal Precautions | Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. |
|---------------------------|---|
| Other Information | Prevent further leakage or spillage if safe to do so. |
| Environmental precautions | See Section 12 for additional Ecological Information. |
| Methods for Cleaning Up | Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal. |

7. HANDLING AND STORAGE

| Handling | Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment. |
|------------------------|--|
| Storage | Keep container tightly closed. Keep out of the reach of children. |
| Incompatible Materials | No information available |

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits

| Chemical name | ACGIH TLV | OSHA PEL |
|------------------|--|----------------|
| Kaolin, calcined | 5 mg/m ³ - TWA 0.02 mg/m ³ - TWA | 5 mg/m³ - TWA |
| | 0.1 mg/m ³ - TWA | |
| | 10 mg/m ³ - STEL | |
| Titanium dioxide | 10 mg/m ³ - TWA | 15 mg/m³ - TWA |

Legend

ACGIH - American Conference of Governmental Industrial Hygienists Exposure Limits OSHA - Occupational Safety & Health Administration Exposure Limits N/E - Not Established

| Engineering Measures | Ensure adequate ventilation, especially in confined areas. | |
|---|---|--|
| Personal Protective Equipment Eye/Face Protection Skin Protection Respiratory Protection | Safety glasses with side-shields. Protective gloves and impervious clothing. In case of insufficient ventilation wear suitable respiratory equipment. | |
| Hygiene Measures | Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling. | |

9. PHYSICAL AND CHEMICAL PROPERTIES

| Appearance | liquid |
|-----------------------------|--------------------------|
| Odor | characteristic |
| Odor Threshold | No information available |
| Density (lbs/gal) | 10.7 - 10.8 |
| Specific Gravity | 1.28 - 1.30 |
| pH | No information available |
| Viscosity (cps) | No information available |
| Solubility(ies) | No information available |
| Water solubility | No information available |
| Evaporation Rate | No information available |
| Vapor pressure @20 °C (kPa) | No information available |
| Vapor density | No information available |
| Wt. % Solids | 90 - 100 |
| Wt. % Solids | 90 - 100 |
| Vol. % Solids | 90 - 100 |

V530-53 - BENJAMIN MOORE COROTECH QUICK-CURE SYSTEM POLYUREA BASECOAT QC TAN

Wt. % Volatiles Vol. % Volatiles VOC Regulatory Limit (g/L) Boiling Point (°F) Boiling Point (°C) Freezing Point (°F) Freezing Point (°C) Flash Point (°F) Flash Point (°C) Method Flammability (solid, gas) Upper flammability limit: Lower flammability limit: Autoignition Temperature (°F) Autoignition Temperature (°C) Decomposition Temperature (°F) **Decomposition Temperature (°C)** Partition coefficient

0 - 10 0 - 10 < 100 595.0 313.0 No information available No information available 442.2 227.9 PMCC Not applicable Not applicable Not applicable No information available No information available No information available No information available No information available

10. STABILITY AND REACTIVITY

| Reactivity | Not Applicable |
|------------------------------------|--|
| Chemical Stability | Stable under normal conditions. |
| Conditions to avoid | Prevent from freezing. |
| Incompatible Materials | No materials to be especially mentioned. |
| Hazardous Decomposition Products | None under normal use. |
| Possibility of hazardous reactions | None under normal conditions of use. |

11. TOXICOLOGICAL INFORMATION

| Product Information | | | |
|--|---|--|--|
| Information on likely routes of exposure | | | |
| Principal Routes of Exposure | Eye contact, skin contact and inhalation. | | |
| Acute Toxicity | | | |
| Product Information | No information available | | |
| Symptoms related to the physical, chemical and toxicological characteristics | | | |
| Symptoms | No information available | | |
| Delayed and immediate effects as well as chronic effects from short and long-term exposure | | | |
| Eye contact | Causes eye irritation. | | |
| | | | |

| Skin contact | Substance may cause slight skin irritation. Prolonged or repeated contact may dry skin and cause irritation. |
|--------------------------|--|
| Inhalation | May cause irritation of respiratory tract. |
| Ingestion | Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. |
| Sensitization | No information available |
| Neurological Effects | No information available. |
| Mutagenic Effects | No information available. |
| Reproductive Effects | No information available. |
| Developmental Effects | No information available. |
| Target organ effects | No information available. |
| STOT - single exposure | No information available. |
| STOT - repeated exposure | No information available. |
| Other adverse effects | No information available. |
| Aspiration Hazard | No information available |

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

| ATEmix (oral) | 7190 mg/kg |
|-----------------|------------|
| ATEmix (dermal) | 387668 |

Component Information

<u>Titanium dioxide</u> LD50 Oral: > 10000 mg/kg (Rat) <u>Glycidoxy propyl trimethoxysilane</u> LD50 Oral: 22.6 ml/kg (Rat) LD50 Dermal: 3970 µL/kg (Rabbit)

Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

| Chemical name | IARC | NTP | OSHA |
|------------------|---------------------|-----|--------|
| | 2B - Possible Human | | Listed |
| Titanium dioxide | Carcinogen | | |

• Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

Legend

IARC - International Agency for Research on Cancer NTP - National Toxicity Program OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

Product Information

Acute Toxicity to Fish No information available

Acute Toxicity to Aquatic Invertebrates

No information available

<u>Acute Toxicity to Aquatic Plants</u> No information available

Persistence / Degradability

No information available.

Bioaccumulation

No information available.

Mobility in Environmental Media

No information available.

<u>Ozone</u>

No information available

Component Information

Acute Toxicity to Fish

<u>Titanium dioxide</u> LC50: > 1000 mg/L (Fathead Minnow - 96 hr.)

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

| | 13. DISPOSAL CONSIDERATIONS | |
|-----------------------|---|--|
| Waste Disposal Method | Dispose of in accordance with federal, state, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options. | |
| | 14. TRANSPORT INFORMATION | |
| DOT | Not regulated | |
| ΙCAO / ΙΑΤΑ | Not regulated | |
| IMDG / IMO | Not regulated | |
| | 15. REGULATORY INFORMATION | |

International Inventories

| TSCA: United States | Yes - All components are listed or exempt. |
|---------------------|--|
| DSL: Canada | Yes - All components are listed or exempt. |

Federal Regulations

SARA 311/312 hazardous categorization

| Acute health hazard | Yes |
|-----------------------------------|-----|
| Chronic Health Hazard | No |
| Fire hazard | No |
| Sudden release of pressure hazard | No |
| Reactive Hazard | No |

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

| Chemical name | CAS No. | <u>Weight-%</u> | CERCLA/SARA 313 (de minimis concentration) |
|------------------|------------|-----------------|---|
| Kaolin, calcined | 66402-68-4 | 20 | 1.0 |

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

None

US State Regulations

California Proposition 65

MARNING: Cancer and Reproductive Harm– www.P65warnings.ca.gov

State Right-to-Know

| Chemical name | Massachusetts | New Jersey | Pennsylvania |
|------------------|---------------|------------|--------------|
| Kaolin, calcined | | X | X |
| Titanium dioxide | Х | X | X |

Legend

X - Listed

16. OTHER INFORMATION

| <u>HMIS</u> - | Health: 1 | Flammability: 1 | Reactivity: 0 | PPE: - |
|---------------|-----------|-----------------|---------------|--------|
| | | | | |

HMIS Legend

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- * Chronic Hazard

X - Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

| Prepared By | Product Stewardship Department Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 800-225-5554 |
|------------------|---|
| Revision Date: | 31-Jul-2018 |
| Revision Summary | Not available |

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

END OF SAFETY DATA SHEET