



Revision Date: 04-Apr-2022

**Revision Number:** 2

1. PRODUCT AND COMPANY IDENTIFICATION

# Product Name Product Code Alternate Product Code Product Class Color Recommended use Restrictions on use

# COROTECH DTM MASTIC URETHANE CATALYST V570-90FR

A57090 CATALYST Light yellow CATALYST No information available

## **Manufactured For**

Benjamin Moore & Co., Limited 8775 Keele Street Concord ON L4K 2N1 Phone: 1-800-361-5898 www.benjaminmoore.ca/corotech

# Manufacturer

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 Phone: 1-866-708-9180 www.benjaminmoore.com/Corotech

# Emergency Telephone CHEMTREC: +1 703-741-5970 / 1-800-424-9300

+1 703-527-3887 (outside US & Canada) CANUTEC: 613-996-6666 (Transport Emergency Only)

2. HAZARDS IDENTIFICATION

# **Classification**

This chemical is considered hazardous by the Hazardous Products Regulations (HPR: SOR/2015-17)

Acute toxicity - Inhalation (Gases)	Category 4
Acute toxicity - Inhalation (Vapors)	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Respiratory sensitization	Category 1
Skin sensitization	Category 1
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2

# Label elements

## Danger

## Hazard statements

Harmful if inhaled May cause allergy or asthma symptoms or breathing difficulties if inhaled May cause an allergic skin reaction May cause respiratory irritation May cause damage to organs through prolonged or repeated exposure



Appearance liquid

Odor little or no odor

# **Precautionary Statements - Prevention**

Use only outdoors or in a well-ventilated area In case of inadequate ventilation wear respiratory protection Contaminated work clothing should not be allowed out of the workplace Wear protective gloves Do not breathe dust/fume/gas/mist/vapors/spray

## **Precautionary Statements - Response**

Get medical advice/attention if you feel unwell **Skin** IF ON SKIN: Wash with plenty of soap and water If skin irritation or rash occurs: Get medical advice/attention Wash contaminated clothing before reuse **Inhalation** 

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician

## **Precautionary Statements - Storage**

Store in a well-ventilated place. Keep container tightly closed Store locked up

## Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

## Other information

No information available

**IMPORTANT:** Designed to be mixed with other components. Mixture will have hazards of all components. Before opening packages, read all warning labels. Follow all precautions.

# 3. COMPOSITION INFORMATION ON COMPONENTS

Chemical name	CAS No.	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Hexane, 1,6-diisocyanato-, homopolymer	28182-81-2	60 - 100%	-	-
Hexamethylene-1,6-diisocyanat e	822-06-0	0.1 - 0.25%	-	-

\*The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AI	D MEASURES
General Advice	No hazards which require special first aid measures.
Eye Contact	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
Skin Contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician. Wash clothing before reuse. Destroy contaminated articles such as shoes.
Inhalation	Move to fresh air. If symptoms persist, call a physician.
Ingestion	Clean mouth with water and afterwards drink plenty of water. Consult a physician if necessary.
Most Important Symptoms/Effects	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause allergic skin reaction.
Notes To Physician	Treat symptomatically.
5. FIRE-FIGHT	ING MEASURES
Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Protective equipment and precautions for firefighters	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.
Specific Hazards Arising From The Chemical	Closed containers may rupture if exposed to fire or extreme heat.
Sensitivity to mechanical impact	No
Sensitivity to static discharge	No

Flash Point Data Flash point (°F) Flash Point (°C) Method	460 238 PMCC
Flammability Limits In Air	
Lower flammability limit: Upper flammability limit:	Not applicable Not applicable
NFPA Health: 2 Flammability: 1	Instability: 1 Special: Not Applicable
NFPA Legend 0 - Not Hazardous 1 - Slightly 2 - Moderate 3 - High 4 - Severe	

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

# 6. ACCIDENTAL RELEASE MEASURES

**Personal Precautions** 

Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.

**Other Information** 

Environmental precautions

Methods for Cleaning Up

See Section 12 for additional Ecological Information.

Prevent further leakage or spillage if safe to do so.

Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

7. HANDLING AND STORAGE

Handling

Storage

Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.

Keep container tightly closed. Keep out of the reach of children.

**Incompatible Materials** 

No information available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## **Exposure Limits**

Chemical name	ACGIH TLV	Alberta	British Columbia	Ontario	Quebec

# V570-90FR - COROTECH DTM MASTIC URETHANE CATALYST

Hexamethylene-1,6-diisocyan	TWA: 0.005 ppm	0.005 ppm - TWA	0.005 ppm - TWA	0.005 ppm - TWA	0.005 ppm - TWAEV
ate		0.03 mg/m³ - TWA	0.01 ppm - Ceiling Respiratory Sensitizer	0.02 ppm - Ceiling	0.034 mg/m³ - TWAEV
Legend ACGIH - American Conference Alberta - Alberta Occupational E British Columbia - British Colum Ontario - Ontario Occupational Quebec - Quebec Occupational N/E - Not established	Exposure Limits ibia Occupational Expo Exposure Limits	,,,			
Engineering Measures		Er	nsure adequate vent	ilation, especially	in confined areas.
Personal Protective Equ	uipment				
Eye/Face Protection			afety glasses with sid		
Skin Protection			otective gloves and		
Respiratory Protecti	on		case of insufficient juipment.	ventilation wear su	uitable respiratory
Hygiene Measures			void contact with ski ash contaminated cl		

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Odor **Odor Threshold** Density (lbs/gal) **Specific Gravity** bН Viscosity (cps) Solubility(ies) Water solubility **Evaporation Rate** Vapor pressure Vapor density Wt. % Solids Vol. % Solids Wt. % Volatiles Vol. % Volatiles VOC Regulatory Limit (g/L) Boiling Point (°F) **Boiling Point (°C)** Freezing point (°F) Freezing Point (°C) Flash point (°F) Flash Point (°C) Method Flammability (solid, gas) Upper flammability limit: Lower flammability limit: Autoignition Temperature (°F) Autoignition Temperature (°C) Decomposition Temperature (°F)

liquid little or no odor No information available 9.5 - 9.9 1.13 - 1.19 No information available 90 - 100 90 - 100 0 - 10 0 - 10 < 250 No information available No information available No information available No information available 460 238 PMCC Not applicable Not applicable Not applicable No information available No information available No information available

thoroughly after handling.

Decomposition Temperature (°C) Partition coefficient No information available No information available

**10. STABILITY AND REACTIVITY** 

Reactivity	Not Applicable
Chemical Stability	Stable under normal conditions.
Conditions to avoid	Prevent from freezing.
Incompatible Materials	No materials to be especially mentioned.
Hazardous Decomposition Products	None under normal use.
Possibility of hazardous reactions	None under normal conditions of use.

# **11. TOXICOLOGICAL INFORMATION**

## Product Information Information on likely routes of exposure

**Principal Routes of Exposure** 

Eye contact, skin contact and inhalation.

Acute Toxicity Product Information

No information available

Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** 

No information available

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

Eye contact Skin contact	May cause slight irritation Substance may cause slight skin irritation. Prolonged or repeated contact may dry skin and cause irritation.
Inhalation	May cause irritation of respiratory tract.
Ingestion	Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Sensitization	Respiratory sensitizer. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.
Neurological Effects	No information available.
Mutagenic Effects	No information available.
Reproductive Effects	No information available.
Developmental Effects	No information available.
Target organ effects	No information available.
STOT - single exposure	May cause disorder and damage to the. Respiratory system. Lungs.
STOT - repeated exposure	Causes damage to organs through prolonged or repeated exposure if inhaled.

# Other adverse effects Aspiration Hazard

No information available. No information available.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (inhalation-dust/mist)	4.6	mg/L
ATEmix (inhalation-vapor)	11	mg/L

#### **Component Information**

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Hexane, 1,6-diisocyanato-,	-	-	= 18500 mg/m <sup>3</sup> (Rat)1 h
homopolymer 28182-81-2			
Hexamethylene-1,6-diisocyanate 822-06-0	= 746 mg/kg (Rat)	= 7001 mg/kg(Rat)	= 0.06 mg/L (Rat)4 h

# Chronic Toxicity

# Carcinogenicity

There are no known carcinogenic chemicals in this product above reportable levels.

**12. ECOLOGICAL INFORMATION** 

## **Ecotoxicity Effects**

The environmental impact of this product has not been fully investigated.

## **Product Information**

## **Acute Toxicity to Fish**

No information available

## Acute Toxicity to Aquatic Invertebrates

No information available

## Acute Toxicity to Aquatic Plants

No information available

## Persistence / Degradability

No information available.

# **Bioaccumulation**

No information available.

# Mobility in Environmental Media

No information available.

#### <u>Ozone</u>

No information available

# **Component Information**

Acute Toxicity to Fish No information available

Acute Toxicity to Aquatic Invertebrates No information available

No information available

# Acute Toxicity to Aquatic Plants

<u>Hexane, 1,6-diisocyanato-, homopolymer</u> EC50: > 1000 mg/L (Green algae (Scenedesmus subspicatus), 72 hrs.)

# **13. DISPOSAL CONSIDERATIONS**

## Waste Disposal Method

Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

# 14. TRANSPORT INFORMATION

TDG

ICAO / IATA

IMDG / IMO

Not regulated

Not regulated

Not regulated

# 15. REGULATORY INFORMATION

# International Inventories

TSCA: United States	Yes - All components are listed or exempt.
DSL: Canada	Yes - All components are listed or exempt.

# National Pollutant Release Inventory (NPRI)

## NPRI Parts 1-4

This product contains the following Parts 1-4 NPRI chemicals:

None


#### NPRI Part 5

This product contains the following NPRI Part 5 Chemicals:

None

#### WHMIS Regulatory Status

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.



**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada at

http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked\_questions-questions\_posees-eng.php.

Prepared By	Product Stewardship Department Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 800-225-5554
Issuing Date	31-Mar-2022
Revision Date: Reason for revision	04-Apr-2022 Not available

#### **Disclaimer**

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown

above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

**End of Safety Data Sheet**