



Revision Date: 17-Feb-2023

**Revision Number:** 4

1. PRODUCT AND COMPANY IDENTIFICATION

### **Product Name**

Product Code Alternate Product Code Product Class Color Recommended use Restrictions on use

### Manufactured For

Benjamin Moore & Co., Limited 8775 Keele Street Concord ON L4K 2N1 Phone: 1-800-361-5898 www.benjaminmoore.ca/corotech

### **Manufacturer**

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 Phone: 1-866-708-9180 www.benjaminmoore.com/Corotech

# COROTECH COMMAND WATERBORNE ACRYLIC URETHANE SATIN BASE 3

V3923XFR A3923X Water thinned paint All Paint No information available

> Emergency Telephone CHEMTREC: +1 703-741-5970 / 1-800-424-9300 +1 703-527-3887 (outside US & Canada) CANUTEC: 613-996-6666 (Transport Emergency Only)

2. HAZARDS IDENTIFICATION

## **Classification**

This chemical is considered hazardous by the Hazardous Products Regulations (HPR: SOR/2015-17)

Skin sensitization	Category 1A
Germ cell mutagenicity	Category 1B
Reproductive toxicity	Category 1B

### Label elements

Danger

Hazard statements

Odor little or no odor

May cause an allergic skin reaction May cause genetic defects May damage fertility or the unborn child **Control of the control of the control** 

Precautionary Statements - Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Avoid breathing dust/fume/gas/mist/vapors/spray Contaminated work clothing must not be allowed out of the workplace Wear protective gloves

### **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention Skin IF ON SKIN: Wash with plenty of soap and water If skin irritation or rash occurs: Get medical advice/attention

Wash contaminated clothing before reuse

## **Precautionary Statements - Storage**

Store locked up

### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

### Other information

No information available

**CAUTION:** All floor coatings may become slippery when wet. Where non-skid characteristics are desired, use an appropriate anti-slip aggregate.

**WARNING:** This product contains isothiazolinone compounds at levels of <0.1%. These substances are biocides commonly found in most paints and a variety of personal care products as a preservative. Certain individuals may be sensitive or allergic to these substances, even at low levels.

## 3. COMPOSITION INFORMATION ON COMPONENTS

Chemical name	CAS No	Weight-%	Hazardous Material	Date HMIRA filed and
		_	Information Review Act	date exemption granted
			registry number (HMIRA	(if applicable)

### V3923XFR - COROTECH COMMAND WATERBORNE ACRYLIC URETHANE SATIN BASE 3

ГТ				
			registry #)	
Titanium dioxide	13463-67-7	1 - 5%	-	-
Kaolin	1332-58-7	1 - 5%	-	-
Ethylene glycol	1559-35-9	1 - 5%	-	-
mono-2-ethylhexyl ether				
Zinc phosphate	7779-90-0	1 - 5%	-	-
Ammonium hydroxide	1336-21-6	0.25 - 0.5%	-	-
Alcohols, C12 - 14, ethoxylated	68439-50-9	0.25 - 0.5%	-	-
Poly(oxy-1,2-ethanediyl),	104810-48-2	0.1 - 0.25%	-	-
.alpha[3-[3-(2H-benzotriazol-2-				
yl)-5-(1,1-dimethylethyl)-4-hydro				
xyphenyl]-1-oxopropyl]omega				
hydroxy-				
Carbamic acid,	10605-21-7	0.1 - 0.25%	-	-
1H-benzimidazol-2-yl-, methyl				
ester				
Poly(oxy-1,2-ethanediyl),	104810-47-1	0.1 - 0.25%	-	-
.alpha[3-[3-(2H-benzotriazol-2-				
yl)-5-(1,1-dimethylethyl)-4-hydro				
xyphenyl]-1-oxopropyl]omega				
[3-[3-(2H-benzotriazol-2-yl)-5-(1,				
1-dimethylethyl)-4-hydroxyphen				
yl]-1-oxoprop				
Decanedioic acid,	41556-26-7	0.1 - 0.25%	-	-
bis(1,2,2,6,6-pentamethyl-4-pip				
eridinyl) ester				

\*The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

General Advice	If symptoms persist, call a physician. Show this safety data sheet to the doctor in attendance.
Eye Contact	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
Skin Contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician. Wash clothing before reuse. Destroy contaminated articles such as shoes.
Inhalation	Move to fresh air. If symptoms persist, call a physician.
Ingestion	Clean mouth with water and afterwards drink plenty of water. Consult a physician if necessary.
Most Important Symptoms/Effects	May cause allergic skin reaction.
Notes To Physician	Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Protective equipment and precautions for firefighters	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.
Specific Hazards Arising From The Chemical	Closed containers may rupture if exposed to fire or extreme heat.
Sensitivity to mechanical impact	No
Sensitivity to static discharge	No
Flash Point Data Flash point (°F) Flash Point (°C) Method	250 121 PMCC
Flammability Limits In Air	
Lower flammability limit: Upper flammability limit:	Not applicable Not applicable
NFPA Health hazards Flammability Stability Special:	2 0 0 Not Applicable

#### **NFPA Legend** 0 - Not Hazardous

- 1 Slightly
- 2 Moderate
- 3 High 4 - Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

# 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.
Other Information	Prevent further leakage or spillage if safe to do so.
Environmental precautions	See Section 12 for additional Ecological Information.
Methods for Cleaning Up	Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

# 7. HANDLING AND STORAGE

Handling

Storage

### **Incompatible Materials**

Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.

Keep container tightly closed. Keep out of the reach of children.

No information available

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### **Exposure Limits**

Chemical name	ACGIH TLV	Alberta	British Columbia	Ontario	Quebec
Titanium dioxide	TWA: 0.2 mg/m <sup>3</sup>	10 mg/m³ - TWA	10 mg/m <sup>3</sup> - TWA	10 mg/m³ - TWA	10 mg/m <sup>3</sup> - TWAEV
	nanoscale respirable	-	3 mg/m <sup>3</sup> - TWA	-	-
	particulate matter				
	TWA: 2.5 mg/m <sup>3</sup>				
	finescale respirable				
	particulate matter				
Kaolin	TWA: 2 mg/m <sup>3</sup>	2 mg/m <sup>3</sup> - TWA	2 mg/m <sup>3</sup> - TWA	2 mg/m³ - TWA	5 mg/m <sup>3</sup> - TWAEV
	particulate matter		-		-
	containing no asbestos				
	and <1% crystalline				
	silica, respirable				
	particulate matter				
Ammonium hydroxide	STEL: 35 ppm	-	-	-	-
	TWA: 25 ppm				

#### Legend

ACGIH - American Conference of Governmental Industrial Hygienists Alberta - Alberta Occupational Exposure Limits British Columbia - British Columbia Occupational Exposure Limits

Ontario - Ontario Occupational Exposure Limits

Quebec - Quebec Occupational Exposure Limits

N/E - Not established

### **Engineering Measures**

Personal Protective Equipment Eye/Face Protection Skin Protection Respiratory Protection Ensure adequate ventilation, especially in confined areas.

Safety glasses with side-shields Protective gloves and impervious clothing. Use only with adequate ventilation. In operations where exposure limits are exceeded, use a NIOSH approved respirator that has been selected by a technically qualified person for the specific work conditions. When spraying the product or applying in confined areas, wear a NIOSH approved respirator specified for paint spray or organic vapors.

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Hygiene Measures

Appearance Odor **Odor Threshold** Density (lbs./gal) **Specific Gravity** Hα Viscosity (cps) Solubility(ies) Water solubility **Evaporation Rate** Vapor pressure @20 °C (kPa) Relative vapor density Wt. % Solids Vol. % Solids Wt. % Volatiles Vol. % Volatiles VOC Regulatory Limit (g/L) Boiling Point (°F) Boiling Point (°C) Freezing point (°F) Freezing Point (°C) Flash point (°F) Flash Point (°C) Method Flammability (solid, gas) Upper flammability limit: Lower flammability limit: Autoignition Temperature (°F) Autoignition Temperature (°C) **Decomposition Temperature (°F) Decomposition Temperature (°C) Partition coefficient** 

liquid little or no odor No information available 9.1 - 9.51.09 - 1.14 No information available 40 - 50 30 - 40 50 - 60 60 - 70 < 150 212 100 32 0 250 121 PMCC Not applicable Not applicable Not applicable No information available No information available No information available No information available No information available

# **10. STABILITY AND REACTIVITY**

Reactivity	Not Applicable
Chemical Stability Stable under normal conditions	
Conditions to avoid	Prevent from freezing.
Incompatible Materials	No materials to be especially mentioned.
Hazardous Decomposition Products	None under normal use.
Possibility of hazardous reactions	None under normal conditions of use.

# 11. TOXICOLOGICAL INFORMATION

Product Information

Information on likely routes of exposure	
Principal Routes of Exposure	Eye contact, skin contact and inhalation.
Acute Toxicity Product Information	No information available
Symptoms related to the physical, chemical and toxic	ological characteristics
Symptoms	No information available
Delayed and immediate effects as well as chronic effe	ects from short and long-term exposure
Eye contact Skin contact	May cause slight irritation Substance may cause slight skin irritation. Prolonged or repeated contact may dry skin and cause irritation.
Inhalation Ingestion	May cause irritation of respiratory tract. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Sensitization Neurological Effects Mutagenic Effects Reproductive Effects Developmental Effects Target organ effects STOT - single exposure STOT - repeated exposure Other adverse effects Aspiration Hazard	May cause an allergic skin reaction. No information available. Suspected of causing genetic defects. May damage fertility or the unborn child. No information available. No information available. No information available. No information available. No information available. No information available.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	26635 mg/kg
ATEmix (inhalation-dust/mist)	295.5 mg/l

### **Component Information**

Caution - This mixture contains a substance not yet fully tested

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-
Kaolin 1332-58-7	> 5000 mg/kg (Rat)	> 5000 mg/kg (Rat)	-
Ethylene glycol mono-2-ethylhexyl ether 1559-35-9	= 3080 mg/kg (Rat)	= 2120 mg/kg (Rabbit)= 2120 μL/kg (Rabbit)	-
Zinc phosphate 7779-90-0	> 5000 mg/kg (Rat)	-	-
Ammonium hydroxide 1336-21-6	= 350 mg/kg(Rat)	-	-
Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester 10605-21-7	> 5050 mg/kg (Rat)	> 10000 mg/kg (Rabbit)	-
Decanedioic acid, bis(1,2,2,6,6-pentamethyl-4-piperidi	= 2615 mg/kg (Rat)	-	-

nyl) ester 41556-26-7		

### Chronic Toxicity

### Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

Chemical name	IARC	NTP
	2B - Possible Human Carcinogen	
Titanium dioxide		

• Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

### Legend

IARC - International Agency for Research on Cancer NTP - National Toxicity Program OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

## **Ecotoxicity Effects**

The environmental impact of this product has not been fully investigated.

## **Product Information**

### Acute Toxicity to Fish

No information available

### Acute Toxicity to Aquatic Invertebrates

No information available

### Acute Toxicity to Aquatic Plants

No information available

#### Persistence / Degradability

No information available.

#### **Bioaccumulation**

There is no data for this product.

### Mobility in Environmental Media

No information available.

#### Ozone

Not applicable

## **Component Information**

### Acute Toxicity to Fish

<u>Titanium dioxide</u> LC50: > 1000 mg/L (Fathead Minnow - 96 hr.) <u>Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester</u> LC50: 1.5 mg/L (Rainbow Trout - 96 hr.)

### Acute Toxicity to Aquatic Invertebrates

Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester LC50: 0.22 mg/L (water flea - 48 hr.)

### Acute Toxicity to Aquatic Plants

No information available

**13. DISPOSAL CONSIDERATIONS** 

Waste Disposal Method

Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

# 14. TRANSPORT INFORMATION

TDG

Not regulated

ICAO / IATA

IMDG / IMO

Not regulated

**15. REGULATORY INFORMATION** 

## International Inventories

**TSCA: United States**Yes - All components are listed or exempt.**DSL: Canada**Yes - All components are listed or exempt.

# National Pollutant Release Inventory (NPRI)

### NPRI Parts 1-4

This product contains the following Parts 1-4 NPRI chemicals:

None

### NPRI Part 5

This product contains the following NPRI Part 5 Chemicals:

### None

### WHMIS Regulatory Status

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR

## 16. OTHER INFORMATION

#### HMIS

2*
1
0
-

### **HMIS Legend**

0 - Minimal Hazard

1 - Slight Hazard

2 - Moderate Hazard

- 3 Serious Hazard
- 4 Severe Hazard
- \* Chronic Hazard

X - Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada at

http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked\_questions-questions\_posees-eng.php.

Prepared By	Product Stewardship Department Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 800-225-5554
Issuing Date	03-Dec-2021
Revision Date: Reason for revision	17-Feb-2023 Not available

**Disclaimer** 

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

## **End of Safety Data Sheet**