

# Woodluxe®

WOOD STAIN REMOVER K015

# **General Description**

Designed to strip stains and finishes from exterior wood surfaces. Also remove stains from mould, mildew, algae, dirt and water, restoring the natural wood tone. Ideal for use on exterior wood decking, siding, fencing, shakes and furniture. Product does not control mould, mildew, fungus or algae, only removes stains.

- · Removes both latex and oil finishes
- Fast-acting
- Concentrated formula

#### Usage

Residential or commercial applications. Previously finished, exterior wood surfaces.

#### **Technical Data**

Max Mixing Ratio (Water: Remover) 4:1

**Coverage at Max Dilution** 46.4 – 92.9 sq. m. (4 x 3.78 L Water, 3.78 Remover) (500 – 1000 sq. ft)

Depending on substrate and application method

Surface	Min:	10 ° C (50 °F)
Temperature During		, ,
Application	Max:	32.2 °C (90 °F)
Clean Up		Clean Water
Thinner		Clean Water
Weight Per Gallon		4.1 kg (9.1 lbs.)
Storage	Min:	4.4 ° C (40 °F)
Temperature	Max:	32.2 °C 90 °F
VOC		147 g/L

## **Surface Preparation**

Project surfaces may be damp or dry. Do not apply if surface temperature is below 10 °C (50 °F). Protect adjacent surfaces; cover with plastic and/or tape off any areas not being stripped. Pre-wet and/or cover vegetation; rinsing residue will not harm plants or roots. Exposure to concentrate may burn foliage.

**PRIOR TO APPLICATION:** Determine proper dilution. Test a small, inconspicuous area and allow to dry before general use. Before and after application, liberally spray surrounding plants and vegetation with water. Avoid contact with metal, lawn furniture and fabric. If necessary, protect adjacent surfaces with plastic.

## Application

Mixing Recommendations:

Multiple Coats / Solid or Semi Solid Stain

Do not dilute

Weathered Solid Colour or Semi Solid Stain

3.78 L water: 3.78 L remover Semi Transparent Stain 2 x 3.78 L water: 3.78 L remover Transparent/Translucent Stain 3 x 3.78 L water: 3.78 L remover

Clear Finishes

4 x 3.78 L water: 3.78 L remover

**DO NOT MIX CLEANER IN METAL CONTAINERS.**NEVER MIX OR USE WITH OTHER CLEANERS OR CHEMICALS.

- 1) Apply product liberally to surface with plastic garden sprayer, brush or roller.
- 2) Allow solution to stand for 10-30 minutes, depending upon age and type of finish to be removed.
- 3) Agitate with stiff bristle brush in direction of wood grain and rinse using a garden hose with nozzle or power washer.
- 4) Neutralize surface with Woodluxe® Wood Brightener and Neutralizer (K017) following label directions.
- 5) Allow to dry thoroughly. **Note:** When applying to vertical surfaces, apply from bottom to top.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @ https://www.canada.ca/en/health-canada/services/environmental-workplace-

health/environmental-workplace-health/environmental-contaminants/lead/lead-information-package-some-commonly-asked-questions-about-lead-human-health.html

# Limitations

- Do not apply when air and surface temperatures are below 10 °C (50 °F)
- Remover (K015) may darken certain wood types during application. If desired, use Wood Brightener & Neutralizer (K017) to restore wood colour back to its natural appearance.

#### Clean Up

Clean equipment with warm, soapy water.

### **Technical Assistance**

Available through your local authorized independent Benjamin Moore retailer.

call 1-866-708-9180

visit www.benjaminmoore.ca

#### **Environmental Health & Safety Information**

DANGER CORROSIVE

#### **CAUSES BURNS**

Do not swallow.
Do not get in eyes.
Do not get on skin or clothing.
Do not breathe fumes.

Handle with care.
Keep out of reach of children.
Wear rubber gloves and safety glasses.
Use only in a well-ventilated area.
Wear a mask or respirator.

### FIRST AID TREATMENT

Contains sodium hydroxide & sodium metasilicate. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes. If on skin, rinse well with water. If on clothes, remove clothes. If breathed in, move person to fresh air.

# KEEP OUT OF REACH OF CHILDREN PROTECT FROM FREEZING

Refer to Safety Data Sheet for additional health and safety information.