

General Description

Use Woodlux® Wood Brightener and Neutralizer to remove tannin bleed that is common with cedar and redwood or to remove rust stains from wood and concrete. It will also neutralize and brighten wood surfaces after using Woodlux® Wood Restorer for gray & weathered wood (016) or Woodlux® Wood Stain Remover (015), in addition to breaking the “mill glaze” on new wood. Product does not control mold, mildew, fungus or algae, only removes stains.

- For restoring severely weathered wood
- Bleach-free formula is gentle to wood
- Concentrated formula

Usage

Residential or commercial applications. New or stripped, previously finished, exterior wood surfaces.

Technical Data

Max Mixing Ratio (Water : Neutralizer) 8 : 1

Coverage at Max Dilution 1,600 – 2,400 Sq. Ft
(8 Water : 1 Neutralizer)

Depending on substrate and application method

Surface Temperature Min: 50 °F

During Application Max: 90 °F

Clean Up Clean Water

Thinner Clean Water

Weight Per Gallon 8.7 lbs.

Storage Min: 40 °F

Temperature Max: 90 °F

Surface Preparation

Project surfaces may be damp or dry. Do not apply if surface temperature is below 50 °F (10 °C). Protect adjacent surfaces; cover with plastic and/or tape off any areas not being stripped. Pre-wet and/or cover vegetation; rinsing residue will not harm plants or roots. Exposure to concentrate may burn foliage.

PRIOR TO APPLICATION: Determine proper dilution. Test a small, inconspicuous area and allow to dry before general use. Before and after application, liberally spray surrounding plants and vegetation with water. Avoid contact with metal, lawn furniture and fabric. If necessary, protect adjacent surfaces with plastic.

Application

Mixing Recommendations:

This container makes up to 9 gallons of product. Mix ½ gallon of Woodlux® Wood Brightener and Neutralizer with 3 ½ gallons of water. For stubborn areas mix ½ gallon of Woodlux® Wood Brightener and Neutralizer with 2 ½ gallons of water. When using through a power washer chemical injector, place intake tube directly into container

DO NOT MIX CLEANER IN METAL CONTAINERS. NEVER MIX OR USE WITH OTHER CLEANERS OR CHEMICALS.

- 1) Apply product liberally to surface with plastic garden sprayer, brush or power washer chemical injector.
- 2) Allow solution to stand for 10 – 30 minutes.
- 3) Agitate with stiff bristle brush in direction of wood grain and rinse using a garden hose with nozzle or power washer.
- 4) Allow to dry thoroughly.

Note: When applying to vertical surfaces, apply from bottom to top.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Informational Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Limitations

- Do not apply when air and surface temperatures are below 50 °F (10 °C)

Compliance & Certifications

OTC	✓
OTC II	✓
CARB	✓
CARB07	✓
CARB19	✓
UTAH	✓
AZMC	✓
SCAQMD	✓

Clean Up

Clean equipment with warm, soapy water.

DISPOSAL: USE COMPLETELY OR DISPOSE OF PROPERLY. Local disposal requirements vary; consult your sanitation department or state-designated environmental agency for local disposal options.

Technical Assistance

Available through your local authorized independent Benjamin Moore retailer.

call 1-866-708-9180

visit www.benjaminmoore.com

Environmental Health & Safety Information

Contains: Oxalic acid

CAUSES BURNS OF EYE, SKIN AND MUCOUS MEMBRANES. HARMFUL BY INHALATION. HARMFUL OR FATAL IF SWALLOWED.

Use only with adequate ventilation. Do not breathe vapors or sanding dust. Avoid contact with eyes, skin and clothing. Wear chemical resistant goggles and face shield, chemical resistant gloves and protective clothing during application and cleanup. Do not wear contact lenses. Open doors, windows or use other means to ensure fresh air entry during application and cleanup. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor levels are above the applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Do not permit anyone without protection in the painting area. Wash thoroughly after handling. Close container after each use. Wet surfaces are extremely slippery.

FIRST AID: If affected by inhalation of vapors or sanding dust, remove to fresh air and get medical help immediately. In case of eye contact, flush immediately with copious amounts of water holding eyelids open for at least 15 minutes and get medical attention immediately. In cases of skin contact, remove contaminated clothing and flush affected area with water for at least 15 minutes, get medical help immediately. If swallowed, DO NOT INDUCE VOMITING, get medical help immediately.

IN CASE OF SPILL – Absorb with inert material and dispose of as specified under “Clean up”.



WARNING Cancer and Reproductive Harm– www.P65Warnings.ca.gov

Refer to the product label & Safety Data Sheet for product specific information.

**KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING**

Refer to Safety Data Sheet for additional health and safety information.