

General Description

Use Woodlux® All-In-One Wood Cleaner on exterior wood decking, siding, fencing, shakes and furniture to quickly remove dirt and stains from mould, mildew, algae and water. Also recommended for use on vinyl, stucco, concrete, pavers and brick.

- Ideal for maintenance cleaning
- Removes stains from mould and mildew
- Concentrated formula

Usage

Residential or commercial applications on wood decking, siding, shingles and furniture. Also recommended for concrete, stucco, vinyl, fiberglass and outdoor furniture.

Technical Data

Max Mixing Ratio (Water : Cleaner) 7 : 1

Coverage at Max Dilution 148.6 – 222 sq. m.
(7 x 3.78 L Water, 3.78 Cleaner) (1,600 – 2,400 sq. ft.)

Depending on substrate and application method

Surface Temperature During Application	Min:	10 °C (50 °F)
	Max:	32.2 °C (90 °F)
Clean Up Thinner		Clean Water
Weight Per Gallon		4.5 kg (9.9 lbs.)
Storage Temperature	Min:	4.4 °C (40 °F)
	Max:	32.2 °C 90 °F

Surface Preparation

Project surfaces may be damp or dry. Do not apply if surface temperature is below 10 °C (50 °F). Protect adjacent surfaces; cover with plastic and/or tape off any areas not being stripped. Pre-wet and/or cover vegetation; rinsing residue will not harm plants or roots. Exposure to concentrate may burn foliage.

PRIOR TO APPLICATION: Determine proper dilution. Test a small, inconspicuous area and allow to dry before general use. Before and after application, liberally spray surrounding plants and vegetation with water. Avoid contact with metal, lawn furniture and fabric. If necessary, protect adjacent surfaces with plastic.

Application

Mixing Recommendations:

This container makes up to 8 cans of 3.78 L product. Mix ½ can of 3.78 L Woodlux® All-In-One Wood Cleaner with 3 ½ cans of 3.78 L water. For stubborn areas mix ½ can of 3.78 L of Woodlux® All-In-One Wood Cleaner with 2 ½ cans of 3.78 L water. When using through a power washer chemical injector, place intake tube directly into container.

DO NOT MIX CLEANER IN METAL CONTAINERS. NEVER MIX OR USE WITH OTHER CLEANERS OR CHEMICALS.

- 1) Apply product liberally to surface with plastic garden sprayer, brush or power washer chemical injector.
- 2) Allow solution to stand for 10 – 30 minutes, depending upon age and type of finish to be removed.
- 3) Agitate with stiff bristle brush in direction of wood grain and rinse using a garden hose with nozzle or power washer.
- 4) Allow to dry thoroughly.

Note: When applying to vertical surfaces, apply from bottom to top.

Limitations

- Do not apply when air and surface temperatures are below 10 °C (50 °F)

Clean Up

Clean equipment with warm, soapy water.

Technical Assistance

Available through your local authorized independent Benjamin Moore retailer.

call 1-866-708-9180
visit www.benjaminmoore.ca

Environmental Health & Safety Information

DANGER
CORROSIVE

CAUSES BURNS

Do not swallow.
Do not get in eyes.
Do not get on skin or clothing.
Do not breathe fumes.

Handle with care.
Keep out of reach of children.
Wear rubber gloves and safety glasses.
Use only in a well-ventilated area.
Wear a mask or respirator.

FIRST AID TREATMENT

Contains sodium hypochlorite and sodium metasilicate. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes. If on skin, rinse well with water. If on clothes, remove clothes. If breathed in, move person to fresh air.

KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING

Refer to Safety Data Sheet for additional health and safety information.