



CONCRETE WATER-PROOFING SEALER 075

Features

- Formulated to provide long lasting weather resistance to exterior concrete floor and wall surfaces.
- Fast dry and easy application.
- The clear finish penetrates bare concrete, leaving minimum surface film while protecting masonry surfaces from powdering and staining.

General Description

A blend of durable silicone and acrylic resins designed to penetrate bare concrete floor and wall surfaces.

Recommended For

For new or unpainted exterior surfaces such as patios, walks, driveways, carports, loading docks, tennis courts: poured or precast concrete, cement block and stucco walls. Also for garage, factory and warehouse floors.

Limitations

CAUTION: All sealed walking surfaces may become slippery when wet. Where non-skid characteristics are desired, a small amount of P67 Anti-Slip Aggregate may be added.

- Not recommended for use over previously painted surfaces.
- Do not apply to wood or metal surfaces.
- Not for application over asphalt or macadam.
- Do not apply when air and surface temperatures are below 50°F.

Product Information

<p>Colors — Standard: Clear</p>	<p>Technical Data [◇] Clear</p>																		
<p>— Special Colors: Contact your Benjamin Moore & Co. representative.</p>	<table border="1"> <tr> <td>Vehicle Type</td> <td>Silicone / Acrylic Blend</td> </tr> <tr> <td>Pigment Type</td> <td>N/A</td> </tr> <tr> <td>Volume Solids</td> <td>24.5%</td> </tr> </table>	Vehicle Type	Silicone / Acrylic Blend	Pigment Type	N/A	Volume Solids	24.5%												
Vehicle Type	Silicone / Acrylic Blend																		
Pigment Type	N/A																		
Volume Solids	24.5%																		
<p>— Tint Bases: Not available</p>	<table border="1"> <tr> <td>Coverage per Gallon at Recommended Film Thickness</td> <td>300 Sq. Ft.</td> </tr> <tr> <td>Recommended Film Thickness</td> <td>– Wet 4.3 mils – Dry 1.3 mils</td> </tr> </table>	Coverage per Gallon at Recommended Film Thickness	300 Sq. Ft.	Recommended Film Thickness	– Wet 4.3 mils – Dry 1.3 mils														
Coverage per Gallon at Recommended Film Thickness	300 Sq. Ft.																		
Recommended Film Thickness	– Wet 4.3 mils – Dry 1.3 mils																		
<p>Certification: VOC compliant in federally regulated areas only</p>	<p>Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint.</p> <table border="1"> <tr> <td>Dry Time @ 77° F (25° C) @ 50% RH</td> <td>– To Touch ½ Hour – To Recoat Overnight †</td> </tr> </table>	Dry Time @ 77° F (25° C) @ 50% RH	– To Touch ½ Hour – To Recoat Overnight †																
Dry Time @ 77° F (25° C) @ 50% RH	– To Touch ½ Hour – To Recoat Overnight †																		
<p>Technical Assistance Available through your local authorized independent Benjamin Moore & Co. retailer. For the location of the retailer nearest you, call 1-800-826-2623, see www.benjaminmoore.com, or consult your local Yellow Pages.</p>	<p>High humidity and cool temperatures will result in longer dry, recoat and service times. † To hard dry allow 3 days.</p> <table border="1"> <tr> <td>Dries By</td> <td>Evaporation</td> </tr> <tr> <td>Viscosity</td> <td>< 50 KU</td> </tr> <tr> <td>Flash Point</td> <td>Combustible</td> </tr> <tr> <td>Gloss / Sheen</td> <td>Low Lustre</td> </tr> <tr> <td>Surface Temperature at Application</td> <td>– Min. 50° F – Max 90° F</td> </tr> <tr> <td>Thin With</td> <td>Do Not Thin</td> </tr> <tr> <td>Clean Up Thinner</td> <td>Mineral Spirits</td> </tr> <tr> <td>Weight Per Gallon</td> <td>7.2 lbs</td> </tr> <tr> <td>Storage Temperature</td> <td>– Min. 40° F – Max 90° F</td> </tr> </table> <p>Volatile Organic Compounds (VOC)</p> <p>599 Grams/Liter 5.0 lbs./Gallon</p>	Dries By	Evaporation	Viscosity	< 50 KU	Flash Point	Combustible	Gloss / Sheen	Low Lustre	Surface Temperature at Application	– Min. 50° F – Max 90° F	Thin With	Do Not Thin	Clean Up Thinner	Mineral Spirits	Weight Per Gallon	7.2 lbs	Storage Temperature	– Min. 40° F – Max 90° F
Dries By	Evaporation																		
Viscosity	< 50 KU																		
Flash Point	Combustible																		
Gloss / Sheen	Low Lustre																		
Surface Temperature at Application	– Min. 50° F – Max 90° F																		
Thin With	Do Not Thin																		
Clean Up Thinner	Mineral Spirits																		
Weight Per Gallon	7.2 lbs																		
Storage Temperature	– Min. 40° F – Max 90° F																		

◇ Reported values are for White. Contact Benjamin Moore & Co. for values of other bases or colors.

Concrete Waterproofing Sealer 075

Surface Preparation

Surfaces must be thoroughly dry, free of dirt, sealer, waxes, paint grease or oily substances. Smooth troweled surfaces or nonporous concrete must be etched before applying the Concrete Waterproofing Sealer. Use a 1% muriatic acid solution, rinse thoroughly with water and allow to dry completely, at least 24 hours before sealing (Follow manufacturer's label directions).

CAUTION: Wear work goggles, rubber gloves and boots and protective clothing when using muriatic acid. Allow new concrete to cure 30 days before etching or sealing. Form release agents used with poured or pre-cast concrete walls must be removed with appropriate solvent, and laitance deposits thoroughly removed by hand or power wire brushing.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead

Application

Stir thoroughly before using. Apply one coat with brush, roller or airless spray. Do not apply when air or surface temperatures are below 50°F (10°C). Apply as received in the container.

Thinning / Clean-Up

Do not thin.

Do not apply over asphalt or macadam surfaces as "bleeding" will occur.

Clean tools and equipment with Mineral Spirits.

USE COMPLETELY OR DISPOSE OF PROPERLY. Dry empty containers may be recycled in a can recycling program. Local disposal requirements vary; consult your sanitation department or state-designated environmental agency on disposal options.

Environmental, Health & Safety Information

Contains: Stoddard Solvent

VAPOR HARMFUL. CAUSES SKIN, NOSE AND THROAT IRRITATION NOTICE: Repeated and prolonged exposure to solvents may lead to permanent brain and nervous system damage. Eye watering, headaches, nausea, dizziness and loss of coordination are signs that solvent levels are too high. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Keep away from heat and flame. Use only with adequate ventilation. Do not breathe vapors, spray mist or sanding dust. Avoid contact with eyes and prolonged or repeated contact with skin. Wear eye protection and gloves. To avoid breathing vapors or spray mist, open window and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear properly fitted vapor/particulate respiratory approved by NIOSH for use with paints or leave the area. In all cases follow respiratory manufacturer's directions for respiratory use. Close container after each use.

WARNING: This product contains a chemical known to the state of California to cause cancer and birth defects, or other reproductive harm.

FIRST AID: If affected by inhalation of vapors or spray mist, remove to fresh air. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and call a physician; for skin, wash thoroughly with soap and water. In case of ingestion - DO NOT INDUCE VOMITING, get medical help immediately.

IN CASE OF FIRE - Use foam, CO₂, dry chemical or water fog.
SPILL - Absorb with inert material and dispose of as specified under "CLEAN UP"

KEEP OUT OF REACH OF CHILDREN

Refer to Material Safety Data Sheet for additional health and safety information.