

## General Description

A premium, 100% acrylic exterior flat finish formulated with CleanGuard™ Technology to keep surfaces looking freshly painted longer. It can be applied as a high build, to bridge small cracks and smooth minor surface imperfections. Designed with exceptional adhesion for hard-to-coat, chalky surfaces and self-priming on most surfaces.

- CleanGuard™ Technology to keep surfaces looking freshly painted longer.
- Bridges small cracks and covers minor surface imperfections.
- Excellent flow & leveling.
- Strong adhesion, even on hard-to-coat, chalky substrates.
- Limited Lifetime Warranty.

## Usage

Exterior surfaces such as wood, fiber cement board, hard board, vinyl and aluminum siding, shakes, unglazed brick, concrete, stucco, cinder block and primed metal.

<b>Colors</b>	White (01)
<b>Bases</b>	1X, 2X, 3X, 4X
<b>Colorant System</b>	Gennex®

## Technical Data

<b>Vehicle</b>	Proprietary 100% Acrylic	
<b>Pigment</b>	Titanium Dioxide	
<b>Volume Solids</b>	43 ± 2%	
<b>Spread Rate Per Gallon</b>	300 – 400 Sq. Ft.	
<b>Recommended</b>	Wet:	5.3 – 6.0 mils
<b>Film Thickness</b>	Dry:	1.7 – 2.3 mils
<b>High Build System Coverage:</b>		
80 – 150 Sq. Ft. / 10 – 20 mils wet film thickness. Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job to ensure color uniformity and minimize the disposal of excess paint.		
<b>Dry Time @ 77 °F</b>	To Touch:	1 hour
<b>(25 °C) @ 50% RH</b>	To Recoat:	4 hours
Allow an overnight dry when recoating a high build system application.		
High humidity and cool temperatures will result in longer dry, recoat and service times.		
<b>Surface Temperature</b>	Min:	35 °F
<b>During Application</b>	Max:	100 °F
<b>Viscosity</b>	100 ± 4 KU	
<b>Flash Point</b>	None	
<b>Sheen / Gloss</b>	0 – 3 @ 85°	
<b>Clean Up</b>	Water	
<b>Thinner</b>	refer to page 2	
<b>Weight Per Gallon</b>	10.5 lbs.	
<b>Storage Temperature</b>	Min:	40 °F
	Max:	90 °F
<b>VOC</b>	< 50 g/L	

## Primer Systems

Regal Select Exterior is self-priming on most properly prepared substrates, including wood, fiber cement board, hardboard, nonferrous metals and cured masonry surfaces. On bare substrates two coats are required; previously painted surfaces can be finished with 1 or 2 coats. **Special Note:** Certain custom colors require a Deep Color Base Primer tinted to a special prescription formula to achieve the desired color. Consult your retailer.

**Wood, and engineered wood products:**  
Self-priming

**Bleeding Woods (Redwood, Cedar, etc.):**  
Fresh Start® Exterior Deck & Siding Primer (094) or Fresh Start® High-Hiding All Purpose Primer (046)

**Hardboard Siding, Bare or Factory Primed:**  
Self-priming

**Vinyl Siding & Vinyl Composite:**  
In most cases, a primer is not necessary. Only areas of pitted and porous vinyl siding must be primed. In these cases, we recommend Fresh Start® High-Hiding All Purpose Primer (046).

**Colors that are safe for use on vinyl siding** - Do not paint vinyl with any color darker than the original color or has a Light Reflective Value (LRV) of less than 57 unless it is in the Benjamin Moore approved Colors for Vinyl palette and complies with the specific vinyl manufacturer guidelines when making the color selection and painting. Otherwise, the color will absorb more heat, possibly causing the siding to warp, resulting in additional repairs and expenses.

**Rough or Pitted Masonry:**  
Ultra Spec® Masonry Interior/Exterior Hi-Build Block Filler (571) or equivalent

**Poured or Pre-cast Concrete/Fiber Cement Siding:**  
Self-priming on cured concrete/cement. For new concrete/cement, prime with Ultra Spec® Masonry Interior / Exterior 100% Acrylic Masonry Sealer (608) or Masonry High Build Primer (N609).

**Ferrous Metal (Steel and Iron):**  
High Performance Acrylic Metal Primer (HP1100) or High Performance Alkyd Metal Primer (HP1320)

**Non-Ferrous Metal (Galvanized & Aluminum):**  
All new metal surfaces must be thoroughly cleaned with Oil & Grease Emulsifier (HP6000) to remove contaminants. New shiny non-ferrous metal surfaces that will be subject to abrasion should be dulled with very fine sandpaper or a synthetic steel wool pad to promote adhesion.

Self-Priming. For additional rust protection, prime with Acrylic Metal Primer HP1100.

## Limitations

- Do not apply when air or surface temperatures are below 35 °F (1.7 °C).
- For Wind-Driven Rain over smooth and stable masonry only (non-elastomeric use). Follow primer instructions.
- Not recommended for walking surfaces.

## Compliance & Certifications

<b>OTC</b>	✓
<b>OTC II</b>	✓
<b>CARB</b>	✓
<b>CARB07</b>	✓
<b>CARB19</b>	✓
<b>UTAH</b>	✓
<b>AZMC</b>	✓
<b>SCAQMD</b>	✓
<b>ASTM D6904</b>	
<b>Wind Driven Rain</b>	Pass: (< 0.2)
1 coat Masonry Sealer 608 or Masonry Primer N609; 1 coat 261	
<b>ASTM D1653</b>	
<b>Water Vapor Permeance</b>	37.96 perms
<b>ASTM D3273/D3274</b>	
<b>Mildew Resistance Test</b>	Pass: No Growth
<b>ASTM D522/522M</b>	
<b>Flexibility</b>	Pass: No Cracking
<b>ASTM D2370 Elongation &amp; Tensile Strength</b>	
	21 % 555 PSI
<b>MPI</b>	Pending

**LIMITED LIFETIME WARRANTY:** Benjamin Moore & Co. warrants that this product when used in accordance with the label instructions, will not: 1. blister from properly prepared and primed surfaces, 2. peel from properly prepared and primed surfaces, and 3. wear down or weather to expose the previously painted surface. This warranty shall be effective for so long as you reside in your home and is made to the original residential consumer paint purchaser. This warranty is non-transferable. If this product fails to perform as explained above when used according to label instructions within the warranty period, Benjamin Moore & Co. will, upon presentation of proof of purchase (original sales receipt), provide an equivalent or comparable product at no charge. Since we have no control over surface preparation or application, THIS LIMITED LIFETIME WARRANTY DOES NOT INCLUDE THE COST OF LABOR FOR APPLICATION OF PAINT. BENJAMIN MOORE SHALL IN NO EVENT BE LIABLE FOR INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. SOME STATES DO NOT ALLOW THE EXCLUSION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE LIMITATIONS OR EXCLUSIONS CONTAINED IN THE ABOVE WARRANTY MAY NOT APPLY TO YOU. This warranty gives you specific legal rights; you may also have other rights which vary state to state.

## Technical Assistance

Available through your local authorized independent Benjamin Moore retailer.

call 1-866-708-9180  
visit [www.benjaminmoore.com](http://www.benjaminmoore.com)

## Surface Preparation

Surfaces must be clean, dry and free of oil, grease, wax, rust, mildew, chalk and loose or scaling paint. Cement based water proofing paints should be removed. Glossy surfaces must be dulled. Un-weathered areas such as eaves, porch ceilings, overhangs and protected wall areas should be washed with an appropriate cleaner and rinsed with a strong stream of water from a garden hose or power washer to remove contaminants that can interfere with proper adhesion.

All new masonry surfaces must be power washed or brushed thoroughly with stiff fiber bristles to remove loose particles. New masonry substrates must be allowed to cure for 30 days before priming or painting. Poured or pre-cast concrete with a very smooth surface should be etched or abraded to promote adhesion, after removing all form release agents and curing compounds.

Difficult Substrates: Benjamin Moore offers a number of specialty primers for use over difficult substrates such as bleeding woods, grease stains, crayon markings, hard glossy surfaces, or other substrates where paint adhesion or stain suppression is a particular problem. Your Benjamin Moore® retailer can recommend the right problem-solving primer for your special needs.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Informational Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

## Application

Stir thoroughly before and during use. Apply one or two coats. For best results, use a premium Benjamin Moore® custom-blended nylon/polyester brush, premium Benjamin Moore® roller, or a similar product. Apply paint generously from unpainted area into wet area.

### Spray, Airless:

Pressure / 1,500 – 2,500 PSI

Tip / 0.015 – 0.017

Under normal application conditions Regal® Select Exterior may be sprayed to achieve a high build one coat system over properly prepared substrates that are in good condition. Refer to Surface Preparation / Priming Sections for appropriate priming and preparation information.

### High Build System Coverage:

80 – 150 sq. ft.

10 – 20 mils (wet film thickness)

## Thinning/Cleaning

Conditioning with Benjamin Moore® 518 Extender may be necessary under certain conditions to adjust open time or spray characteristics.

Add 518 Extender or water - Max of 8 fl. oz. to a gallon paint

Never add other paints or solvents.

**Clean Up:** Wash brushes, rollers, and other painting tools in warm soapy water immediately after use. Spray equipment should be given a final rinse with mineral spirits to prevent rusting.

**USE COMPLETELY OR DISPOSE OF PROPERLY.** Dry, empty containers may be recycled in a can recycling program. Local disposal requirements vary; consult your sanitation department or state-designated environmental agency on disposal options.

## Environmental Health & Safety Information

**Use only with adequate ventilation.** Do not breathe spray mist or sanding dust. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to dust and spray mist by wearing a NIOSH approved respirator during application, sanding and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling.



**WARNING** Cancer and Reproductive Harm— [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)  
Refer to the product label & Safety Data Sheet for product specific information.

**FIRST AID:** In case of eye contact, flush immediately with plenty of water for at least 15 minutes; for skin, wash thoroughly with soap and water. If symptoms persist, seek medical attention. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

**IN CASE OF SPILL** – Absorb with inert material and dispose of as specified under “Clean up”.

**KEEP OUT OF REACH OF CHILDREN  
PROTECT FROM FREEZING**

**Refer to Safety Data Sheet for additional  
health and safety information.**