



SUPER SPEC[®]

ALKYD CALCIMINE RECOATER

K306

Features

- Features a uniform, glare-free finish
- Provides a highly serviceable film
- Superior leveling and hiding qualities
- Superb problem-solver coating that excels over difficult recoat surfaces
- Self-priming over calcimine coatings

Recommended For

For commercial and residential applications. Specifically formulated for recoating surfaces previously painted with calcimine material

General Description

A premium quality, high hiding, alkyd flat paint specifically designed for recoating surfaces previously painted with calcimine material. Covers most wall, ceiling, and trim surfaces in one coat.

Limitations

- Do not apply when air and surface temperatures are below 10 °C (50 °F)

Product Information

Product Information		Technical Data [◇]	Pastel Base
Colours — Standard: White (01) (White may be tinted with up to 2.0 fl. oz. of Benjamin Moore [®] Colour Preview [®] colorants per 3.79 L)		Vehicle Type	Alkyd
— Tint Bases: Benjamin Moore [®] Colour Preview [®] Pastel Base 1B		Pigment Type	Titanium Dioxide
— Special Colours: Contact your Benjamin Moore representative		Volume Solids	48%
Certifications & Qualifications: Master Painters Institute MPI # 49		Coverage per 3.79 L at Recommended Film Thickness	37.2 – 41.8 sq. m. (400 – 450 sq. ft.)
Customer Service Information Centre: 1-800-361-5898, info@benjaminmoore.ca , www.benjaminmoore.ca		Recommended Film Thickness	– Wet 3.8 mils – Dry 1.8 mils
		Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint.	
		Dry Time @ 25 °C (77 °F) @ 50% RH	– To Touch 4 - 6 Hours – To Recoat 12 Hours
		Painted surfaces can be washed after two weeks. High humidity and cool temperatures will result in longer dry, recoat and service times.	
		Dries By	Oxidation
		Viscosity	103 ± 3 KU
		Flash Point	Combustible
		Gloss / Sheen	Flat
		Surface Temperature at Application	– Min. 10 °C (50 °F) – Max 32.2 ° (90 °F)
		Thin With	Do Not Thin
		Clean Up Thinner	Mineral Spirits
		Weight Per 3.79 L	6.03 kg (13.3 lbs)
		Storage Temperature	– Min. 4.4 °C (40 °F) – Max 32.2 °C (90 °F)
		Volatile Organic Compounds (VOC)	
		440.7 g/L	

[◇]Reported values are for Pastel Base. Contact Benjamin Moore for values of other bases or colours.

Surface Preparation

Surfaces to be painted must be clean, dry, and free of dirt, dust, grease, oil, soap, wax, scaling paint, water soluble materials, and mildew. Remove any peeling or scaling paint and sand these areas to feather edges smooth with adjacent surfaces. Glossy areas should be dulled. Drywall surfaces must be free of sanding dust.

New plaster or masonry surfaces must be allowed to cure (30 – 60 days) before applying base coat. Cured plaster should be hard, have a slight sheen and maximum pH of 10; soft, porous or powdery plaster indicates improper cure. Never sand a plaster surface; knife off any protrusions and prime plaster before and after applying patching compound. Poured or pre-cast concrete with a very smooth surface should be etched or abraded to promote adhesion, after removing all form release agents and curing compounds. Remove any powder or loose particles before priming.

Difficult Substrates: Benjamin Moore & Co. offers a number of specialty primers for use over difficult substrates such as bleeding woods, grease, crayon markings, hard glossy surfaces, galvanized metal, or other substrates where paint adhesion or stain suppression is a particular problem. Your Benjamin® retailer can recommend the right problem-solving primer for your special needs.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @ <https://www.canada.ca/en/health-canada/services/environmental-workplace-health/environmental-contaminants/lead/lead-information-package-some-commonly-asked-questions-about-lead-human-health.html>

Primer/Finish Systems

Note: All alkyd-based enamels experience a certain amount of yellowing. This effect is accelerated in dark or poorly ventilated areas.

This product is sold only for the repainting of surfaces previously painted with calcimine material. For new surfaces or surfaces previously painted with non-calcimine coatings, a variety of Benjamin Moore® interior products are available. Consult your Benjamin Moore® retailer for recommendations.

Mixing of Paint: Stir thoroughly before and occasionally during use. Apply with a quality china bristle brush, or all purpose synthetic brush, short nap roller, or airless spray.

Do not apply when air and surface temperatures are below 10 °C (50 °F). **Spray, Airless:** Fluid Pressure — 1,500 to 2,000 PSI; Tip: .013 - .017 Orifice

Thinning/Cleaning

Do not thin. Clean up with mineral spirits

DANGER OF COMBUSTION

Keep away from flames or sparks.

Materials such as rags used with this product may begin to burn by themselves. After use, put rags in water or lay flat to dry, then discard.

USE COMPLETELY OR DISPOSE OF PROPERLY. This product contains organic solvents, which may cause adverse effects to the environment if handled improperly. Save unused product for touch-up purposes or a household hazardous waste collection program. Dry, empty containers may be recycled in a can recycling program. **Local disposal requirements vary; consult your sanitation department or provincial environmental agency on disposal options.**

Environmental, Health & Safety Information

Use only in a well ventilated area. Keep container closed when not in use. In case of spillage, absorb with inert material and dispose of in accordance with local regulations. Wash thoroughly after handling.

KEEP OUT OF REACH OF CHILDREN

Refer to Safety Data Sheet for additional health and safety information.