



REMOVE

FINISH REMOVER K315

Features

- Removes both latex and oil finishes
- Fast-acting formula
- Removes clear finishes through solid color stains
- Concentrated formula

General Description

This product is designed for the removal of peeling oil or latex stain, varnish, and clear-coat wood finishes. It will also remove damaged and discolored wood fiber from all exterior wood surfaces: decking, siding, shingles and furniture. Restores wood to its natural tone and prepares the surface for recoating.

Recommended For

Residential or commercial applications. Previously finished, exterior wood surfaces.

Limitations

- Do not apply when air and surface temperatures are below 10 °C (50 °F)
- Remove, Finish Remover may darken certain wood types during application. If desired, use Brighten, Brightener & Neutralizer (K317) to restore wood color back to its natural appearance.

Product Information																					
Colors — Standard: Not applicable	Technical Data N/A																				
— Tint Bases: Not applicable	Max Mixing Ratio (4:1) Mix 3.78 litres of REMOVE with 15.1 litres of water																				
— Special Colors: Not applicable	Coverage Maximum diluted solution (max. 4 gallons) covers approx. 46.5 – 92.9 sq. meters (500 – 100 sq. ft.) Depending on substrate and application method																				
Certifications & Qualifications: VOC compliant in all regulated areas	Flash Point None																				
Customer Information Centre: 1-800-361-5898, info@benjaminmoore.ca , www.benjaminmoore.ca	<table border="0" style="width: 100%;"> <tr> <td style="width: 60%;">Surface Temperature at Application</td> <td style="width: 10%; text-align: center;">– Min.</td> <td style="width: 30%; text-align: right;">10 °C (50 °F)</td> </tr> <tr> <td></td> <td style="text-align: center;">– Max</td> <td style="text-align: right;">32.2 °C (90 °F)</td> </tr> <tr> <td>Thin With</td> <td></td> <td style="text-align: right;">Clean Water</td> </tr> <tr> <td>Clean Up Thinner</td> <td></td> <td style="text-align: right;">Clean Water</td> </tr> <tr> <td>Weight Per Gallon</td> <td></td> <td style="text-align: right;">4.1kg (9.1 lbs)</td> </tr> <tr> <td rowspan="2">Storage Temperature</td> <td style="text-align: center;">– Min.</td> <td style="text-align: right;">4.4 °C (40 °F)</td> </tr> <tr> <td style="text-align: center;">– Max</td> <td style="text-align: right;">32.2 °C (90 °F)</td> </tr> </table>	Surface Temperature at Application	– Min.	10 °C (50 °F)		– Max	32.2 °C (90 °F)	Thin With		Clean Water	Clean Up Thinner		Clean Water	Weight Per Gallon		4.1kg (9.1 lbs)	Storage Temperature	– Min.	4.4 °C (40 °F)	– Max	32.2 °C (90 °F)
Surface Temperature at Application	– Min.	10 °C (50 °F)																			
	– Max	32.2 °C (90 °F)																			
Thin With		Clean Water																			
Clean Up Thinner		Clean Water																			
Weight Per Gallon		4.1kg (9.1 lbs)																			
Storage Temperature	– Min.	4.4 °C (40 °F)																			
	– Max	32.2 °C (90 °F)																			
	Volatile Organic Compounds (VOC) 109 g/L																				

Remove, Finish Remover 315

Surface Preparation

Project surfaces may be damp or dry. Do not apply if surface temperature is below 10 °C (50 °F). Protect adjacent surfaces; cover with plastic and/or tape off any areas not being stripped. Pre-wet and/or cover vegetation; rinsing residue will not harm plants or roots. Exposure to concentrate may burn foliage.

It is recommended that you test product performance in an inconspicuous area prior to use.

PRIOR TO APPLICATION: Determine proper dilution following the chart below. Test a small, inconspicuous area and allow to dry before general use. Before and after application, liberally spray surrounding plants and vegetation with water. Avoid contact with metal, lawn furniture and fabric. If necessary, protect adjacent surfaces with plastic.

Product does not control mold, mildew, fungus or algae, only removes stains.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @ <https://www.canada.ca/en/health-canada/services/environmental-workplace-health/environmental-contaminants/lead/lead-information-package-some-commonly-asked-questions-about-lead-human-health.html>

Application

MIXING: Remove, Finish Remover is a concentrate. This container makes up to 5 gallons of product.

Multiple Coats / Solid Color or Semi Solid Stain	Do not dilute
Weathered / Solid Color or Semi Solid Stain	Mix 3.78 litres of REMOVE with 3.78 litres of water
Semi Transparent Stain	Mix 3.78 litres of REMOVE with 7.5 litres gallon of water
Transparent Stain	Mix 3.78 litres of REMOVE with 11.3 litres of water
Clear Finish	Mix 3.78 litres of REMOVE with 15.1 litres of water

DO NOT MIX CLEANER IN METAL CONTAINERS. NEVER MIX OR USE WITH OTHER CLEANERS OR CHEMICALS.

1. Apply product liberally to surface with plastic garden sprayer, brush or roller.
2. Allow solution to stand for 10-30 minutes, depending on age and type of finish to be removed.
3. Agitate with stiff bristle brush in direction of wood grain and rinse using a garden hose with nozzle or power washer.
4. Neutralize surface with Brighten, Brightener & Neutralizer (K317) following label directions.
5. Allow to dry thoroughly. **Note:** When applying to vertical surfaces, apply from bottom to top.

CAUTION: Project surfaces will be extremely slippery.

Mixing

Mix according to the instructions above.

CLEAN UP: Clean equipment with warm, soapy water.

Environmental Health & Safety Information

DANGER

CORROSIVE

CAUSES BURNS

Do not swallow.

Do not get in eyes.

Do not get on skin or clothing.

Do not breathe fumes.

Handle with care.

Keep out of reach of children.

Wear rubber gloves and safety glasses.

Use only in a well-ventilated area.

Wear a mask or respirator.

FIRST AID TREATMENT

Contains sodium hydroxide and 2-butoxyethanol.

If swallowed, call a Poison Control Centre or doctor immediately.

Do not induce vomiting.

If in eyes, rinse with water for 15 minutes.

If on skin, rinse well with water. If on clothes, remove clothes.

If breathed in, move person to fresh air.

KEEP OUT OF REACH OF CHILDREN PROTECT FROM FREEZING

**Refer to Safety Data Sheet for additional
health and safety information.**