



RESTORE

WOOD RESTORER

K316

Features

- Bleach-free formula is gentle to wood
- Not intended for removing old finishes — use REMOVE, Finish Remover (K315) to remove old finishes
- For restoring severely weathered wood.
- Ideal for removing moderate to severe stains from mould and mildew
- Concentrated formula

General Description

This product is designed to restore severely weathered wood to its natural colour and prepare wood surfaces for recoating. It will quickly restore heavily greyed and weathered wood surfaces. It will quickly remove tannin bleeding, water stains, stains from mould and mildew, and discoloured surface fibre from all exterior wood surfaces, including decking, siding, shakes and furniture.

Recommended For

Residential or commercial applications. New or stripped, previously finished, exterior wood surfaces.

Limitations

- Do not apply when air and surface temperatures are below 10 °C (50 °F).

Product Information	
Colours — Standard: Not applicable	Technical Data N/A
— Tint Bases: Not applicable	Max. Mixing Ratio (8:1): Mix 3.785 litres of RESTORE with 30.28 litres of water
— Special Colours: Not applicable	Coverage Maximum diluted solution (max. 30.28 litres) covers approx. 148.64 - 222.96 sq. metres (1600 to 2400 sq. ft.) Depending on dilution and surface conditions
Certifications & Qualifications: VOC compliant in all regulated areas	Surface Temperature at application – Min. 10 °C (50 °F) – Max. 32.2 °C (90 °F)
CUSTOMER SERVICE INFORMATION CENTRE: 1-800-361-5898, info@benjaminmoore.ca , www.benjaminmoore.ca	Flash Point None
	Thin With Clean Water
	Clean Up Thinner Clean Water
	Weight Per 3.79 L 4 kg (9 lbs)
	Storage Temperature – Min. 4.4 °C (40 °F) – Max. 32.2 °C (90 °F)

◇ Reported values are for RESTORE.

Surface Preparation

Project surfaces may be damp or dry. Do not apply if surface temperature is below 10 °C (50 °F). Protect adjacent surfaces; cover with plastic and/or tape off. Pre-wet and/or cover vegetation; rinsing residue will not harm plants or roots. Exposure to concentrate may burn foliage.

It is recommended that you test product performance in an inconspicuous area prior to use.

PRIOR TO APPLICATION: Determine proper dilution and test a small, inconspicuous area and allow drying before general use. Before and after application, liberally spray surrounding plants and vegetation with water. Avoid contact with metal, lawn furniture and fabric. If necessary, protect adjacent surfaces with plastic.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @ <https://www.canada.ca/en/health-canada/services/environmental-workplace-health/environmental-contaminants/lead/lead-information-package-some-commonly-asked-questions-about-lead-human-health.html>

Application

MIXING: RESTORE, Wood Restorer is a concentrate. A 3.785 litre container makes up to 30.28 Litres of product. Mix 2.0 Litres of RESTORE, Wood Restorer with 13.0 Litres of water. For stubborn areas mix 2.0 Litres of RESTORE, Wood Restorer with 10.0 Litres of water. When using through a power washer chemical injector, place intake tube directly into container.

DO NOT MIX CLEANER IN METAL CONTAINERS. NEVER MIX OR USE WITH OTHER CLEANERS OR CHEMICALS.

1. Apply diluted solution liberally to surface with plastic garden sprayer, brush or through power washer chemical injector.
2. Allow solution to stand for several minutes.
3. Agitate with stiff bristle brush in direction of wood grain and rinse using a garden hose with nozzle or power washer.
4. Neutralize surface with BRIGHTEN, Brightener & Neutralizer (K317) following label directions.
5. Allow surface to dry thoroughly. **Note:** When applying to vertical surfaces, apply from bottom to top.

IMPORTANT: Allow wood surface to dry thoroughly before applying a new finish coat.

CAUTION: Project surfaces will be extremely slippery.

Mixing

Mix according to the instructions above.

CLEAN UP: Clean equipment with warm, soapy water.

Environmental, Health & Safety Information

DANGER

CORROSIVE

CAUSES BURNS

Do not swallow.

Do not get in eyes.

Do not get on skin or clothing.

Do not breathe fumes.

Handle with care.

Keep out of reach of children.

Wear rubber gloves and safety glasses.

Use only in a well-ventilated area.

Wear a mask or respirator.

FIRST AID TREATMENT

Contains sodium hydroxide and 2-butoxyethanol.

If swallowed, call a Poison Control Centre or doctor immediately.

Do not induce vomiting.

If in eyes, rinse with water for 15 minutes.

If on skin, rinse well with water. If on clothes, remove clothes.

If breathed in, move person to fresh air.

KEEP OUT OF REACH OF CHILDREN PROTECT FROM FREEZING

Refer to Safety Data Sheet for
additional health and safety information.