



STAYS CLEAR[®] ACRYLIC POLYURETHANE FLAT F425

Features

- Does not yellow like solvent based varnishes & polyurethanes.
- Tintable to many decorative shades.
- Quick dry and re-coat.
- Soap and water clean up.

Recommended For

- For commercial and residential applications
- Applicable for new or previously painted, stained, or varnished interior wood surfaces.

General Description

A premium quality product that combines the attributes of acrylic and polyurethane resins to produce a clear flat finish that dries quickly with very little odour. For use on new or previously painted, stained or varnished interior wood surfaces. May also be used as a protective clear coating over decorative faux finishes on any substrate. For optimal finish clarity when applying more than one coat use Stays Clear[®] Gloss for the initial coats. Not for floors

Limitations

- Do not apply when air and surface temperatures are below 10 °C (50 °F)
- For use on wood substrates or as a protective topcoat for decorative Faux finishes only
- Not recommended for use on floors

Product Information

<p>Colours — Standard: Clear (00)</p> <p>(May be tinted with up to 2.0 fl. oz. Benjamin Moore[®] Colour Preview[®] or Gennex[®] colorants per 3.79 L.)</p>	<p>Technical Data[◇]</p>	<p>Flat</p>
<p>— Tint Bases: Not available</p>	<p>Vehicle Type</p>	<p>Acrylic Polyurethane</p>
<p>— Special Colours: Not available</p>	<p>Pigment Type</p>	<p>None</p>
<p>Certifications & Qualifications:</p> <p>Qualifies for LEED[®] v4 Credit Qualifies for CHPS low emitting credit (Collaborative for High Performance Schools) CDPH v1 Emission Certified Class A (0-25) over non-combustible surfaces when tested in accordance with ASTM E-84</p>	<p>Volume Solids</p>	<p>32.7%</p>
<p>CUSTOMER SERVICE INFORMATION CENTRE: 1-800-361-5898, info@benjaminmoore.ca, www.benjaminmoore.ca</p>	<p>Coverage per 3.79 L at Recommended Film Thickness</p>	<p>32.5 – 41.8 sq. m. (350 – 450 sq. ft.)</p>
	<p>Recommended Film Thickness</p>	<p>– Wet 4.0 mils – Dry 1.3 mils</p>
	<p>Dry Time @ 25 °C (77 °F) @ 50% RH</p>	<p>– To Touch 1 Hour – To Recoat 2-3 Hours</p>
	<p>Dries By</p>	<p>Evaporation, Coalescence</p>
	<p>Viscosity</p>	<p>77 ± 3 KU</p>
	<p>Flash Point</p>	<p>None</p>
	<p>Gloss / Sheen</p>	<p>Flat (max. 5 @ 60°)</p>
	<p>Surface Temperature at Application</p>	<p>– Min. 10 °C (50 °F) – Max 32 °C (90 °F)</p>
	<p>Thin With</p>	<p>Clean Water</p>
	<p>Clean Up Thinner</p>	<p>Clean Water</p>
	<p>Weight Per 3.79 L</p>	<p>3.9 kg (8.8 lbs)</p>
	<p>Storage Temperature</p>	<p>– Min. 4.4 °C (40 °F) – Max 32 °C (90 °F)</p>
	<p>Volatile Organic Compounds (VOC)</p>	
	<p>269 Grams/Liter</p>	<p>1.0 kg/3.79 L</p>

◇ Reported values are for Flat.

Stays Clear® Acrylic Polyurethane Flat F425

Surface Preparation

Surfaces to be finished must be free from wax, dirt, grease, dust, and other contaminants. Glossy surfaces must be dulled with sandpaper or synthetic steel wool. **Do not use steel wool loose fibres will cause rusting in the finish coat.**

Note: The application of this or any clear acrylic finish over fresh alkyd coatings may cause yellowing of the basecoat.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @ <https://www.canada.ca/en/health-canada/services/environmental-workplace-health/environmental-contaminants/lead/lead-information-package-some-commonly-asked-questions-about-lead-human-health.html>

Primer/Finish Systems

Raw Wood: New interior wood must be sanded smooth. Use fine sandpaper following the grain of the wood to achieve a smooth finish. Stays Clear® may be used as both the sealer and finish on raw wood. Allow sufficient dry time before sanding lightly and applying topcoats.

Sealer: 1 coat Stays Clear® Acrylic Polyurethane

Finish: 1-2 or more coats Stays Clear® Acrylic Polyurethane

Old Finishes: Do not apply over sealers containing silicones, wax, or stearate. Remove old finishes which are chipping, peeling, or in otherwise poor condition. Remove any and all old finishes containing wax or stearate. Other finishes in good condition must be sanded lightly with fine sandpaper until smooth. Surfaces requiring complete restoration must have the finish removed by either power sanding or use of paint and varnish remover, then treated as new surface.

Application

Stir thoroughly before and occasionally during use to ensure a uniform sheen.

Brush: Apply as received in the container with a good quality synthetic brush or painting pad. Apply along grain of the wood in thin, even, uniform coats. Keep a wet-edge during application and avoid working back into partially dry areas.

Roller: Large smooth surfaces can be coated using a short-nap roller in thin, even, uniform coats. Keep a wet-edge during application and avoid working back into partially dry areas.

Spray, Airless: Fluid Pressure —1,500 to 2,000 PSI;

Tip —.011 - .015 Orifice;

Allow a minimum of 2-3 hours dry; then sand lightly with the grain, before recoating. For optimal performance a minimum of two coats are required for furniture or trim.

Thinning/Cleanup

Do not thin; thinning will reduce the sealing ability of this product. Do not add other paints or solvents. Wash painting tools in warm soapy water immediately after use. Spray equipment should be given a final rinse with mineral spirits to prevent rusting.

USE COMPLETELY OR DISPOSE OF PROPERLY. Dry empty containers may be recycled in a can recycling program. Local disposal requirements vary; consult your sanitation department or state-designated environmental agency on disposal options.

Environmental, Health & Safety Information

Use only in a well ventilated area. Keep container closed when not in use. In case of spillage, absorb with inert material and dispose of in accordance with local regulations. Wash thoroughly after handling.

**KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING**

**Refer to Safety Data Sheet for additional
health and safety information.**