



# INTERIOR WOOD FINISHES ACRYLIC URETHANE HIGH GLOSS K430

## Features

- Does not yellow like solvent based varnishes & polyurethanes.
- Tintable to many decorative shades.
- Quick dry and re-coat.
- Soap and water clean up.

## General Description

A water-reducible, non-yellowing, clear varnish. It features rapid dry, good levelling, low odour, good abrasion resistance and easy clean-up with soap and water. It is available in a gloss and a satin finish; both appear milky when liquid but dry to a clear coating.

## Recommended For

A clear coating for interior wood surfaces except floors. It can be used on new or previously varnished wood and also as a protective coating over interior painted surfaces.

## Limitations

- Do not apply when air and surface temperatures are below 10 °C (50 °F)

## Product Information

### Colours — Standard:

Clear  
(May be tinted with up to 2.0 fl. oz. of Benjamin Moore® Colour Preview® colorants per 3.79 L)

### — Tint Bases:

Not available

### — Special Colours:

Contact your Benjamin Moore representative

### Certification:

VOC compliant in all regulated areas.

### Customer Service Information Centre:

1-800-361-5898, [info@benjaminmoore.ca](mailto:info@benjaminmoore.ca), [www.benjaminmoore.ca](http://www.benjaminmoore.ca)

### Technical Data<sup>◇</sup>

### Clear

Vehicle Type	Acrylic Urethane
Pigment Type	None
Volume Solids	20%
Coverage per 3.79 L at Recommended Film Thickness	27.9 – 46.4 sq. m. (300 – 500 sq. ft.)
Recommended Film Thickness	– Wet 4.0 mils – Dry .8 mils
Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure colour uniformity and minimize the disposal of excess paint.	
Dry Time @ 25 °C (77 °F) @ 50% RH	– To Touch ½ Hour – To Recoat 4 Hours
Painted surfaces can be washed after two weeks. High humidity and cool temperatures will result in longer dry, recoat and service times.	
Dries By	Evaporation, Coalescence
Viscosity	77 ± 2 KU
Flash Point	None
Gloss / Sheen	Gloss
Surface Temperature at Application	– Min. 10 °C (50 °F) – Max. 32.2 °C (90 °F)
Thin With	Clean Water
Clean Up Thinner	Clean Water
Weight Per 3.79 L	3.9 kg (8.58 lbs)
Storage Temperature	– Min. 4.4 °C (40 °F) – Max. 32.2 °C (90 °F)

### Volatile Organic Compounds (VOC)

345 g/L

<sup>◇</sup> Reported values are for Clear. Contact Benjamin Moore for values of other bases or colours.

## Interior Wood Finishes, Acrylic Urethane High Gloss K430

### Surface Preparation

Surfaces to be finished must be free from wax, dirt, grease, dust, and other contaminants. Glossy surfaces must be dulled with sandpaper or synthetic steel wool. **Do not use steel wool loose fibres will cause rusting in the finish coat.** Open grained woods such as oak or mahogany that will be subject to water or liquid spills should be filled with wood grain filler following manufacturer's directions. Apply Benjamin Moore® Interior Wood Finishes Penetrating Stain (F241) as needed.

**Note:** The application of this or any clear acrylic finish over fresh alkyd coatings may cause yellowing of the basecoat.

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @ [http://www.hc-sc.gc.ca/iyh-vsv/prod/paint-peinture\\_e.html](http://www.hc-sc.gc.ca/iyh-vsv/prod/paint-peinture_e.html)

### Primer/Finish Systems

**Raw Wood:** New interior wood must be sanded smooth. Use fine sandpaper following the grain of the wood to achieve a smooth finish. Benjamin Moore® Latex Urethane Acrylic Finish may be used as both the sealer and finish on raw wood. Allow sufficient dry time before sanding lightly and applying topcoats.

Sealer: 1 coat of Benjamin Moore® Latex Urethane Acrylic Finish.  
Finish: 1-2 or more coats Interior Wood Finishes, Acrylic Urethane High Gloss (K430)

**Old Finishes:** Do not apply over sealers containing silicones, wax, or stearate. Remove old finishes which are chipping, peeling, or in otherwise poor condition. Remove any and all old finishes containing wax or stearate. Other finishes in good condition must be sanded lightly with fine sandpaper until smooth. Surfaces requiring complete restoration must have the finish removed by either power sanding or use of paint and varnish remover, then treated as new surface.

### Application

Allow a minimum of 3 hours dry; then sand lightly, rubbing with the grain, before recoating. For optimal performance a minimum of two coats are required for furniture or trim.

**Brush:** Stir thoroughly and apply as received in the container with a good quality synthetic brush or painting pad. Apply along grain of the wood in thin, even, uniform coats. Keep a wet edge during application and avoid working back into partially dry areas.

**Roller:** Large smooth surfaces can be coated using a short-nap roller or pad applicator in thin, even, uniform coats. Keep a wet edge during application and avoid working back into partially dry areas.

**Spray, Airless:** Fluid Pressure —1,500 to 2,000 PSI;

Tip —.011 - .015 Orifice;

### Thinning/Cleanup

**Do not thin;** thinning will reduce the sealing ability of this product.

Do not add other paints or solvents. Wash painting tools in warm soapy water immediately after use. Spray equipment should be given a final rinse with mineral spirits to prevent rusting.

USE COMPLETELY OR DISPOSE OF PROPERLY. Dry, empty containers may be recycled in a can recycling program. **Local disposal requirements vary; consult your sanitation department or provincial environmental agency on disposal options.**

### Environmental, Health & Safety Information

**CAUTION! Contains glycol ethers. VAPOUR HARMFUL.**

Contains n-methyl pyrrolidone which CAN BE ABSORBED THROUGH THE SKIN. MAY CAUSE REPRODUCTIVE ORGAN DAMAGE.

This waterborne system contains less than 5% Glycol Ethers. Use adequate ventilation during application and drying. Do not breathe vapours or spray mist. Do not get in eyes or on skin. Wear eye protection and solvent impermeable gloves during application or sanding. Close container after each use. Wash thoroughly after handling. A dust/particulate respirator approved by NIOSH should be worn when sanding or spraying.

**FIRST AID:** If affected by inhalation of vapours or spray mist, remove to fresh air. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and call physician; for skin, wash thoroughly with soap and water. If swallowed, do not induce vomiting. Get medical attention immediately.

**IN CASE OF: FIRE** — Use foam, CO<sub>2</sub>, dry chemical, or water fog.  
**SPILL** — Absorb with inert material and dispose of as specified under "Thinning/Clean Up".

**KEEP OUT OF REACH OF CHILDREN  
PROTECT FROM FREEZING**

**Refer to Material Safety Data Sheet for  
additional health and safety information.**