



ben[®]
 100% ACRYLIC EXTERIOR
 LOW LUSTRE FINISH K542

Features

- Low temperature application down to 1.7 °C (35 °F)
- Resistant to peeling and cracking
- Excellent hide and colour retention
- Resists new mildew formation
- Soap and water clean-up
- 25 Year warranty
- Blister resistant

Recommended For

For use on primed or previously painted wood, hardboard siding, cured masonry, and unglazed brick.

General Description

A 100% acrylic latex low lustre house paint designed for application to a wide variety of exterior surfaces such as wood, hardboard, vinyl and aluminum siding, shingles, unglazed brick, concrete, stucco, cinder block, and primed metal. Provides excellent coverage and durability, with easy soap and water cleanup.

Limitations

- Do not apply when air and surface temperatures are below 1.7 °C (35 °F)
- Not for interior use

Product Information

<p>Colours — Standard: White (01)</p> <p>(May be tinted with up to 60 ml of Benjamin Moore[®] Gennex[®] colorants per 3.79L.)</p>	<table border="1"> <thead> <tr> <th data-bbox="933 741 1266 772">Technical Data[⊙]</th> <th data-bbox="1266 741 1521 772">Pastel Base</th> </tr> </thead> <tbody> <tr> <td data-bbox="933 783 1266 814">Vehicle Type</td> <td data-bbox="1266 783 1521 814">100% Acrylic Latex</td> </tr> <tr> <td data-bbox="933 825 1266 856">Pigment Type</td> <td data-bbox="1266 825 1521 856">Titanium Dioxide</td> </tr> <tr> <td data-bbox="933 867 1266 898">Volume Solids</td> <td data-bbox="1266 867 1521 898">33.3%</td> </tr> <tr> <td data-bbox="933 909 1266 940">Coverage per 3.79 L at</td> <td data-bbox="1266 909 1521 940">32.5 – 44.1 sq. m.</td> </tr> <tr> <td data-bbox="933 930 1266 961">Recommended Film Thickness</td> <td data-bbox="1266 930 1521 961">(350-475 sq. ft.)</td> </tr> <tr> <td data-bbox="933 972 1266 1003">Recommended Film Thickness</td> <td data-bbox="1266 972 1521 1003">– Wet 3.8 mils</td> </tr> <tr> <td data-bbox="933 993 1266 1024"></td> <td data-bbox="1266 993 1521 1024">– Dry 1.3 mils</td> </tr> <tr> <td colspan="2" data-bbox="933 1035 1521 1098">Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure colour uniformity and minimize the disposal of excess paint.</td> </tr> <tr> <td data-bbox="933 1108 1266 1140">Dry Time @ 25 °C</td> <td data-bbox="1266 1108 1521 1140">– To Touch 1 Hour</td> </tr> <tr> <td data-bbox="933 1140 1266 1171">(77 °F) @ 50% RH</td> <td data-bbox="1266 1140 1521 1171">– To Recoat 4 Hours</td> </tr> <tr> <td colspan="2" data-bbox="933 1182 1521 1213">High humidity and cool temperatures will result in longer dry, recoat and service times</td> </tr> <tr> <td data-bbox="933 1224 1266 1255">Dries By</td> <td data-bbox="1266 1224 1521 1255">Evaporation, Coalescence</td> </tr> <tr> <td data-bbox="933 1266 1266 1297">Viscosity</td> <td data-bbox="1266 1266 1521 1297">105 ± 2 KU</td> </tr> <tr> <td data-bbox="933 1308 1266 1339">Flash Point</td> <td data-bbox="1266 1308 1521 1339">N/A</td> </tr> <tr> <td data-bbox="933 1350 1266 1381">Gloss / Sheen</td> <td data-bbox="1266 1350 1521 1381">Low Lustre (10 – 15 @ 60°)</td> </tr> <tr> <td data-bbox="933 1392 1266 1423">Surface Temperature at Application</td> <td data-bbox="1266 1392 1521 1423">– Min. 1.7 °C (35 °F)</td> </tr> <tr> <td data-bbox="933 1413 1266 1444"></td> <td data-bbox="1266 1413 1521 1444">– Max 37.7 °C (100 °F)</td> </tr> <tr> <td data-bbox="933 1455 1266 1486">Thin With</td> <td data-bbox="1266 1455 1521 1486">See Chart</td> </tr> <tr> <td data-bbox="933 1497 1266 1528">Clean Up Thinner</td> <td data-bbox="1266 1497 1521 1528">Clean Water</td> </tr> <tr> <td data-bbox="933 1539 1266 1570">Weight Per 3.79 L</td> <td data-bbox="1266 1539 1521 1570">4.9 kg (10.78 lbs)</td> </tr> <tr> <td data-bbox="933 1581 1266 1612">Storage Temperature</td> <td data-bbox="1266 1581 1521 1612">– Min. 4.4 °C (40 °F)</td> </tr> <tr> <td data-bbox="933 1602 1266 1633"></td> <td data-bbox="1266 1602 1521 1633">– Max 35 °C (95 °F)</td> </tr> <tr> <td colspan="2" data-bbox="933 1644 1521 1751"> <p align="center">Volatile Organic Compounds (VOC)</p> <p align="center">44 g/L</p> </td> </tr> </tbody> </table>	Technical Data [⊙]	Pastel Base	Vehicle Type	100% Acrylic Latex	Pigment Type	Titanium Dioxide	Volume Solids	33.3%	Coverage per 3.79 L at	32.5 – 44.1 sq. m.	Recommended Film Thickness	(350-475 sq. ft.)	Recommended Film Thickness	– Wet 3.8 mils		– Dry 1.3 mils	Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure colour uniformity and minimize the disposal of excess paint.		Dry Time @ 25 °C	– To Touch 1 Hour	(77 °F) @ 50% RH	– To Recoat 4 Hours	High humidity and cool temperatures will result in longer dry, recoat and service times		Dries By	Evaporation, Coalescence	Viscosity	105 ± 2 KU	Flash Point	N/A	Gloss / Sheen	Low Lustre (10 – 15 @ 60°)	Surface Temperature at Application	– Min. 1.7 °C (35 °F)		– Max 37.7 °C (100 °F)	Thin With	See Chart	Clean Up Thinner	Clean Water	Weight Per 3.79 L	4.9 kg (10.78 lbs)	Storage Temperature	– Min. 4.4 °C (40 °F)		– Max 35 °C (95 °F)	<p align="center">Volatile Organic Compounds (VOC)</p> <p align="center">44 g/L</p>	
Technical Data [⊙]	Pastel Base																																																
Vehicle Type	100% Acrylic Latex																																																
Pigment Type	Titanium Dioxide																																																
Volume Solids	33.3%																																																
Coverage per 3.79 L at	32.5 – 44.1 sq. m.																																																
Recommended Film Thickness	(350-475 sq. ft.)																																																
Recommended Film Thickness	– Wet 3.8 mils																																																
	– Dry 1.3 mils																																																
Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure colour uniformity and minimize the disposal of excess paint.																																																	
Dry Time @ 25 °C	– To Touch 1 Hour																																																
(77 °F) @ 50% RH	– To Recoat 4 Hours																																																
High humidity and cool temperatures will result in longer dry, recoat and service times																																																	
Dries By	Evaporation, Coalescence																																																
Viscosity	105 ± 2 KU																																																
Flash Point	N/A																																																
Gloss / Sheen	Low Lustre (10 – 15 @ 60°)																																																
Surface Temperature at Application	– Min. 1.7 °C (35 °F)																																																
	– Max 37.7 °C (100 °F)																																																
Thin With	See Chart																																																
Clean Up Thinner	Clean Water																																																
Weight Per 3.79 L	4.9 kg (10.78 lbs)																																																
Storage Temperature	– Min. 4.4 °C (40 °F)																																																
	– Max 35 °C (95 °F)																																																
<p align="center">Volatile Organic Compounds (VOC)</p> <p align="center">44 g/L</p>																																																	
<p>— Tint Bases: Benjamin Moore[®] Gennex[®] bases 1X, 2X, 3X & 4X</p>																																																	
<p>— Special Colours: Contact your Benjamin Moore representative</p>																																																	
<p>Certifications & Qualifications: VOC compliant in all regulated areas</p> <p>Master Painters Institute MPI # 15 Water vapor permeance ASTM D1653: 42 perms Wind driven rain ASTM D6904 (1 coat masonry primer/1 coat K542) Early Rain Resistance: 1 ½ – 2 hours after application over wood, primed surfaces or previously painted surfaces (25 °C / 77 °F / 50% RH) - Other surfaces such as hardboard or vinyl may require a longer dry time</p>																																																	
<p>Customer Service Information Centre 1-800-361-5898, info@benjaminmoore.ca, www.benjaminmoore.ca</p>																																																	

[⊙]Reported values are for Pastel Base. Contact Benjamin Moore for values of other bases or colours

Surface Preparation

Surfaces must be clean, dry and free of oil, grease, wax, rust, mildew, chalk and loose or scaling paint. Cement based water proofing paints should be removed. Glossy surfaces must be dulled. Un-weathered areas such as eaves, porch ceilings, overhangs and protected wall areas should be washed with a Benjamin Moore® Clean (K318) and rinsed with a strong stream of water from a garden hose or power washer to remove contaminants that can interfere with proper adhesion. Stains from mildew must be removed by cleaning with Benjamin Moore® Clean (K318) prior to coating the surface. **Caution:** Refer to the (K318) Clean technical data and material safety data sheets for instructions on its proper use and handling.

All masonry surfaces must be power washed or brushed thoroughly with stiff fiber bristles to remove loose particles. New masonry substrates must be allowed to cure for 30 days before priming or painting. Poured or pre-cast concrete with a very smooth surface should be etched or abraded to promote adhesion, after removing all form release agents and curing compounds.

Difficult Substrates: Benjamin Moore offers a number of specialty primers for use over difficult substrates such as bleeding woods, grease stains, crayon markings, hard glossy surfaces, or other substrates where paint adhesion or stain suppression is a particular problem. Your Benjamin Moore retailer can recommend the right problem-solving primer for your special needs.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @ <https://www.canada.ca/en/health-canada/services/environmental-workplace-health/environmental-contaminants/lead/lead-information-package-some-commonly-asked-questions-about-lead-human-health.html>

Primer/Finish Systems

New surfaces should be fully primed, and previously painted surfaces may be primed or spot primed as necessary. For best hiding results, tint the primer to the approximate shade of the finish coat, especially when a significant colour change is desired. **Special Note:** Certain custom colours require a Deep Colour Base Primer tinted to a special prescription formula to achieve the desired colour. Consult your retailer.

Wood and engineered wood products:

Primer: Fresh Start® High-Hiding All Purpose Primer (K046) or Fresh Start® Multi-Purpose Latex Primer (F023)
Finish: 1 or 2 coats of ben® Exterior 100% Acrylic Flat Finish (K541)

Bleeding Type Woods, (Redwood and Cedar):

Primer: Fresh Start® Exterior Wood Primer (K094) or 1-2 coats of Fresh Start® High-Hiding All Purpose Primer (K046) may be used
Finish: 1 or 2 coats ben® Exterior 100% Acrylic Low Lustre Finish (K542)

Hardboard Siding, Bare or Factory Primed:

Primer: Fresh Start® High-Hiding All Purpose Primer (K046) or Fresh Start® Multi-Purpose Latex Primer (F023)
Finish: 1 or 2 coats ben® Exterior 100% Acrylic Low Lustre Finish (K542)

Vinyl & Vinyl Composite Siding:

Note: Do not paint vinyl siding or trim darker than the original colour.
Primer: Fresh Start® Multi-Purpose Latex Primer (F023)
Finish: 1 or 2 coats ben® Exterior 100% Acrylic Low Lustre Finish (K542)

Rough or Pitted Masonry:

Primer: Ultra Spec® Masonry Interior/Exterior Hi-Build Block Filler (K571)
Finish: 1 or 2 coats ben® Exterior 100% Acrylic Low Lustre Finish (K542)

Poured or Pre-cast Concrete and Fiber Cement Siding:

Primer: Fresh Start® Multi-Purpose Latex Primer (F023)
Finish: 1 or 2 coats ben® Exterior 100% Acrylic Low Lustre Finish (K542)

Ferrous Metal (Steel and Iron):

Primer: Ultra Spec HP® Acrylic Metal Primer (FP04) or Super Spec HP® Alkyd Metal Primer (KP06)
Finish: 1 or 2 coats ben® Exterior 100% Acrylic Low lustre Finish (K542)

Non-Ferrous Metal (Galvanized & Aluminum): All new metal surfaces must be thoroughly cleaned with Corotech® Oil & Grease Emulsifier (V600) to remove contaminants. New shiny non-ferrous metal surfaces that will be subject to abrasion should be dulled with very fine sandpaper or a synthetic steel wool pad to promote adhesion

Primer: Ultra Spec HP® Acrylic Metal Primer (FP04)
Finish: 1 or 2 coats ben® Exterior 100% Acrylic Low Lustre Finish (K542)

Repaint, All Substrates: Prime bare areas with the primer recommended for the substrate above.

Application

Stir thoroughly before and during use. Apply one or two coats.

Paint Application: For best results, use a premium Benjamin Moore® custom-blended nylon/polyester brush, premium Benjamin Moore® roller, or a similar product. Apply paint generously from unpainted area into wet area. This product can also be sprayed. Refer to the chart below for application recommendations.

Thinning/Clean up

Conditioning with Benjamin Moore® K518 Extender may be necessary under certain conditions to adjust open time or spray characteristics. The chart below is for general guidance		
	Mild conditions	Severe conditions
	Humid (RH> 50%) with no direct sunlight & with little to no wind	Dry (RH<50%), in direct sunlight, or windy conditions
Brush: Nylon / Polyester	No thinning necessary	Add K518 Extender or water: Max of 236 ml (8 fl. oz.) to a 3.79 L Never add other paints or solvents.
Roller: Premium Quality		
Spray: Airless Pressure: 1500 -2500 psi Tip: 0.013-0.017		

Clean Up: Clean up with warm soapy water. Spray equipment should be given a final rinse with mineral spirits to prevent rusting.

Environmental Health & Safety Information

Use only in a well ventilated area. Keep container closed when not in use. In case of spillage, absorb with inert material and dispose of in accordance with local regulations. Wash thoroughly after handling.

**KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING**

Refer to Safety Data Sheet for additional health and safety information.