



# MOORESTYLE<sup>®</sup>

EXTERIOR ACRYLIC LATEX  
SEMI-GLOSS K588

## Features

- A quality 100% Acrylic Latex Semi-Gloss finish
- Provides a breathable surface for maximum durability
- Mildew resistant
- Fast, simple clean up with warm soapy water
- Excellent gloss retention
- Resistant to peeling and cracking
- Low temperature application above 10 °C (50 °F)
- Excellent hiding
- Excellent colour retention

## Recommended For

For use on masonry surfaces such as stucco, cement and concrete blocks, unglazed brick as well as wood, metal, aluminum, vinyl, hardboard, shakes and shingles.

## General Description

This excellent quality product provides a durable semi-gloss finish. It features good gloss retention, easy brushing, rapid dry and same day recoat.

## Limitations

- Refrain from painting in direct sun
- Do not apply when damp, foggy or rainy weather is anticipated
- Do not paint vinyl siding or trim darker than the original colour.

## Product Information

<b>Colours:—Standard:</b> 588-01 Ultra White	<b>Technical Data<sup>◇</sup></b>	<b>Pastel Base</b>
<b>—Tint Bases:</b> Benjamin Moore <sup>®</sup> Colour Preview <sup>®</sup> bases 1B (Pastel), 2B (Medium), 3B (Deep), 4B (Ultra)	Vehicle Type <span style="float: right;">Acrylic Latex</span>	
<b>—Special Colours:</b> Contact your Benjamin Moore representative	Pigment Type <span style="float: right;">Titanium Dioxide</span>	
<b>Certification:</b>  <b>VOC compliant in all regulated areas.</b>	Volume Solids <span style="float: right;">31%</span>	
	Coverage per 3.79 L at Recommended Film Thickness <span style="float: right;">37.2 - 41.8 sq. m. (400 – 450 sq. ft.)</span>	
	Recommended Film Thickness <span style="float: right;">– Wet 3.7 mils – Dry 1.2 mils</span>	
	Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure colour uniformity and minimize the disposal of excess paint.	
	Dry Time @ 25 °C (77 °F) @ 50% RH <span style="float: right;">– To Touch 2 Hours – To Recoat 6 Hours</span>	
	High humidity and cool temperatures will result in longer dry, recoat and service times.	
	Dries By <span style="float: right;">Evaporation, Coalescence</span>	
	Viscosity <span style="float: right;">92 ± 2 KU</span>	
	Flash Point <span style="float: right;">None</span>	
	Gloss / Sheen <span style="float: right;">Semi-Gloss</span>	
<b>CUSTOMER SERVICE INFORMATION CENTRE:</b> 1-800-361-5898, <a href="mailto:info@benjaminmoore.ca">info@benjaminmoore.ca</a> , <a href="http://www.benjaminmoore.ca">www.benjaminmoore.ca</a>	Surface Temperature <span style="float: right;">– Min. 10 °C (50 °F) – Max. 32.2 °C (90 °F)</span>	
	Thin With <span style="float: right;">Clean Water</span>	
	Clean Up Thinner <span style="float: right;">Clean Water</span>	
	Weight Per 3.79 L <span style="float: right;">4.6 kg (10.2 lbs)</span>	
	Storage Temperature <span style="float: right;">– Min. 4.4 °C (40 °F) – Max. 35 °C (95 °F)</span>	
<b>Volatile Organic Compounds (VOC)</b>  <div style="text-align: center;">135 g/L</div>		

<sup>◇</sup> Reported values are for Pastel Base. Contact Benjamin Moore for values of other bases or colours.

## Surface Preparation

Surfaces must be clean, dry and free of oil, grease, wax, rust, mildew, chalk and loose or scaling paint. Cement based water proofing paints should be removed. Glossy surfaces must be dulled. Un-weathered areas such as eaves, porch ceilings, overhangs and protected wall areas should be washed with a Benjamin Moore® Clean (K318) and rinsed with a strong stream of water from a garden hose or power washer to remove contaminants that can interfere with proper adhesion. Stains from mildew must be removed by cleaning with Benjamin Moore® Clean (K318) prior to coating the surface. **Caution:** Refer to the (K318) Clean technical data and material safety data sheets for instructions on its proper use and handling.

All new masonry surfaces must be power washed or brushed thoroughly with stiff fibre bristles to remove loose particles. New masonry substrates must be allowed to cure for 30 days before priming or painting. Poured or pre-cast concrete with a very smooth surface should be etched or abraded to promote adhesion, after removing all form release agents and curing compounds.

**Difficult Substrates:** Benjamin Moore offers a number of specialty primers for use over difficult substrates such as bleeding woods, grease stains, crayon markings, hard glossy surfaces, or other substrates where paint adhesion or stain suppression is a particular problem. Your Benjamin Moore retailer can recommend the right problem-solving primer for your special needs.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @ [http://www.hc-sc.gc.ca/iyh-vsv/prod/paint-peinture\\_e.html](http://www.hc-sc.gc.ca/iyh-vsv/prod/paint-peinture_e.html).

## Primer/Finish Systems

New surfaces should be fully primed, and previously painted surfaces may be primed or spot primed as necessary. For best hiding results, tint the primer to the approximate shade of the finish coat, especially when a significant colour change is desired. **Special Note:** Certain custom colours require a Deep Colour Base Primer tinted to a special prescription formula to achieve the desired colour. Consult your retailer.

### Wood and engineered wood products

**Primer:** MooreStyle® Exterior Acrylic latex primer (K582), or MooreStyle® Exterior Alkyd Primer (K583)

**Finish:** 1 or 2 coats of MooreStyle® Exterior Acrylic Latex Semi-Gloss (K588)

### Bleeding Type Woods, (Redwood and Cedar)

**Primer:** Fresh Start® All-Purpose Alkyd Primer (K024) or Fresh Start® Moorwhite® Penetrating Alkyd Primer (K100)

**Finish:** 1 or 2 coats of MooreStyle® Exterior Acrylic Latex Semi-Gloss (K588)

### Hardboard Siding, Bare or Factory Primed

**Primer:** MooreStyle® Exterior Acrylic Latex Primer (K582), or MooreStyle® Exterior Alkyd Primer (K583)

**Finish:** 1 or 2 coats of MooreStyle® Exterior Acrylic Latex Semi-Gloss (K588)

### Rough or Pitted Masonry

**Primer:** Super Spec® Latex Block Filler (K160) or Super Spec® Masonry Interior/Exterior Hi-Build Block Filler (K206)

**Finish:** 1 or 2 coats of MooreStyle® Exterior Acrylic Latex Semi-Gloss (K588)

### Poured or Pre-cast Concrete and Fibre Cement Siding

**Primer:** MooreStyle® Exterior Acrylic latex primer (K582), Fresh Start® All-Purpose 100% Acrylic Primer (F/K023) or Fresh Start® 100% Acrylic Superior Primer (K046)

**Finish:** 1 or 2 coats of MooreStyle® Exterior Acrylic Latex Semi-Gloss (K588)

### Ferrous Metal (Steel and Iron)

**Primer:** Super Spec HP® Acrylic Metal Primer (KP04), Super Spec HP® Alkyd Metal Primer (KP06) or Fresh Start® Rust Inhibitive Primer (K163)

**Finish:** 1 or 2 coats of MooreStyle® Exterior Acrylic Latex Semi-Gloss (K588)

**Non-Ferrous Metal (Galvanized & Aluminum)** All new metal surfaces must be thoroughly cleaned with Super Spec HP® Oil & Grease Emulsifier (KP83) to remove contaminants. New shiny non-ferrous metal surfaces that will be subject to abrasion should be dulled with very fine sandpaper or a synthetic steel wool pad to promote adhesion

**Primer:** Super Spec HP® Acrylic Metal Primer (KP04)

**Finish:** 1 or 2 coats of MooreStyle® Exterior Acrylic Latex Semi-Gloss (K588)

**Repaint, All Substrates:** Prime bare areas with the primer recommended for the substrate above.

## Application

Stir thoroughly before and during use. Apply one or two coats.

**Paint Application:** For best results, use a premium Benjamin Moore® custom-blended nylon/polyester brush, premium Benjamin Moore® roller, or a similar product. Apply paint generously from unpainted area into wet area. This product can also be sprayed.

## Thinning/Cleanup

**Clean Up:** Clean up with warm soapy water. Spray equipment should be given a final rinse with mineral spirits to prevent rusting.

**USE COMPLETELY OR DISPOSE OF PROPERLY.** Dry empty containers may be recycled in a can recycling program. Local disposal requirements vary; consult your sanitation department or provincial environmental agency on disposal options.

## Environmental, Health & Safety Information

**Use only in a well ventilated area.** Keep container closed when not in use. In case of spillage, absorb with inert material and dispose of in accordance with local regulations. Wash thoroughly after handling.

**KEEP OUT OF REACH OF CHILDREN  
PROTECT FROM FREEZING**

**Refer to Material Safety Data Sheet for  
additional health and safety information.**