

General Description

An easy to apply fast-drying vinyl acrylic primer/finish for use on properly prepared interior drywall and thoroughly cured plaster.

- Uniform Flat Finish
- Good Dry Hide
- Good Touch Up
- Resists Spattering

Usage

New interior drywall for walls and ceilings, and thoroughly cured plaster. It is ideal for new residential and commercial construction, as well as rental properties.

Colors	White (11)
Bases	N/A
Colorant System	N/A

Can be tinted with up to 2 fl. oz. of Benjamin Moore Genex®, Color Preview® or Universal colorant per gallon.

Technical Data

Vehicle	Vinyl Acrylic	
Pigment	Titanium Dioxide	
Volume Solids	30 ± 2%	
Spread Rate Per Gallon	300 – 400 Sq. Ft.	
Recommended	Wet:	4.0 – 5.3 mils
Film Thickness	Dry:	1.2 – 1.6 mils
Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint.		
Dry Time @ 77 °F	To Touch:	30 Minutes
(25 °C) @ 50% RH	To Recoat:	4 hours
High humidity and cool temperatures will result in longer dry, recoat and service times.		
Surface Temperature	Min:	50 °F
During Application	Max:	90 °F
Viscosity	112 ± 4 KU	
Flash Point	N/A	
Sheen / Gloss	1 – 3 @ 85°	
Clean Up	Warm, soapy water	
Thinner	Clean water	
Weight Per Gallon	10.9 lbs.	
Storage Temperature	Min:	40 °F
	Max:	95 °F
VOC	19 g/L	0.16 lbs./gallon

Surface Preparation

Surfaces to be painted must be clean, dry, and free of dirt, dust, grease, oil, soap, wax, scaling paint, water soluble materials and mildew. Remove any peeling or scaling paint and sand these areas to feather edges smooth with adjacent surfaces. Glossy areas should be dulled. Drywall surfaces must be free of sanding dust. Spot prime before and after filling nail holes, cracks, and other surface imperfections.

New plaster or masonry surfaces must be allowed to cure (30 days) before applying base coat. Cured plaster should be hard, have a slight sheen and maximum pH of 10; soft, porous or powdery plaster indicates improper cure. Knife off any protrusions and prime plaster before and after applying patching compound. Remove any powder or loose particles.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Informational Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Application

Stir product with a circular, lifting motion before you begin to paint. Coronado® PVA Primer / Finish may be applied by brush, roller, or spray, at a rate of application not to exceed 400 square feet per gallon. Surface texture and porosity will affect actual yield. For best brush application results, use a quality synthetic filament brush. For roller application use a 3/8" nap cover for smooth surfaces, a 1/2" nap cover for semi-rough surfaces, and a 3/4" nap cover for rough surfaces. May be reduced with clean water up to 15% for spray application.

For use as a primer, apply one coat allowing 4 hours to dry before applying 1-2 finish coats. For use as a primer and finish, apply 2 coats allowing 4 hours to dry between each coat.

Spray, Airless:
 Pressure / 1,500 – 3,000 PSI
 Tip / 0.013 – 0.017

Compliance & Certifications

FEDERAL	✓
OTC	✓
OTC II	✓
CARB	✓
CARB07	✓
CARB19	✓
UTAH	✓
AZMC	✓
SCAQMD	✓

Eligible for LEED® v4	✓
CDPH Emissions Certified	✓
Eligible for CHPS low emitting credit (Collaborative for High Performance Schools)	✓
MPI	50

Limitations

- Apply when surface temperature is above 50 °F (10 °C).
- Not for use in high-abuse areas that are frequently washed or scrubbed.

Technical Assistance

Available through your local authorized independent retailer.

call 1-866-708-9180
 visit www.benjaminmoore.com

Clean Up

Wash brushes, rollers, and other painting tools in warm soapy water immediately after use. Spray equipment should be given a final rinse with mineral spirits to prevent rusting.

USE COMPLETELY OR DISPOSE OF PROPERLY. Dry, empty containers may be recycled in a can recycling program. Local disposal requirements vary; consult your sanitation department or state-designated environmental agency on disposal options.

Environmental Health & Safety Information

Use only with adequate ventilation. Do not breathe vapors, spray mist or sanding dust. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to dust and spray mist by wearing a NIOSH approved respirator during application, sanding and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling.



WARNING Cancer and Reproductive Harm— www.P65Warnings.ca.gov
Refer to the product label & Safety Data Sheet for product specific information.

WARNING: This product contains isothiazolinone compounds at levels of <0.1%. These substances are biocides commonly found in most paints and a variety of personal care products as a preservative. Certain individuals may be sensitive or allergic to these substances, even at low levels.

FIRST AID: If affected by inhalation of vapors or spray mist, remove to fresh air. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention immediately; for skin, wash thoroughly with soap and water. If symptoms persist, seek medical attention. If swallowed, do not induce vomiting. Get medical attention immediately.

IN CASE OF SPILL – Absorb with inert material and dispose of as specified under “Clean Up”.

**KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING**

**Refer to Safety Data Sheet for additional health
and safety information.**