



# QUICKSTAIN ALKYD WIPING STAIN 1AS.12XX

## Features

- 17 Pre-Mixed popular Colours
- Tint Base For Custom Colours
- Ready To Use Formulation
- Uniform Penetration
- Superior Grain Definition
- Resists Fading and Bleeding
- Fast Drying

## General Description

Lenmar® QuickStain Alkyd Wiping Stains have been uniquely designed for the professional woodworker in the Flooring, Furniture & Cabinet Industry and are formulated for ease of use, and colour stability. The major benefits of this stain line include: 17 of the most popular pre-mixed stain colours, a natural / clear tint base for custom tinting with Lenmar® Dyes and colorants (or another approved system), capability to intermix different colours to create new stains, ease of application for uniform penetration, superior grain definition, and resistance to bleeding and fading. Do not apply multiple coats of stain, remove all excess stain, and allow to thoroughly dry before applying topcoat.

## Recommended For

Kitchen Cabinets, Furniture, Window & Door Trim, Baseboards & Moulding, Interior Doors & Hand Rails, Wood Floors.

## Limitations

Product Information																																		
<b>Colours — Standard:</b> Cherry Mahogany, New England Walnut, Dark Mahogany, Cordovan, Spiced Brown, Golden Oak, Fruitwood, Special Walnut, Spanish Oak, Salem Maple, Ebony, White, Mission Oak, Dark Cherry, Blackberry, Dark Walnut, Traditional Cherry	<b>Technical Data</b> <sup>◇</sup> <table border="1"> <thead> <tr> <th colspan="2"></th> <th>White</th> </tr> </thead> <tbody> <tr> <td>Vehicle Type</td> <td></td> <td>Alkyd</td> </tr> <tr> <td>Pigment Type</td> <td></td> <td>N/A</td> </tr> <tr> <td>Weight Solids</td> <td></td> <td>39% ± 1.0%</td> </tr> <tr> <td>Volume Solids</td> <td></td> <td>18% ± 1.0%</td> </tr> <tr> <td>Coverage per 3.79 L at 1 mil DFT</td> <td></td> <td>N/A</td> </tr> <tr> <td>Recommended Film Thickness</td> <td>– Wet</td> <td>N/A</td> </tr> <tr> <td></td> <td>– Dry</td> <td>N/A</td> </tr> <tr> <td>Dry Time @ 23.8 °C (75 °F) @ 50% RH</td> <td>– Tack Free</td> <td>15 Minutes</td> </tr> <tr> <td></td> <td>– To Screen</td> <td>N/A</td> </tr> <tr> <td></td> <td>– To Recoat</td> <td>30 Minutes</td> </tr> </tbody> </table>			White	Vehicle Type		Alkyd	Pigment Type		N/A	Weight Solids		39% ± 1.0%	Volume Solids		18% ± 1.0%	Coverage per 3.79 L at 1 mil DFT		N/A	Recommended Film Thickness	– Wet	N/A		– Dry	N/A	Dry Time @ 23.8 °C (75 °F) @ 50% RH	– Tack Free	15 Minutes		– To Screen	N/A		– To Recoat	30 Minutes
		White																																
Vehicle Type		Alkyd																																
Pigment Type		N/A																																
Weight Solids		39% ± 1.0%																																
Volume Solids		18% ± 1.0%																																
Coverage per 3.79 L at 1 mil DFT		N/A																																
Recommended Film Thickness	– Wet	N/A																																
	– Dry	N/A																																
Dry Time @ 23.8 °C (75 °F) @ 50% RH	– Tack Free	15 Minutes																																
	– To Screen	N/A																																
	– To Recoat	30 Minutes																																
<b>— Tint Bases:</b> 1AS.1200, Natural/Clear Base	High humidity and cool temperatures will result in longer dry and recoat times.																																	
<b>— Special Colours:</b> Contact your dealer/distributor.	Dries By Evaporation/Oxidation																																	
<b>Certifications &amp; Qualifications:</b> The products supported by this data sheet contain a maximum of 550 grams per litre VOC /VOS excluding water & exempt solvents.  This product is not compliant for field applications. This product is intended for Shop or OEM application only.	Viscosity N/A Flash Point 12.8 °C (55 °F) Gloss / Sheen N/A Surface Temperature at Application – Min. 7.2 °C (45 °F) – Max. 32.2 °C (90 °F) Thin With See Application Section Clean Up Thinner 1A.137 Mineral Spirits																																	
<b>Technical Assistance:</b> Available through your local authorized independent dealer. For the location of the dealer nearest you, call 1-800-361-5898 or visit <a href="http://www.lenmar-coatings.ca">www.lenmar-coatings.ca</a>	Weight Per 3.79 L 3.3 – 4.4 kg (7.33 – 9.77 lbs) Storage Temperature – Min. 10 °C (50 °F) – Max. 32.2 °C (90 °F) <b>Volatile Organic Compounds (VOC)</b>  500 Grams/Litre																																	

◇ Reported values are for White. Contact dealer/distributor for values of other bases or colours.

## QuickStain Alkyd Wiping Stain 1AS.12XX

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @ <https://www.canada.ca/en/health-canada/services/environmental-workplace-health/environmental-contaminants/lead/lead-information-package-some-commonly-asked-questions-about-lead-human-health.html>

### Application

Over properly prepared interior wood surfaces, apply only one full coat of QuickStain Alkyd Wiping Stain by spray, with a natural bristle brush or with a clean lint-free cloth. Remove all excess stain within 5 minutes after application. When dry (usually 30 minutes), continue with sealer and topcoat system in accordance with their Product Data Sheets. For OEM spray-no-wipe applications, reduce a minimum of 1:1 with VM&P naphtha, and apply in very light coats. Check adhesion before proceeding with this type of application. See characteristics for finish options and recommended dry times. For floor applications, wait 2 – 3 hours before proceeding with topcoats.

### Specifications

Moisture content of wood should be no higher than 9%. Wood must be free of all surface contaminants. Using 120-grit sandpaper, sand with the grain and remove all dust. Thoroughly mix stain and intermix multiple containers of same colour. Test colour before proceeding. Colour intensity may vary due to wood species, surface preparation, and method of application. Submerge stain soaked rags in water to avoid spontaneous combustion. Read label and SDS for additional information and warnings.

### Clean Up

Clean up with 1A.137 Mineral Spirits.

### Environmental Health & Safety Information

#### **DANGER!**

**Causes skin irritation**

**May cause genetic defects**

**May cause cancer**

**Suspected of damaging fertility or the unborn child**

**May cause respiratory irritation. May cause drowsiness or dizziness**

**Causes damage to organs through prolonged or repeated exposure**

**May be fatal if swallowed and enters airways**

**Flammable liquid and vapor**

**Risk of spontaneous combustion**

**Prevention:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wash face, hands and any exposed skin thoroughly after handling. Do not breathe dust/fume/mist/vapors/spray. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/open flames/hot surfaces, no smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep cool. Immediately after use, place rags, steel wool or waste used with this product in a sealed water-filled metal container or lay flat to dry.

**Response:** If exposed or concerned get medical attention. If skin irritation occurs get medical attention. If on skin (or hair) take off immediately all contaminated clothing. Rinse skin with water. Wash contaminated clothing before reuse. If inhaled remove victim to fresh air and keep at rest in a position comfortable for breathing. If swallowed immediately call a POISON CENTER or physician. Do NOT induce vomiting. In case of fire use CO<sub>2</sub>, dry chemical, or foam for extinction.

**Storage:** Store locked up. Store in a well-ventilated place. Keep container tightly closed.

**Disposal:** Dispose of contents /container to an approved waste disposal plant. Materials such as rags used with this product may begin to burn by themselves. After use, put rags in water or lay flat to dry, and then discard.

This document represents hazards of the product referenced above. Refer to the individual Safety Data Sheet for hazards of the specific product you will be using.

### **KEEP OUT OF REACH OF CHILDREN FOR PROFESSIONAL USE ONLY**

**THIS PRODUCT IS INTENDED FOR SHOP OR  
OEM APPLICATION ONLY.**

**READ ALL DIRECTIONS BEFORE USE.  
UNDERSTAND ALL DANGERS WITH THIS  
PRODUCT PRIOR TO USE.**

**Refer to Safety Data Sheet for  
additional health and safety information.**