



QUICKSTAIN ALKYD WIPING STAIN 1AS.12XX

Features

- 17 Pre-Mixed popular Colors
- Tint Base For Custom Colors
- Ready To Use Formulation
- Uniform Penetration
- Superior Grain Definition
- Resists Fading and Bleeding
- Fast Drying

General Description

Lenmar® QuickStain Alkyd Wiping Stains have been uniquely designed for the professional woodworker in the Flooring, Furniture & Cabinet Industry and are formulated for ease of use, and color stability. The major benefits of this stain line include: 17 of the most popular pre-mixed stain colors, a natural / clear tint base for custom tinting with Lenmar® Dyes and colorants (or another approved system), capability to intermix different colors to create new stains, ease of application for uniform penetration, superior grain definition, and resistance to bleeding and fading. Do not apply multiple coats of stain, remove all excess stain, and allow to thoroughly dry before applying topcoat.

Recommended For

Kitchen Cabinets, Furniture, Window & Door Trim, Baseboards & Molding, Interior Doors & Hand Rails, Wood Floors.

Limitations

Product Information

<p>Colors — Standard: Cherry Mahogany, New England Walnut, Dark Mahogany, Cordovan, Spiced Brown, Golden Oak, Fruitwood, Special Walnut, Spanish Oak, Salem Maple, Ebony, White, Mission Oak, Dark Cherry, Blackberry, Dark Walnut, Traditional Cherry</p>	<table border="1"> <thead> <tr> <th colspan="2">Technical Data◇</th> <th>White</th> </tr> </thead> <tbody> <tr> <td>Vehicle Type</td> <td></td> <td>Alkyd</td> </tr> <tr> <td>Pigment Type</td> <td></td> <td>N/A</td> </tr> <tr> <td>Weight Solids</td> <td></td> <td>39% ± 1.0%</td> </tr> <tr> <td>Volume Solids</td> <td></td> <td>18% ± 1.0%</td> </tr> <tr> <td>Coverage per Gallon at 1 mil DFT</td> <td></td> <td>N/A</td> </tr> <tr> <td>Recommended Film Thickness</td> <td>- Wet - Dry</td> <td>N/A N/A</td> </tr> <tr> <td>Dry Time @ 75 °F (23.8 °C) @ 50% RH</td> <td>- Tack Free - To Screen - To Recoat</td> <td>15 Minutes N/A 30 Minutes</td> </tr> <tr> <td colspan="3">High humidity and cool temperatures will result in longer dry and recoat times.</td> </tr> <tr> <td>Dries By</td> <td></td> <td>Evaporation/Oxidation</td> </tr> <tr> <td>Viscosity</td> <td></td> <td>N/A</td> </tr> <tr> <td>Flash Point</td> <td></td> <td>55° F (12.8°C)</td> </tr> <tr> <td>Gloss / Sheen</td> <td></td> <td>N/A</td> </tr> <tr> <td>Surface Temperature at Application</td> <td>- Min. - Max.</td> <td>45 °F 90 °F</td> </tr> <tr> <td>Thin With</td> <td></td> <td>See Application Section</td> </tr> <tr> <td>Clean Up Thinner</td> <td></td> <td>1A.137 Mineral Spirits</td> </tr> <tr> <td>Weight Per Gallon</td> <td></td> <td>7.33 – 9.77 lbs</td> </tr> <tr> <td>Storage Temperature</td> <td>- Min. - Max.</td> <td>50 °F 90 °F</td> </tr> <tr> <td colspan="3">Volatile Organic Compounds (VOC)</td> </tr> <tr> <td></td> <td>500 Grams/Liter</td> <td>4.17 Lbs./Gallon</td> </tr> </tbody> </table>	Technical Data◇		White	Vehicle Type		Alkyd	Pigment Type		N/A	Weight Solids		39% ± 1.0%	Volume Solids		18% ± 1.0%	Coverage per Gallon at 1 mil DFT		N/A	Recommended Film Thickness	- Wet - Dry	N/A N/A	Dry Time @ 75 °F (23.8 °C) @ 50% RH	- Tack Free - To Screen - To Recoat	15 Minutes N/A 30 Minutes	High humidity and cool temperatures will result in longer dry and recoat times.			Dries By		Evaporation/Oxidation	Viscosity		N/A	Flash Point		55° F (12.8°C)	Gloss / Sheen		N/A	Surface Temperature at Application	- Min. - Max.	45 °F 90 °F	Thin With		See Application Section	Clean Up Thinner		1A.137 Mineral Spirits	Weight Per Gallon		7.33 – 9.77 lbs	Storage Temperature	- Min. - Max.	50 °F 90 °F	Volatile Organic Compounds (VOC)				500 Grams/Liter	4.17 Lbs./Gallon
Technical Data◇		White																																																											
Vehicle Type		Alkyd																																																											
Pigment Type		N/A																																																											
Weight Solids		39% ± 1.0%																																																											
Volume Solids		18% ± 1.0%																																																											
Coverage per Gallon at 1 mil DFT		N/A																																																											
Recommended Film Thickness	- Wet - Dry	N/A N/A																																																											
Dry Time @ 75 °F (23.8 °C) @ 50% RH	- Tack Free - To Screen - To Recoat	15 Minutes N/A 30 Minutes																																																											
High humidity and cool temperatures will result in longer dry and recoat times.																																																													
Dries By		Evaporation/Oxidation																																																											
Viscosity		N/A																																																											
Flash Point		55° F (12.8°C)																																																											
Gloss / Sheen		N/A																																																											
Surface Temperature at Application	- Min. - Max.	45 °F 90 °F																																																											
Thin With		See Application Section																																																											
Clean Up Thinner		1A.137 Mineral Spirits																																																											
Weight Per Gallon		7.33 – 9.77 lbs																																																											
Storage Temperature	- Min. - Max.	50 °F 90 °F																																																											
Volatile Organic Compounds (VOC)																																																													
	500 Grams/Liter	4.17 Lbs./Gallon																																																											
<p>— Tint Bases: 1AS.1200, Natural/Clear Base</p>																																																													
<p>— Special Colors: Contact your dealer</p>																																																													
<p>Certifications & Qualifications: VOC compliant in federally regulated areas only</p> <p>The products supported by this data sheet contain a maximum of 550 grams per liter VOC /VOS (4.59 lbs/gal.) excluding water & exempt solvents.</p>																																																													
<p>Technical Assistance: Available through your local authorized independent Lenmar dealer. For the location of the dealer nearest you, call 1-866-708-9180 or visit www.lenmar-coatings.com</p>																																																													

◇ Reported values are for White. Contact dealer/distributor for values of other bases or colors.

QuickStain Alkyd Wiping Stain 1AS.12XX

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Application

Over properly prepared interior wood surfaces, apply only one full coat of QuickStain Alkyd Wiping Stain by spray, with a natural bristle brush or with a clean lint-free cloth. Remove all excess stain within 5 minutes after application. When dry (usually 30 minutes), continue with sealer and topcoat system in accordance with their Product Data Sheets. For OEM spray-no-wipe applications, reduce a minimum of 1:1 with VM&P naphtha, and apply in very light coats. Check adhesion before proceeding with this type of application. See characteristics for finish options and recommended dry times. For floor applications, wait 2 – 3 hours before proceeding with topcoats.

Specifications

Moisture content of wood should be no higher than 9%. Wood must be free of all surface contaminants. Using 120-grit sandpaper, sand with the grain and remove all dust. Thoroughly mix stain and intermix multiple containers of same color. Test color before proceeding. Color intensity may vary due to wood species, surface preparation, and method of application. Submerge stain soaked rags in water to avoid spontaneous combustion. Read label and SDS for additional information and warnings.

Clean Up

Clean up with 1A.137 Mineral Spirits.

Environmental Health & Safety Information

DANGER!

Causes serious eye irritation

May cause cancer

Suspected of damaging fertility or the unborn child

May cause damage to organs

Causes damage to organs through prolonged or repeated exposure

May be fatal if swallowed and enters airways

Flammable liquid and vapor

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wash face, hands and any exposed skin thoroughly after handling. Wear eye/face protection. Do not breathe dust/fume/mist/vapors/spray. Do not eat, drink or smoke when using this product. Keep away from heat/sparks/open flames/hot surfaces, no smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

Response: If exposed or concerned get medical attention. If in eyes rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists get medical attention. If on skin (or hair) take off immediately all contaminated clothing. Rinse skin with water. If swallowed immediately call a POISON CENTER or physician. Do NOT induce vomiting. In case of fire use CO₂, dry chemical, or foam for extinction.

Storage: Store locked up. Store in a well-ventilated place. Keep cool.

Disposal: Dispose of contents /container to an approved waste disposal plant.

DANGER - Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed water-filled metal container.



WARNING Cancer and Reproductive Harm—
www.P65warnings.ca.gov

This document represents hazards of the product referenced above. Refer to the individual Safety Data Sheet for hazards of the specific product you will be using.

**KEEP OUT OF REACH OF CHILDREN
INTENDED FOR PROFESSIONAL USE ONLY**

**WARNING; USE OF THIS PRODUCT ON
FLOOR APPLICATIONS IS PROHIBITED IN THE
STATE OF MASSACHUSETTS AND THE CITY
OF NEW YORK.**

**This product may be compliant under
Architectural and Industrial Maintenance
regulations in some jurisdictions when field
applied to stationary structures. This product
may also be Shop or OEM applied. Check local
regulations.**

**READ ALL DIRECTIONS BEFORE USE.
UNDERSTAND ALL DANGERS WITH THIS
PRODUCT PRIOR TO USE.**

**Refer to Safety Data Sheet for
additional health and safety information.**