



QUICKSTAIN LACQUER WIPING STAIN 1LS.1XXX

Features

- 17 Pre-Mixed Popular Colours
- Tint Base For Custom Colours
- Ready To Use Formulations
- Uniform Penetration
- Helps Against Blotching
- Superior Grain Definition
- Resists Fading and Bleeding
- Fast Drying For Lacquers

Recommended For

Kitchen Cabinets, Furniture, Window and Door Trim, Baseboards and Moulding, Interior Doors and Hand Rails.

General Description

Lenmar® QuickStain Lacquer Wiping Stains have been uniquely designed for the professional woodworker in the Furniture & Cabinet Industry and are formulated strictly for use in shop applications only. The major benefits of this stain line include: 17 of the most popular pre-mixed stain colours, a natural / clear tint base for custom tinting with 144 colorants (or another approved system), capability to intermix different colours to create new stains, ease of application for uniform penetration, superior grain definition, and resistance to bleeding and fading. Do not apply multiple coats of stain, remove all excess stain, and allow to thoroughly dry before top coating.

Limitations

- Not for use on Floors.

Product Information

Colours — Standard:

Cherry Mahogany, New England Walnut, Dark Mahogany, Cordovan, Spiced Brown, Golden Oak, Fruitwood, Special Walnut, Spanish Oak, Salem Maple, Ebony, White, Mission Oak, Dark Cherry, Blackberry, Dark Walnut, Traditional Cherry

— Tint Bases:

1LS.1000, Natural/ Clear Base may be tinted with 144/844 type Industrial Colorants up to 237 mL per 3.79 L.

— Special Colours:

Contact your Dealer/Distributor.

Certifications & Qualifications:

The products supported by this data sheet contain a maximum of 830 grams per litre VOC /VOS excluding water & exempt solvents.

This product is not compliant for field applications.

Technical Assistance:

Available through your local authorized independent dealer. For the location of the dealer nearest you, call 1-800-361-5898 or visit www.lenmar-coatings.ca

Technical Data◇

	White
Vehicle Type	Proprietary
Pigment Type	N/A
Weight Solids	15%
Volume Solids	10%
Coverage per 3.79 L @ 1 mil DFT	N/A
Recommended Film Thickness	– Wet N/A – Dry N/A
Dry Time @ 23.8 °C (75 °F) @ 50% RH	– Spray & Wipe 10 – 15 Minutes – Spray No Wipe 20 – 30 Minutes
High humidity and cool temperatures will result in longer dry and recoat times.	
Dries By	Evaporation
Viscosity	18 – 22 Seconds (#2 Zahn)
Flash Point	17.8 °C (64 °F)
Gloss / Sheen	N/A
Surface Temperature at Application	– Min. 7.2 °C (68 °F) – Max. 32.2 °C (90 °F)
Thin With	See Application section on page 2
Clean Up Thinner	1A.406 or 1A.519 Lacquer Thinner
Weight Per 3.79 L	2.9 – 4.4 kg (6.49 – 9.77 lbs)
Storage Temperature	– Min. 10 °C (50 °F) – Max. 32.2 °C (90 °F)

Volatile Organic Compounds (VOC)

739 Grams/Litre

◇ Reported values are for White. Contact dealer/distributor for values of other bases or colours.

QuickStain Lacquer Wiping Stain 1LS.1XXX

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @ <https://www.canada.ca/en/health-canada/services/environmental-workplace-health/environmental-contaminants/lead/lead-information-package-some-commonly-asked-questions-about-lead-human-health.html>

Application

Over properly prepared interior wood surfaces, apply only one full coat of QuickStain Lacquer Wiping Stain by spray, with a natural bristle brush or with a clean lint-free cloth. Remove all excess stain within 5 minutes after application. When dry (usually 10-15 minutes), continue with sealer and topcoat system in accordance with their Product Data Sheets. For spray-no-wipe applications, reduce a minimum of 2:1 with Lacquer Thinner, n-Butyl Acetate, or Acetone (STAY IN COMPLIANCE WITH LOCAL REGULATIONS) (Two parts thinner to one part stain). Apply in light coats, 1-2 wet mils. Check adhesion before proceeding with this type of application (should be used for light colours only). See characteristics for recommended dry times.

Specifications

Moisture content of wood should be no higher than 9%. Wood must be free of all surface contaminants. Using 120-150 grit sandpaper, sand with the grain and remove all dust. Thoroughly mix stain and intermix multiple containers of same colour. Test colour before proceeding. Colour intensity may vary due to wood species, surface preparation, and method of application. Submerge stain soaked rags in water to avoid spontaneous combustion. Read label and SDS for additional information and warnings.

Clean Up

Clean up with 1A.406 or 1A.519 Lacquer Thinner.

Environmental Health & Safety Information

DANGER!

Harmful if swallowed

Causes skin irritation

Causes serious eye irritation

Suspected of causing cancer

Suspected of damaging fertility or the unborn child

May cause respiratory irritation. May cause drowsiness or dizziness

Causes damage to organs through prolonged or repeated exposure

May be fatal if swallowed and enters airways

Highly flammable liquid and vapor

Reactive flammable material

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wash face, hands and any exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. Wear eye/face protection. Do not breathe dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep cool.

Response: IF exposed or concerned: Get medical advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/ attention. If skin irritation occurs: Get medical advice/ attention. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. Rinse mouth. In case of fire: Use CO₂, dry chemical, or foam for extinction.

Storage: Store locked up. Store in a well-ventilated place. Keep container tightly closed.

Disposal: Dispose of contents /container to an approved waste disposal plant.

This document represents hazards of the product referenced above. Refer to the individual Safety Data Sheet for hazards of the specific product you will be using.

**NOT FOR USE ON FLOORS
FOR PROFESSIONAL USE ONLY
KEEP OUT OF REACH OF CHILDREN**

**THIS PRODUCT IS INTENDED FOR SHOP OR
OEM APPLICATION ONLY.**

**READ ALL DIRECTIONS BEFORE USE.
UNDERSTAND ALL DANGERS WITH THIS
PRODUCT PRIOR TO USE.**

**Refer to Safety Data Sheet for
additional health and safety information.**