



# QUICKSTAIN®

## GILSONITE BASE

### 1U.1053

#### Features

- Easy to mix in
- Provides good grain definition
- Clean Color

#### Recommended For

- Addition to solvent based stains to obtain better grain strike.

#### General Description

Lenmar® QuickStain® Gilsonite base has been uniquely designed for use as a colorant for Lenmar Dealers and the professional wood finisher and is formulated strictly for use in shop applications only. Gilsonite is used to obtain darker grain in lighter wiping stain colors.

#### Limitations

- Gilsonite should only be added to solvent borne systems, and should be tested in all systems to insure compatibility.
- This product is intended for Shop or OEM application only.

#### Product Information

Product Information	
<b>Colors — Standard:</b> N/A	<b>Technical Data</b> $\diamond$
<b>— Tint Bases:</b> N/A	<b>Base</b> Vehicle Type: Gilsonite Pigment Type: Asphalt-based Weight Solids: 19.9% Volume Solids: 15.6%
<b>— Special Colors:</b> Contact your Dealer/Distributor.	Coverage per Gallon at Recommended Film Thickness: N/A Recommended Film Thickness: – Wet: N/A – Dry: N/A Coverage calculation does not include spray loss or equipment inefficiency. Also allow for wood species, surface preparation, surface defects and porosity of substrate to affect spread rates.
<b>Certification &amp; Qualifications:</b> <b>VOC compliant in federally regulated areas only</b>	Dry Time @ 75 °F (23.8 °C) @ 50% RH: To Touch: Dependent upon base product added to To Recoat: Dependent upon base product added to Dries By: N/A
<b>Technical Assistance:</b> Available through your local authorized independent Lenmar dealer. For the location of the dealer nearest you, call 1-866-708-9180 or visit <a href="http://www.lenmar-coatings.com">www.lenmar-coatings.com</a>	Viscosity: N/A Flash Point: 105 °F (41 °C) Gloss / Sheen: N/A Surface Temperature at Application: – Min.: 68 °F – Max.: 90 °F Thin With: VM&P Naphtha Clean Up Thinner: 1A.137 Mineral Spirits Weight Per Gallon: 7.0 lbs. Storage Temperature: – Min.: 50 °F – Max.: 90 °F  <b>Volatile Organic Compounds (VOC)</b>  684 Grams/Liter    5.70 Lbs./Gallon

## QuickStain® Gilsonite Base 1U.1053

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Informational Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### Application

Over properly prepared interior wood surfaces. Gilsonite should be added at levels below 8% by volume to any Lenmar® wiping stain system. Products should be tested for compatibility before use. Finished products should be tested for settling and color stability as well as color matching. Gilsonite colorants are asphalt based, and can make some stains settle more quickly and may require more frequent agitation while in use to maintain color consistency. See characteristics for finish options and recommended dry times. VM&P Naphtha and Mineral Spirits make the best solvents, but others may be used if desired. Check with technical service if questions arise.

### Specifications

Moisture content of wood should be no higher than 9%. Wood must be free of all surface contaminants. Using 150-grit sandpaper, sand with the grain and remove all dust. Thoroughly mix gilsonite before addition to an existing stain. Failure to do so may impact color consistency. Always test the color before proceeding. Color intensity may vary due to wood species, surface preparation and method of application. Read label and SDS for additional information and warnings.

### Clean up

Clean up with 1A.137 Mineral Spirits.

### Environmental Health & Safety Information

#### DANGER!

**Causes skin irritation**

**Suspected of causing cancer**

**May cause drowsiness or dizziness**

**Causes damage to organs through prolonged or repeated exposure**

**May be fatal if swallowed and enters airways**

**Flammable liquid and vapor**

**Prevention:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wash face, hands and any exposed skin thoroughly after handling. Do not breathe dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep cool.

**Response:** IF exposed or concerned: Get medical advice/attention. If skin irritation occurs: Get medical advice/attention. IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower. Wash contaminated clothing before reuse. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction.

**Storage:** Store locked up. Store in a well-ventilated place. Keep container tightly closed.

**Disposal:** Dispose of contents/container to an approved waste disposal plant.

**IMPORTANT:** Designed to be mixed with other components. Mixture will have hazards of all components. Before opening packages, read all warning labels. Follow all precautions.

May cause allergic skin reaction



**WARNING** Cancer and Reproductive Harm—  
[www.P65warnings.ca.gov](http://www.P65warnings.ca.gov)

This document represents hazards of the product referenced above. Refer to the individual Safety Data Sheet for hazards of the specific product you will be using.

**KEEP OUT OF REACH OF CHILDREN  
INTENDED FOR PROFESSIONAL USE ONLY**

**THIS PRODUCT IS INTENDED FOR SHOP OR  
OEM APPLICATION ONLY.**

**READ ALL DIRECTIONS BEFORE USE.  
UNDERSTAND ALL DANGERS WITH THIS  
PRODUCT PRIOR TO USE.**

**Refer to Safety Data Sheet for  
additional health and safety information.**