



FLOOR CLEANER

1YB.321

Features

- Floor Cleaner
- No Residue Or Film
- Ready To Use
- Zero VOC

General Description

Floor Cleaner 1YB.321 is designed to clean hardwood floors easily and without any film or residue left behind. Floor Cleaner 1YB.321 is recommended for use as a general maintenance cleaner for hardwood floors, but may also be used to clean laminate flooring. Floor Cleaner 1YB.321 is ideal for cleaning floors prior to recoating, but is also the second cleaning step in the Lenmar® clean and prep system for refinishing hardwood floors without sanding.

Recommended For

Clean and Prep System, Cleaning and Tacking, and Maintenance Cleaning.

Limitations

- Do not pour Floor Cleaner 1YB.321 directly on any wood floor. Pouring any liquid directly on a hardwood floor may damage the wood fiber and degrade the finish.
- Do not use this product on any wax-finished floor.

Product Information

| Colors — Standard: | Technical Data | Floor Cleaner |
|--|--|------------------------------|
| N/A | Vehicle Type | Proprietary |
| — Tint Bases: | Pigment Type | N/A |
| N/A | Weight Solid | 6% – 11% |
| — Special Colors: | Volume Solids | 6% – 11% |
| N/A | Coverage per Gallon at Recommended Film Thickness | 2000 – 3000 Sq. Ft. |
| Certifications & Qualifications: | Recommended Film Thickness | – Wet N/A – Dry N/A |
| VOC compliant in all regulated areas | Depending on surface texture and porosity. | |
| The product supported by this data sheet contains zero VOC /VOS excluding water & exempt solvents. | High humidity and cool temperatures will result in longer dry, recoat and service times. | |
| | Dries By | N/A |
| | Viscosity | N/A |
| | Flash Point | >200 °F |
| | Gloss / Sheen | N/A |
| | Surface Temperature at Application | – Min. 68 °F – Max. 90 °F |
| | Thin With | Do Not Thin |
| | Clean Up Thinner | N/A |
| | Weight Per Gallon | 9.0 lbs |
| | Storage Temperature | – Min. 50 °F – Max. 90 °F |
| Technical Assistance: | Volatile Organic Compounds (VOC) | |
| Available through your local authorized independent Lenmar dealer. For the location of the dealer nearest you, call 1-866-708-9180 or visit www.lenmar-coatings.com | 0 Grams/Liter 0 Lbs./Gallon | |

Floor Cleaner 1YB.321

Surface Preparation

Preparation: Floor must be cleaned thoroughly. Remove all surface debris, such as caked on mud and chewing gum. Sweep and vacuum the floor, paying special attention to corners. Cleaning may have to be done more than once to achieve a completely clean surface. Allow floor to dry completely. Check floor for streaks or residue, and if present clean a second time.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Informational Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Application

General Purpose Cleaning: Transfer Floor Cleaner 1YB.321 to a spray bottle for easy application for spot cleaning. Spray directly onto the floor or on a microfiber cloth or mop and wipe the surface clean. For large surfaces, pour Floor Cleaner 1YB.321 into a bucket and soak several clean rags or towels until thoroughly wet. Wring out to remove excess fluid. Wrap around a push broom and mop the floor. Prevent redepositing of dirt and oil by refolding the towels to clean sides as the towel surface becomes soiled. Pay special attention to corners. Repeat the procedure until the entire floor has been cleaned.

Automatic Scrubbers: Use a red or white pad with the scrubber. Fill with Floor Cleaner 1YB.321. Make sure buffing/polishing pads and squeegees are working well. A person with a mop must follow behind the scrubber to remove any excess liquid remaining on the floor surface.

Do not pour Floor Cleaner 1YB.321 directly on any wood floor. Pouring any liquid directly on a hardwood floor may damage the wood fiber and degrade the finish. Do not use this product on any wax-finished floor.

Clean up

USE COMPLETELY OR DISPOSE OF PROPERLY. Dry empty containers may be recycled in a can recycling program. **Local disposal requirements vary; consult your sanitation department or state-designated environmental agency on disposal options.**

Environmental Health & Safety Information

Use only with adequate ventilation. Do not breathe spray mist or sanding dust. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to dust and spray mist by wearing a NIOSH approved respirator during application, sanding and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling.



WARNING Cancer and Reproductive Harm—
www.P65warnings.ca.gov

FIRST AID: In case of eye contact, flush immediately with plenty of water for at least 15 minutes; for skin, wash thoroughly with soap and water. If symptoms persist, seek medical attention. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

IN CASE OF SPILL – Absorb with inert material and dispose of as specified under “CleanUp”.

**KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING**

**Refer to Safety Data Sheet for
additional health and safety information.**