



# ELASTITE®

## 100% ACRYLIC FLAT FINISH

### 260 LINE

#### Features

- Acrylic Latex Flat House Paint
- Excellent Durability
- Superb Color Retention
- Fast Dry
- Blister Resistant

#### General Description

An Acrylic Latex Flat House Paint which provides lasting service over new or previously painted surfaces in good condition. Acrylic Latex House Paint will provide a durable and protective finish on any properly prepared and primed exterior surface.

#### Recommended For

For exterior wood, masonry, hardboard and metal in commercial, institutional and residential applications. Use on exterior siding, foundations, fascia, shutters or retaining walls. Contains an agent that inhibits growth of mildew on the surface of the paint film.

#### Limitations

- May be applied when surface and air temperatures are between 50 °F and 90 °F (10 °C and 32.2 °C).
- Do not apply if rain is threatening.

#### Product Information

Colors — Standard:	Technical Data◇	Deep Base
	Vehicle Type	Acrylic
	Pigment Type	Titanium Dioxide
	Volume Solids	43 ± 1.0%
— Tint Bases:	Coverage per Gallon at Recommended Film Thickness	325 – 400 Sq. Ft.
Deep Base	Recommended Film Thickness	– Wet 4.0 to 5.3 mils – Dry 1.7 to 2.1 mils
— Special Colors:	Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint.	
Contact your dealer.	Dry Time @ 77°F (25°C) @ 50% RH	– Tack Free 30 Minutes – To Recoat 4 Hours
<b>Certification:</b>	High humidity and cool temperatures will result in longer dry, recoat and service times.	
The products supported by this data sheet contain a maximum of 50 grams per liter VOC/VOS (0.42 lbs/gal.) excluding water & exempt solvents. This product is compliant under the Ozone Transport Commission regulations as a Flat Coating.	Dries By	Coalescence
	Viscosity	115 – 120 KU
	Flash Point	N/A
	Gloss / Sheen	Flat 3 - 10 Units@60°
	Surface Temperature at Application	– Min. 50°F – Max. 90°F
	Thin With	Clean Water
	Clean Up Thinner	Warm Soapy Water
	Weight Per Gallon	10.9 lbs
	Storage Temperature	– Min. 50°F – Max. 90°F
<b>Technical Assistance:</b>	<b>Volatile Organic Compounds (VOC)</b>	
Available through your local authorized independent dealer. For the location of the dealer nearest you, call 1-800-225-5554 or visit <a href="http://www.coronadopaint.com">www.coronadopaint.com</a> .	45 Grams/Liter	0.38 Lbs./Gallon

◇ Reported values are for Deep Base, Contact dealer for values of other bases or colors.

## Surface Preparation

Surfaces must be clean and free of grease, wax, and mildew. Remove any chalk and loose or scaling paint. If previously coated with cement-base waterproofing paints, clean by sandblasting. Glossy surfaces must be dulled. Un-weathered areas such as eaves, ceilings, and overhangs should be washed with a detergent solution and/or rinsed with a strong stream of water from a garden hose to remove contaminants that can interfere with proper adhesion. Stains from mildew must be removed by cleaning with an anti-mildew wash prior to coating the surface. **Caution:** Refer to the anti-mildew wash technical data and material safety data sheet for instructions on its proper use and handling. For metal surfaces, remove rust. Wipe down with paint thinner to remove surface oils.

All new masonry surfaces must be power washed or brushed thoroughly with stiff fiber bristles to remove loose particles. New masonry substrates must be allowed to cure for 30 days before priming or painting.

**Primers:** New surfaces should be fully primed. Previously painted surfaces should be primed or spot primed as necessary. There are a number of specialty primers available in our family of brands that can be used on difficult substrates such as bleeding woods, hard glossy surfaces, or other substrates where paint adhesion or stain blocking is a problem. Your dealer can recommend the right problem solving primer necessary to meet your needs.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

## Application

Stir product with a circular, lifting motion before you begin to paint. Acrylic Latex Flat House Paint may be applied by brush, spray, pad or roller, at a rate of application not to exceed 400 square feet per gallon. Surface texture and porosity will affect actual yield. For best brush application results, use a quality synthetic filament brush. For roller application, use a 3/8" or 1/2" nap cover for smooth surfaces, a 3/4" nap cover for semirough surfaces and a 1" or 1 1/2" nap cover for rough surfaces. For spray application, thin with clean water, up to 20% reduction if necessary. Do not apply when surface or air temperatures are below 50° F. Do not apply to hot surfaces or in direct sunlight. Do not apply if rain is threatening.

## Clean Up

Clean up with warm, soapy water followed by a clean water rinse.

USE COMPLETELY OR DISPOSE OF PROPERLY. Dry empty containers may be recycled in a can recycling program. **Local disposal requirements vary; consult your sanitation department or state-designated environmental agency on disposal options.**

## Environmental Health & Safety Information

**Cancer Hazard.** Contains Crystalline Silica which can cause cancer when in respirable form (spray mist or sanding dust).

Use only with adequate ventilation. Do not breathe spray mist or sanding dust. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to dust and spray mist by wearing a NIOSH approved respirator during application, sanding and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling.

**WARNING:** This product contains a chemical known to the state of California to cause cancer and birth defects, or other reproductive harm.

**FIRST AID:** In case of eye contact, flush immediately with plenty of water for at least 15 minutes; for skin, wash thoroughly with soap and water. If symptoms persist, seek medical attention. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

**IN CASE OF SPILL** – Absorb with inert material and dispose of as specified under "Clean up".

**KEEP OUT OF REACH OF CHILDREN  
PROTECT FROM FREEZING**

**Refer to Safety Data Sheet for  
additional health and safety information.**