



SUPER KOTE 5000®

ACRYLIC LATEX FLAT

28 LINE

Features

- Premium commercial acrylic latex designed for the professional painter
- No spatter and fast-dry formula provide fast production
- Professional finish withstands washing
- Soap and water cleanup

Recommended For

Interior drywall, plaster, wood, metal, masonry and stucco in commercial, institutional and residential applications. It may be washed repeatedly without film damage. Perfect for offices, bedrooms, living rooms or wherever a flat sheen is desirable.

General Description

Super Kote 5000® is designed for commercial projects—when getting the job done quickly is a priority. With low spatter and easy application, this premium-quality, vinyl-acrylic formula delivers dependable quality and productivity.

Limitations

- Apply only when surface and air temperatures are above 50 °F (10 °C).

Product Information

| | | |
|---|--|--|
| Colors — Standard: White (1), Black (2), Brite White (6) | Technical Data◇ | White |
| — Tint Bases: Pastel Base (32), Tint Base (33), Deep Base (34), Accent Base (36) Tint with Universal colorants only | Vehicle Type Pigment Type Volume Solids Coverage per Gallon at Recommended Film Thickness Recommended Film Thickness | Vinyl Acrylic Titanium Dioxide 32.1 ± 1.0% 300 – 400 Sq. Ft. (27.8 – 37.2 Sq. m.) – Wet 4.0 to 5.3 mils – Dry 1.3 to 1.7 mils |
| — Special Colors: Contact your dealer. | Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint. Dry Time @ 77 °F (25 °C) @ 50% RH – Tack Free 30 Minutes – To Recoat 4 Hours | |
| Certifications & Qualifications: VOC compliant in all regulated areas The products supported by this data sheet contain a maximum of 50 grams per liter VOC/VOS (0.42 lbs./gal.) excluding water & exempt solvents. This product meets the qualifications for LEED (Leadership in Energy and Environmental Design) projects as a flat coating. Master Painters Institute MPI # 53 | High humidity and cool temperatures will result in longer dry, recoat and service times. Dries By Viscosity Flash Point Gloss / Sheen Surface Temperature at Application Thin With Clean Up Thinner Weight Per Gallon Storage Temperature | Coalescence 105 – 110 KU 200°F or greater (TT-P-141, Method 4293) Flat (1 - 2 @ 85°) – Min. 50 °F (10 °C) – Max. 90 °F (32 °C) Clean Water Warm, Soapy Water 11.6 lbs. (5.2 kg) – Min. 40 °F (4.4 °C) – Max. 95 °F (35 °C) |
| Technical Assistance: Available through your local authorized independent dealer. For the location of the dealer nearest you, call 1-866-708-9180, or visit www.coronadopaint.com | Volatile Organic Compounds (VOC) 50 Grams/Liter 0.42 Lbs./Gallon | |

◇ Reported values are for White. Contact dealer for values of other bases or colors.

Super Kote 5000® Acrylic Latex Flat 28 Line

Surface Preparation

Surfaces to be painted must be clean, dry, and free of dirt, dust, grease, oil, soap, wax, scaling paint, water soluble materials and mildew. Remove any peeling or scaling paint, and sand these areas to feather edges smooth with adjacent surfaces. Glossy areas should be dulled. Drywall surfaces must be free of sanding dust. Spot prime before and after filling nail holes, cracks, and other surface imperfections.

New plaster or masonry surfaces must be allowed to cure (30 days) before applying base coat. Cured plaster should be hard, have a slight sheen and maximum pH of 10; soft, porous or powdery plaster indicates improper cure.

Primers: New surfaces should be fully primed. Previously painted surfaces should be primed or spot primed as necessary. There are a number of specialty primers available in our family of brands that can be used on difficult substrates such as bleeding woods, hard glossy surfaces, or other substrates where paint adhesion or stain blocking is a problem. Your dealer can recommend the right problem solving primer necessary to meet your needs.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Informational Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Application

Stir thoroughly. Apply by brush (synthetic filament), roller or spray. Length of roller nap depends upon the texture of the surface. Thinning is not usually required for brush or roller application. Apply a full, even coat. Do not apply directly over chalky surfaces or bleeding stains. Apply only when surface and air temperatures are above 50°F (10°C).

Spray, Airless: Fluid Pressure—1,500 to 2,000 PSI;
Tip—.017 - .021 Orifice

Clean Up

Clean up with warm, soapy water.

USE COMPLETELY OR DISPOSE OF PROPERLY. Dry, empty containers may be recycled in a can recycling program. **Local disposal requirements vary; consult your sanitation department or state-designated environmental agency on disposal options.**

Environmental Health & Safety Information

Use only with adequate ventilation. Do not breathe spray mist or sanding dust. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to dust and spray mist by wearing a NIOSH approved respirator during application, sanding and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling.



WARNING Cancer and Reproductive Harm—
www.P65warnings.ca.gov

FIRST AID: In case of eye contact, flush immediately with plenty of water for at least 15 minutes; for skin, wash thoroughly with soap and water. If symptoms persist, seek medical attention. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

IN CASE OF SPILL – Absorb with inert material and dispose of as specified under "Clean Up".

**KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING**

**Refer to Safety Data Sheet for
additional health and safety information.**