



# CRYLI COTE®

## 100% ACRYLIC EXTERIOR PAINT

### SEMI-GLOSS 2 LINE

#### Features

- 100% Acrylic Exterior Paint
- Excellent Durability
- Superb Color and Gloss Retention
- Fast Dry
- Blister Resistant

#### General Description

Cryli Cote® 100% Acrylic Semi-Gloss Exterior Paint will provide a durable and protective finish on properly primed and prepared exterior surfaces. This semi-gloss acrylic finish provides outstanding gloss and color retention. Contains an agent which inhibits growth of mildew on the surface of the paint film.

#### Recommended For

On exterior fascia, siding, shutters and railings; an ideal semi-gloss sheen for accenting trim work.

#### Limitations

- Avoid painting over hot surfaces or in direct sunlight. Apply when surface temperature is above 50 °F (10 °C)
- Not for interior use.

#### Product Information

Colors — Standard:	Technical Data◇	White
White (1)	Vehicle Type	100% Acrylic
<b>— Tint Bases:</b>	Pigment Type	Titanium Dioxide
Tint Base (33), Deep Base (34), Accent Base (36)	Volume Solids	33.8 ± 1.0%
Tint with Universal colorants only	Coverage per Gallon at Recommended Film Thickness	325 - 425 Sq. Ft.
<b>— Special Colors:</b>	Recommended Film Thickness	
Contact your dealer.	– Wet	3.8 to 4.9 mils
<b>Certification &amp; Qualifications :</b>	– Dry	1.3 to 1.7 mils
The products supported by this data sheet contain a maximum of 100 grams per liter VOC/VOS (.83 lbs/gal.) excluding water and exempt solvents.	Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint.	
This product is compliant under the Ozone Transport Commission regulations as a Non-Flat Coating.	Dry Time @ 77 °F (25 °C) @ 50% RH	– Tack Free: 1 Hour – To Recoat: 4 Hours
Meets the performance specifications of Mil-P-28578	High humidity and cool temperatures will result in longer dry, recoat and service times.	
<b>Technical Assistance:</b>	Dries By	Coalescence
Available through your local authorized independent dealer. For the location of the dealer nearest you, call 1-866-708-9180, or visit <a href="http://www.coronadopaint.com">www.coronadopaint.com</a>	Viscosity	95 – 100 KU
	Flash Point	N/A
	Gloss / Sheen	Semi-Gloss (45 - 55 Units @ 60°)
	Surface Temperature at Application	– Min.: 50 °F – Max.: 90 °F
	Thin With	Clean Water
	Clean Up Thinner	Warm Soapy Water
	Weight Per Gallon	10.5 lbs
	Storage Temperature	– Min.: 40 °F – Max.: 90 °F
	<b>Volatile Organic Compounds (VOC)</b>	
	97 Grams/Liter	.81 Lbs./Gallon

◇ Reported values are for White. Contact dealer for values of other bases or colors.

## Cryli Cote® 100% Acrylic Exterior Paint Semi-Gloss 2 Line

### Surface Preparation

Surfaces must be clean, dry and free of grease, wax, and mildew. Remove any chalk and loose or scaling paint. If previously coated with cement-base waterproofing paints, clean by sandblasting. Glossy surfaces must be dulled. Un-weathered areas such as eaves, ceilings, and overhangs should be washed with a detergent solution and/or rinsed with a strong stream of water from a garden hose to remove contaminants that can interfere with proper adhesion. Stains from mildew must be removed by cleaning with an anti-mildew wash prior to coating the surface. **Caution:** Refer to the anti-mildew wash technical data and material safety data sheet for instructions on its proper use and handling. For metal surfaces, remove rust. Wipe down with paint thinner to remove surface oils.

All new masonry surfaces must be power washed or brushed thoroughly with stiff fiber bristles to remove loose particles. New masonry substrates must be allowed to cure for 30 days before priming or painting.

**Primers:** New surfaces should be fully primed. Previously painted surfaces should be primed or spot primed as necessary. There are a number of specialty primers available in our family of brands that can be used on difficult substrates such as bleeding woods, hard glossy surfaces, or other substrates where paint adhesion or stain blocking is a problem. Your dealer can recommend the right problem solving primer necessary to meet your needs.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Informational Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**WARRANTY:** Manufacturer warrants that this product when used in accordance with the label instructions will not: 1. blister from properly prepared and primed surfaces, 2. peel from properly prepared and primed surfaces, and 3. wear down or weather to expose the previously painted surface. This warranty shall be effective for 20 years and is made to the original residential consumer paint purchaser. This warranty is non-transferable. If this product fails to perform as explained above when used according to label instructions within the warranty period, Manufacturer will, upon presentation of proof of purchase (original sales receipt), provide an equivalent or comparable product at no charge. Since we have no control over surface preparation or application, THIS LIMITED WARRANTY DOES NOT INCLUDE THE COST OF LABOR FOR APPLICATION OF PAINT. MANUFACTURER SHALL IN NO EVENT BE LIABLE FOR INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. SOME STATES DO NOT ALLOW THE EXCLUSION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE LIMITATIONS OR EXCLUSIONS CONTAINED IN THE ABOVE WARRANTY MAY NOT APPLY TO YOU. This warranty gives you specific legal rights; you may also have other rights which vary state to state.

### Application

Stir product with a circular, lifting motion before you begin to paint. 100% Acrylic Exterior Paint may be applied by brush, spray, pad or roller, at a rate of application not to exceed 425 square feet per gallon. Surface texture and porosity will affect actual yield. For best brush application results, use a quality synthetic filament brush. For roller application, use a 3/8" or 1/2" nap cover for smooth surfaces, a 3/4" nap cover for semirough surfaces and a 1" or 1 1/2" nap cover for rough surfaces. For spray application, thin with clean water, up to 20% reduction if necessary. Do not apply when surface or air temperatures are below 50° F. Do not apply to hot surfaces or in direct sunlight. Do not apply if rain is threatening.

### Clean Up

Clean up with warm, soapy water followed by a clean water rinse.

USE COMPLETELY OR DISPOSE OF PROPERLY. Dry empty containers may be recycled in a can recycling program. **Local disposal requirements vary; consult your sanitation department or state-designated environmental agency on disposal options.**

### Environmental Health & Safety Information

**Use only with adequate ventilation.** Do not breathe spray mist or sanding dust. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to dust and spray mist by wearing a NIOSH approved respirator during application, sanding and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling.



**WARNING** Cancer and Reproductive Harm—  
[www.P65warnings.ca.gov](http://www.P65warnings.ca.gov)

**FIRST AID:** In case of eye contact, flush immediately with plenty of water for at least 15 minutes; for skin, wash thoroughly with soap and water. If symptoms persist, seek medical attention. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

**IN CASE OF SPILL** – Absorb with inert material and dispose of as specified under "Cleanup".

**KEEP OUT OF REACH OF CHILDREN  
PROTECT FROM FREEZING**

**Refer to Safety Data Sheet for  
additional health and safety information.**