ESTº 1957
CORONADO®
PREMIUM PAINTS

Cryli Cote®

100% Acrylic Exterior Paint
Semi-Gloss N2

General Description

A 100% Acrylic Exterior Paint which provides lasting service over new or previously painted surfaces in good condition. This paint will provide a durable and protective finish on any properly prepared and primed exterior surface

- Excellent Durability
- Fast Dry
- Blister Resistant

Usage

For exterior wood, masonry, hardboard and metal in commercial, institutional and residential applications. Use on exterior siding, foundations, fascia, shutters or retaining walls. Designed as a self-priming system on non-bleeding woods, smooth poured or pre-cast masonry and clean, properly prepared galvanized metal surfaces.

Colors	Tintable White (1)
Bases	Tint Base (33), Accent Base (36)
Colorant System	Gennex®

Technical Data

Vehicle		100% Acrylic
Pigment		Titanium Dioxide
Volume Solids		36 ± 2%
Spread Rate Per Gallon		350 – 450 Sq. Ft.
Recommended Film Thickness	Wet:	3.6 – 4.6 mils
	Dry:	1.3 – 1.6 mils

Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint.

Dry Time @ 77 °F (25 °C) @ 50% RH	Tack Free:	1 Hour
	To Recoat:	4 Hours

High humidity and cool temperatures will result in longer dry, recoat and service times.

Surface Temperature During Application	Min:	40 °F
	Max:	100 °F
Viscosity		96 ± 4 KU
Flash Point		None
Sheen / Gloss		45 – 55 @ 60°
Clean Up		Warm, soapy water
Thinner		Clean water
Weight Per Gallon		10.5 lbs.
Storage Temperature	Min:	40 °F
	Max:	90 °F
VOC		< 50 g/L

Surface Preparation

Surfaces must be clean, dry and free of oil, grease, wax, rust, mildew, chalk and loose or scaling paint. Cement based water proofing paints should be removed. Glossy surfaces must be dulled. Un-weathered areas such as eaves, porch ceilings, overhangs and protected wall areas should be washed with an appropriate cleaner and rinsed with a strong stream of water from a garden hose or power washer to remove contaminants that can interfere with proper adhesion. Patch holes, cracks and other surface imperfections. New masonry surfaces must be allowed to cure (30 days) before applying base coat.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Informational Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Primer Systems

New and previously painted surfaces should be primed, or spot primed as necessary. There are a number of specialty primers that can be used on difficult substrates such as hard glossy surfaces, or other substrates where paint adhesion or stain blocking is a problem. Your dealer can recommend the right problem-solving primer necessary to meet your needs.

Wood/Engineered Wood Products:
Self-priming

Bleeding Type Woods, (Redwood and Cedar):
Use an alkyd or stain blocking acrylic primer

Masonry; Rough or Pitted Masonry:
Use a latex block filler

Masonry; Smooth Poured or Pre-cast Concrete:
Self-priming. New masonry substrates must be allowed to fully cure for 30 days before painting.

Ferrous Metal (Steel & Iron):
Use an acrylic or alkyd rust preventative metal primer

Non-Ferrous Metal (Galvanized & Aluminum):
Self-priming. All new metal surfaces must be thoroughly cleaned with an oil & grease emulsifier to remove contaminants. New shiny non-ferrous metal surfaces that will be subject to abrasion should be dulled with very fine sandpaper or a synthetic steel wool pad to promote adhesion.

Compliance & Certifications

FEDERAL	✓
OTC	✓
OTC II	✓
CARB	✓
CARB07	✓
CARB19	✓
UTAH	✓
AZMC	✓
SCAQMD	✓
MPI	11

WARRANTY: Manufacturer warrants that this product when used in accordance with the label instructions will not: 1. blister from properly prepared and primed surfaces, 2. peel from properly prepared and primed surfaces, and 3. wear down or weather to expose the previously painted surface. This warranty shall be effective for 20 years and is made to the original residential consumer paint purchaser. This warranty is non-transferable. If this product fails to perform as explained above when used according to label instructions within the warranty period, Manufacturer will, upon presentation of proof of purchase (original sales receipt), provide an equivalent or comparable product at no charge. Since we have no control over surface preparation or application, THIS LIMITED WARRANTY DOES NOT INCLUDE THE COST OF LABOR FOR APPLICATION OF PAINT. MANUFACTURER SHALL IN NO EVENT BE LIABLE FOR INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. SOME STATES DO NOT ALLOW THE EXCLUSION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE LIMITATIONS OR EXCLUSIONS CONTAINED IN THE ABOVE WARRANTY MAY NOT APPLY TO YOU. This warranty gives you specific legal rights; you may also have other rights which vary state to state.

Limitations

- Do not apply when air and surface temperatures are below 40 °F (4.4 °C).
- Not recommended for walking surfaces.

Technical Assistance

Available through your local authorized independent retailer.

call 1-866-708-9180
visit www.coronadopaint.com

Application

Stir product with a circular, lifting motion before you begin to paint. Cryli Cote® may be applied by brush, spray or roller, at a rate of application not to exceed 450 square feet per gallon. Surface texture and porosity will affect actual yield. For best brush application results, use a quality synthetic filament brush. For roller application, use a 3/8" or 1/2" nap cover for smooth surfaces, a 3/4" nap cover for semi-rough surfaces and a 1" or 1 ½" nap cover for rough surfaces. For spray application, thin with clean water, up to 20% reduction if necessary. Do not apply when surface or air temperatures are below 40 °F. Do not apply to hot surfaces or in direct sunlight. Do not apply if rain is threatening.

Spray, Airless:
Pressure / 1,500 – 2,500 PSI
Tip / 0.013 – 0.017

Clean Up

Wash brushes, rollers, and other painting tools in warm soapy water immediately after use. Spray equipment should be given a final rinse with mineral spirits to prevent rusting.

USE COMPLETELY OR DISPOSE OF PROPERLY. Dry, empty containers may be recycled in a can recycling program. Local disposal requirements vary; consult your sanitation department or state-designated environmental agency on disposal options.

Environmental Health & Safety Information

Use only with adequate ventilation. Do not breathe vapors, spray mist or sanding dust. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to dust and spray mist by wearing a NIOSH approved respirator during application, sanding and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling.

WARNING Cancer and Reproductive Harm– www.P65Warnings.ca.gov
Refer to the product label & Safety Data Sheet for product specific information.

FIRST AID: In case of eye contact, flush immediately with plenty of water for at least 15 minutes; for skin, wash thoroughly with soap and water. If symptoms persist, seek medical attention. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

IN CASE OF SPILL – Absorb with inert material and dispose of as specified under "Clean Up".

KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING

Refer to Safety Data Sheet for additional health and safety information.

Manufactured by Benjamin Moore & Co., 101 Paragon Drive, Montvale, NJ 07645 Tel: 866-708-9180 www.coronadopaint.com N2 US 061026
©2021, 2026 Benjamin Moore & Co. All trademarks belong to their respective owners. All rights reserved