



SUPER KOTE[®] 3000

ACRYLIC LATEX FLAT

301 LINE

Features

- Acrylic Latex Flat Paint
- Fast Drying
- Suitable for use in USDA inspected facilities
- Excellent Touch Up
- Hides Imperfections

Recommended For

Professional grade paint for commercial and residential use on drywall, plaster, wood and masonry. Provides excellent touch up and hides imperfections in new construction and repaint work.

General Description

Super Kote[®] 3000 Acrylic Latex Flat is designed to provide good dry hide appearance when applied to properly prepared interior surfaces. It resists spattering and exhibits excellent touch-up characteristics. The flat sheen hides surface imperfections. This product is an excellent choice for new construction as well as remedial work.

Limitations

- Apply only when surface and air temperatures are above 50 °F (10 °C).
- Not for use in high abuse areas.

Product Information

Colors — Standard:	Technical Data [◇]	White
White (1)	Vehicle Type	Acrylic
— Tint Bases:	Pigment Type	Titanium Dioxide
Pastel Base (32), Tint Base (33), Deep Base (34)	Volume Solids	29.1 ± 1.0%
Tint with Universal colorants only	Coverage per Gallon at Recommended Film Thickness	350 – 450 Sq. Ft.
— Special Colors:	Recommended Film Thickness	– Wet 3.6 to 4.6 mils – Dry 1.1 to 1.3 mils
Contact your dealer.	Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint.	
Certifications & Qualifications:	Dry Time @ 77 °F (25 °C) @ 50% RH	– Tack Free 1 Hour – To Recoat 4 Hours
VOC compliant in all regulated areas	High humidity and cool temperatures will result in longer dry, recoat and service times.	
The products supported by this data sheet contain a maximum of 50 grams per liter VOC/VOS (0.41 lbs/gal.) excluding water & exempt solvents.	Dries By	Coalescence
This product meets the qualifications for LEED (Leadership in Energy and Environmental Design) projects as a flat coating.	Viscosity	94 - 99 KU
Technical Assistance:	Flash Point	200 °F or greater (TT-P-141, Method 4293)
Available through your local authorized independent dealer. For the location of the dealer nearest you, call 1-866-708-9180, or visit www.coronadopaint.com	Gloss / Sheen	Flat (3 – 4.5 @ 85°)
	Surface Temperature at Application	– Min. 50 °F – Max. 90 °F
	Thin With	Clean Water
	Clean Up Thinner	Warm Soapy Water
	Weight Per Gallon	10.18 lbs.
	Storage Temperature	– Min. 40 °F – Max. 95 °F
	Volatile Organic Compounds (VOC)	
	42 Grams/Liter	0.35 Lbs./Gallon

[◇] Reported values are for White. Contact dealer for values of other bases or colors.

Super Kote® 3000 Acrylic Latex Flat 301 Line

Surface Preparation

Surfaces to be painted must be clean, dry, and free of dirt, dust, grease, oil, soap, wax, peeling or flaking paint, water soluble materials and mildew. Remove any peeling or flaking paint, and sand these areas to feather edges smooth with adjacent surfaces. Glossy areas should be dulled. Drywall surfaces must be free of sanding dust. Spot prime before and after filling nail holes, cracks, and other surface imperfections.

New plaster or masonry surfaces must be allowed to cure (30 days) before applying base coat. Cured plaster should be hard, have a slight sheen and maximum pH of 10; soft, porous or powdery plaster indicates improper cure.

Primers: New surfaces should be fully primed. Previously painted surfaces should be primed or spot primed as necessary. There are a number of specialty primers available in our family of brands that can be used on difficult substrates such as bleeding woods, hard glossy surfaces, or other substrates where paint adhesion or stain blocking is a problem. Your dealer can recommend the right problem solving primer necessary to meet your needs.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Informational Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Application

Stir product thoroughly with a circular, lifting motion ensuring even mixing throughout.

Roller – 3/8" to 1 ¼ " nap, depending on surface texture

Brush – Nylon or polyester filament

Spray, Airless – Fluid Pressure—1,500 to 2,000 PSI; Tip—.017 - .021 Orifice.

Clean Up

Clean up with warm, soapy water.

USE COMPLETELY OR DISPOSE OF PROPERLY. Dry empty containers may be recycled in a can recycling program. **Local disposal requirements vary; consult your sanitation department or state-designated environmental agency on disposal options.**

Environmental Health & Safety Information

Use only with adequate ventilation. Do not breathe spray mist or sanding dust. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to dust and spray mist by wearing a NIOSH approved respirator during application, sanding and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling.



WARNING Cancer and Reproductive Harm—
www.P65warnings.ca.gov

FIRST AID: In case of eye contact, flush immediately with plenty of water for at least 15 minutes; for skin, wash thoroughly with soap and water. If symptoms persist, seek medical attention. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

IN CASE OF SPILL – Absorb with inert material and dispose of as specified under "CleanUp".

**KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING**

**Refer to Safety Data Sheet for
additional health and safety information.**