



SUPER KOTE® 3000

ACRYLIC LATEX EGGSHELL

302 LINE

Features

- Acrylic Latex Eggshell Paint
- Suitable for use in USDA inspected facilities
- Washable
- Low Sheen
- Fast Drying

Recommended For

Professional grade paint for commercial and residential use on drywall, plaster, wood, metal and masonry. Provides excellent touch up and hides imperfections in new construction and repaint work.

General Description

Super Kote® 3000 Acrylic Latex Eggshell is designed particularly for the professional contractor. The formulation provides that necessary balance between performance and value. Super Kote® 3000 Acrylic Latex Eggshell demonstrates good hide and will withstand repeated washing without damaging the film. May be used for new work or re-do, commercial or residential interior applications.

Limitations

- Apply only when surface and air temperatures are above 50 °F (10 °C).

Product Information

Colors — Standard: White (1)	Technical Data \diamond White														
— Tint Bases: Pastel Base (32), Tint Base (33) Tint with Universal colorants only	<table border="1"> <tr><td>Vehicle Type</td><td>Acrylic</td></tr> <tr><td>Pigment Type</td><td>Titanium Dioxide</td></tr> <tr><td>Volume Solids</td><td>30.2 ± 1.0%</td></tr> <tr><td>Coverage per Gallon at Recommended Film Thickness</td><td>300 – 400 Sq. Ft.</td></tr> <tr><td>Recommended Film Thickness</td><td>– Wet 4.0 to 5.3 mils – Dry 1.2 to 1.6 mils</td></tr> </table>	Vehicle Type	Acrylic	Pigment Type	Titanium Dioxide	Volume Solids	30.2 ± 1.0%	Coverage per Gallon at Recommended Film Thickness	300 – 400 Sq. Ft.	Recommended Film Thickness	– Wet 4.0 to 5.3 mils – Dry 1.2 to 1.6 mils				
Vehicle Type	Acrylic														
Pigment Type	Titanium Dioxide														
Volume Solids	30.2 ± 1.0%														
Coverage per Gallon at Recommended Film Thickness	300 – 400 Sq. Ft.														
Recommended Film Thickness	– Wet 4.0 to 5.3 mils – Dry 1.2 to 1.6 mils														
— Special Colors: Contact your dealer.	Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint.														
Certifications & Qualifications: VOC compliant in all regulated areas The products supported by this data sheet contain a maximum of 50 grams per liter VOC/VOS (0.41 lbs/gal.) excluding water & exempt solvents. This product meets the qualifications for LEED (Leadership in Energy and Environmental Design) projects as a non-flat coating.	<table border="1"> <tr><td>Dry Time @ 77 °F (25 °C) @ 50% RH</td><td>– Tack Free 2 Hours – To Recoat 4 Hours</td></tr> <tr><td colspan="2">High humidity and cool temperatures will result in longer dry, recoat and service times.</td></tr> <tr><td>Dries By</td><td>Evaporation</td></tr> <tr><td>Viscosity</td><td>92 – 97 KU</td></tr> <tr><td>Flash Point</td><td>N/A</td></tr> <tr><td>Gloss / Sheen</td><td>Eggshell (15 - 20 @ 85°)</td></tr> </table>	Dry Time @ 77 °F (25 °C) @ 50% RH	– Tack Free 2 Hours – To Recoat 4 Hours	High humidity and cool temperatures will result in longer dry, recoat and service times.		Dries By	Evaporation	Viscosity	92 – 97 KU	Flash Point	N/A	Gloss / Sheen	Eggshell (15 - 20 @ 85°)		
Dry Time @ 77 °F (25 °C) @ 50% RH	– Tack Free 2 Hours – To Recoat 4 Hours														
High humidity and cool temperatures will result in longer dry, recoat and service times.															
Dries By	Evaporation														
Viscosity	92 – 97 KU														
Flash Point	N/A														
Gloss / Sheen	Eggshell (15 - 20 @ 85°)														
Technical Assistance: Available through your local authorized independent dealer. For the location of the dealer nearest you, call 1-866-708-9180, or visit www.coronadopaint.com	<table border="1"> <tr><td>Surface Temperature at Application</td><td>– Min. 50 °F – Max. 90 °F</td></tr> <tr><td>Thin With</td><td>Clean Water</td></tr> <tr><td>Clean Up Thinner</td><td>Warm Soapy Water</td></tr> <tr><td>Weight Per Gallon</td><td>10.3 lbs.</td></tr> <tr><td>Storage Temperature</td><td>– Min. 40 °F – Max. 95 °F</td></tr> <tr><td colspan="2" style="text-align: center;">Volatile Organic Compounds (VOC)</td></tr> <tr><td colspan="2" style="text-align: center;">43.3 Grams/Liter 0.36 Lbs./Gallon</td></tr> </table>	Surface Temperature at Application	– Min. 50 °F – Max. 90 °F	Thin With	Clean Water	Clean Up Thinner	Warm Soapy Water	Weight Per Gallon	10.3 lbs.	Storage Temperature	– Min. 40 °F – Max. 95 °F	Volatile Organic Compounds (VOC)		43.3 Grams/Liter 0.36 Lbs./Gallon	
Surface Temperature at Application	– Min. 50 °F – Max. 90 °F														
Thin With	Clean Water														
Clean Up Thinner	Warm Soapy Water														
Weight Per Gallon	10.3 lbs.														
Storage Temperature	– Min. 40 °F – Max. 95 °F														
Volatile Organic Compounds (VOC)															
43.3 Grams/Liter 0.36 Lbs./Gallon															

\diamond Reported values are for White, Contact dealer for values of other bases or colors.

Surface Preparation

Surfaces to be painted must be clean, dry, and free of dirt, dust, grease, oil, soap, wax, scaling paint, water soluble materials and mildew. Remove any peeling or scaling paint, and sand these areas to feather edges smooth with adjacent surfaces. Glossy areas should be dulled. Drywall surfaces must be free of sanding dust. Spot prime before and after filling nail holes, cracks, and other surface imperfections.

New plaster or masonry surfaces must be allowed to cure (30 days) before applying base coat. Cured plaster should be hard, have a slight sheen and maximum pH of 10; soft, porous or powdery plaster indicates improper cure. Remove any powder or loose particles.

Primers: New surfaces should be fully primed. Previously painted surfaces should be primed or spot primed as necessary. There are a number of specialty primers available in our family of brands that can be used on difficult substrates such as bleeding woods, hard glossy surfaces, or other substrates where paint adhesion or stain blocking is a problem. Your dealer can recommend the right problem solving primer necessary to meet your needs.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Informational Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Application

Stir product with a circular, lifting motion before you begin to paint. Product may be applied by brush, roller, pad or spray techniques, at a rate of application not to exceed 400 square feet per gallon. Surface texture and porosity will affect actual yield. For best brush application results, use a quality synthetic filament brush. For roller application use a ¼" or 3/8" nap cover for smooth surfaces, a ½" nap cover for semi-rough surfaces, and a ¾" nap cover for rough surfaces. May be reduced with clean water up to 15% for spray application.

Spray, Airless - Fluid Pressure — 1,500 to 2,000 PSI
Tip — .017 - .019 Orifice

Clean up

Clean up with warm, soapy water.

USE COMPLETELY OR DISPOSE OF PROPERLY. Dry empty containers may be recycled in a can recycling program. **Local disposal requirements vary; consult your sanitation department or state-designated environmental agency on disposal options.**

Environmental Health & Safety Information

Use only with adequate ventilation. Do not breathe spray mist or sanding dust. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to dust and spray mist by wearing a NIOSH approved respirator during application, sanding and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling.



WARNING Cancer and Reproductive Harm—
www.P65warnings.ca.gov

FIRST AID: In case of eye contact, flush immediately with plenty of water for at least 15 minutes; for skin, wash thoroughly with soap and water. If symptoms persist, seek medical attention. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

IN CASE OF SPILL – Absorb with inert material and dispose of as specified under "CleanUp".

**KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING**

**Refer to Safety Data Sheet for
additional health and safety information.**