



SUPER KOTE 5000

ACRYLIC LATEX ENAMEL EGGSHELL 30 LINE

Features

- Premium commercial acrylic latex designed for the professional painter
- No spatter and fast-dry formula provide fast production
- Professional finish withstands washing
- Soap and water cleanup

Recommended For

Interior drywall, plaster, wood, metal, masonry and stucco in commercial, institutional and residential applications. It may be washed repeatedly without film damage. Perfect for bedrooms, hallways or wherever a low-sheen enamel is desired.

General Description

Super Kote 5000 Acrylic Latex Eggshell Enamel is designed to be applied with equal success by contractors or do-it-yourselfers. It applies easily without spattering, covers most surfaces in one coat and may be washed repeatedly without film damage. Perfect for bedrooms, hallways or wherever a low sheen is desirable.

Limitations

- Apply only when surface and air temperatures are above 10 °C (50 °F).

Product Information

Colours — Standard:	Technical Data [◇]	White
White (1)	Vehicle Type	Vinyl Acrylic
— Tint Bases:	Pigment Type	Titanium Dioxide
Pastel Base (32), Tint Base (33), Deep Base (34), Accent Base (36)	Volume Solids	32.0 ± 1.0%
Tint with Universal colorants only	Coverage per 3.75 L at Recommended Film Thickness	27.9 – 37.2 sq. m. (300 – 400 sq. ft.)
— Special Colours:	Recommended Film Thickness	4.0 to 5.3 mils 1.3 to 1.7 mils
Contact your dealer.	Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint.	
Certifications & Qualifications:	Dry Time @ 25°C (77°F) @ 50% RH	– Tack Free 30 Minutes – To Recoat 4 Hours
VOC compliant in Canada	High humidity and cool temperatures will result in longer dry, recoat and service times.	
The products supported by this data sheet contain a maximum of 50 grams per liter VOC/VOS (0.42 lbs/gal.) excluding water & exempt solvents.	Dries By	Coalescence
This product meets the qualifications for LEED (Leadership in Energy and Environmental Design) projects as a non-flat coating.	Viscosity	95 – 100 KU
This product has been approved by CFIA (Canadian Food Inspection Agency) for use in Food Processing Facilities.	Flash Point	93.3 °C (200 °F) or greater (TT-P-141, Method 4293)
This product is currently approved for use under MPI # 44	Gloss / Sheen	Eggshell (15 - 20 @ 85°)
Technical Assistance:	Surface Temperature at Application	– Min. 10 °C (50 °F) – Max. 32 °C (90 °F)
Available through your local authorized independent dealer. For the location of the dealer nearest you, call 1-800-361-5898 or visit www.coronadopaint.ca	Thin With	Clean Water
	Clean Up Thinner	Warm, Soapy Water
	Weight Per 3.75 L	5.0 kg (11.0 lbs).
	Storage Temperature	– Min. 4.4 °C (40 °F) – Max. 35 °C (95 °F)
	Volatile Organic Compounds (VOC)	
	50 Grams/Liter	

[◇] Reported values are for White. Contact dealer for values of other bases or colors.

Super Kote 5000 Acrylic Latex Enamel Eggshell 30 Line

Surface Preparation

Surfaces to be painted must be clean, dry, and free of dirt, dust, grease, oil, soap, wax, scaling paint, water soluble materials and mildew. Remove any peeling or scaling paint, and sand these areas to feather edges smooth with adjacent surfaces. Glossy areas should be dulled. Drywall surfaces must be free of sanding dust. Spot prime before and after filling nail holes, cracks, and other surface imperfections.

New plaster or masonry surfaces must be allowed to cure (30 days) before applying base coat. Cured plaster should be hard, have a slight sheen and maximum pH of 10; soft, porous or powdery plaster indicates improper cure.

Primers: New surfaces should be fully primed. Previously painted surfaces should be primed or spot primed as necessary. There are a number of specialty primers available in our family of brands that can be used on difficult substrates such as bleeding woods, hard glossy surfaces, or other substrates where paint adhesion or stain blocking is a problem. Your dealer can recommend the right primer solving primer necessary to meet your needs.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @ <https://www.canada.ca/en/health-canada/services/environmental-workplace-health/environmental-contaminants/lead/lead-information-package-some-commonly-asked-questions-about-lead-human-health.html>

Application

Stir thoroughly. Apply by brush (synthetic filament), roller or spray. Length of roller nap depends upon the texture of the surface. Thinning is not usually required for brush or roller application. Apply a full, even coat. Do not apply directly over chalky surfaces or bleeding stains. Apply only when surface and air temperatures are above 10°C (50°F).

Spray, Airless: Fluid Pressure—1,500 to 2,000 PSI;

Tip—.017 - .019 Orifice

Clean Up

Clean up with warm, soapy water.

Environmental Health & Safety Information

Use only in a well ventilated area. Keep container closed when not in use. In case of spillage, absorb with inert material and dispose of in accordance with local regulations. Wash thoroughly after handling.

**KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING**

**Refer to Safety Data Sheet for
additional health and safety information.**