



SUPER KOTE 5000[®]

INTERIOR ACRYLIC LATEX PRIMER SEALER 40 LINE

Features

- Multipurpose acrylic latex primer/sealer designed for the professional painter
- Fast-dry formula with easy application contribute to quick recoat and production times
- Seals the substrate and is an excellent foundation coat
- Excellent adhesion
- Soap and water cleanup

Recommended For

For priming and sealing interior walls of plaster, drywall and masonry in commercial, institutional and residential properties. Use under latex or alkyd finishes.

General Description

A fast drying Acrylic Latex Primer/Sealer for interior drywall and plaster. The smooth drying film has superior sealing properties and provides an excellent foundation for latex or oil finish coat systems. This workhorse primer/ sealer is perfectly suited for use in residential/commercial properties and is easy to apply.

Limitations

- Apply only when surface temperature is above 50 °F (10 °C)

Product Information

Colors — Standard:		Technical Data [◇]		White
White (11)		Vehicle Type		Vinyl Acrylic
— Tint Bases:		Pigment Type		Titanium Dioxide
N/A		Volume Solids		31.9 ± 1.0%
— Special Colors:		Coverage per Gallon at Recommended Film Thickness		350 - 450 Sq. Ft.
Contact your dealer.		Recommended Film Thickness		3.6 – 4.6 mils 1.1 – 1.5 mils
Certifications & Qualifications: VOC compliant in all regulated areas Qualifies for LEED [®] v4 Credit Qualifies for CHPS low emitting credit (Collaborative for High Performance Schools) CDPH v1 Emission Certified Class A (0-25) over non-combustible surfaces when tested in accordance with ASTM E-84 Master Painters Institute MPI # 50		Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint.		
Technical Assistance: Available through your local authorized independent dealer. For the location of the dealer nearest you, call 1-866-708-9180 or visit www.coronadopaint.com .		Dry Time @ 77 °F (25 °C) @ 50% RH		– Tack Free 30 Minutes – To Recoat 4 Hours
		High humidity and cool temperatures will result in longer dry, recoat and service times.		
		Dries By		Coalescence
		Viscosity		90 – 95 KU
		Flash Point		N/A
		Gloss / Sheen		Flat (3 – 5 @ 60°)
		Surface Temperature at Application		– Min. 50 °F – Max. 90 °F
		Thin With		Clean Water
		Clean Up Thinner		Warm, Soapy Water
		Weight Per Gallon		11.1 lbs.
		Storage Temperature		– Min. 50 °F – Max. 90 °F
		Volatile Organic Compounds (VOC)		
		46 Grams/Liter		0.38 Lbs./Gallon

[◇] Reported values are for White. Contact dealer for values of other bases or colors.

Super Kote 5000® Interior Acrylic Latex Primer Sealer 40 Line

Surface Preparation

Surfaces to be painted must be clean, dry, and free of dirt, dust, grease, oil, soap, wax, flaking paint, water soluble materials and mildew. Remove any peeling or flaking paint, and sand these areas to feather edges smooth with adjacent surfaces. Glossy areas should be dulled. Drywall surfaces must be free of sanding dust. Spot prime before and after filling nail holes, cracks, and other surface imperfections.

New plaster or masonry surfaces must be allowed to cure (30 days) before applying base coat. Cured plaster should be hard, have a slight sheen and maximum pH of 10; soft, porous or powdery plaster indicates improper cure.

Difficult Substrates: Super Kote 5000® primer 40-11 works well on many substrates as a primer/sealer. For difficult substrates where a specialty primer might be needed, Our family of brands offers a variety of specialty primers for use over difficult substrates such as bleeding woods, grease stains, crayon markings, hard glossy surfaces, galvanized metal or other substrates where paint adhesion or stain suppression is a particular problem. Your dealer can recommend the right Insl-x problem-solving primer for your special needs.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Informational Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Application

Stir thoroughly. Apply by brush (synthetic filament), roller or spray. Length of roller nap depends upon the texture of the surface. Thinning is not usually required for brush or roller application. Apply a full, even coat. Do not apply directly over chalky surfaces or bleeding stains. Apply only when surface temperature is above 50 °F (10 °C).

Spray, Airless: Fluid Pressure — 1,500 to 2,000 PSI;
Tip — .015 - .019 Orifice

Clean Up

Clean up with warm, soapy water.

USE COMPLETELY OR DISPOSE OF PROPERLY. Dry empty containers may be recycled in a can recycling program. **Local disposal requirements vary; consult your sanitation department or state-designated environmental agency on disposal options.**

Environmental Health & Safety Information

Use only with adequate ventilation. Do not breathe spray mist or sanding dust. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to dust and spray mist by wearing a NIOSH approved respirator during application, sanding and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling.



WARNING Cancer and Reproductive Harm—
www.P65warnings.ca.gov

FIRST AID: In case of eye contact, flush immediately with plenty of water for at least 15 minutes; for skin, wash thoroughly with soap and water. If symptoms persist, seek medical attention. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

IN CASE OF SPILL – Absorb with inert material and dispose of as specified under “Clean Up”.

**KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING**

**Refer to Safety Data Sheet for
additional health and safety information.**