



FINALTOUCH®

ULTRA TOUCH-UP LATEX WALL PAINT FLAT 62 LINE

Features

- Fast Drying
- Water Clean-Up
- Excellent Touch-Up
- Resists Spattering

General Description

FinalTouch® is formulated to provide perfect touch-up and final finishing for all interior new construction wall surfaces. After spray and back-roll of your final finish coat, FinalTouch® is designed to feather smoothly with a fine nap roller to provide invisible touch-ups.

Recommended For

Interior – Drywall, Plaster, Wood, Metal, Masonry, Cement, Block, Stucco. An ideal flat coating to be used for new construction as well as general maintenance, apartments and the budget minded consumers.

Limitations

- Do not apply directly over chalky surfaces or bleeding stains.
- Apply when temperature is above 50 °F and in humidity less than 85%.
- Not for use in high abuse areas.

Product Information

Colors — Standard: White (1)	Technical Data \diamond White Vehicle Type Vinyl Acrylic Pigment Type Titanium Dioxide Volume Solids 33 ± 1.0% Coverage per Gallon at Recommended Film Thickness 300 — 400 Sq. Ft.
— Tint Bases: Pastel Base (32), Tint Base (33)	Recommended Film Thickness – Wet 4.0 - 5.4 mils – Dry 1.3 - 1.8 mils Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint.
— Special Colors: Contact your dealer.	Dry Time @ 77 °F (25 °C) @ 50% RH – Tack Free 30 Minutes – To Recoat 4 Hours High humidity and cool temperatures will result in longer dry, recoat and service times.
Certifications & Qualifications: VOC compliant in all regulated areas The products supported by this data sheet contain a maximum of 50 grams per liter VOC / VOS (0.42 lbs. /gal.) excluding water & exempt solvents.	Dries By Coalescence Viscosity 108 – 113 KU Flash Point 200 °F or greater (TT-P-141, Method 4293) Gloss / Sheen Flat (0-5 @ 85°)
Technical Assistance: Available through your local authorized independent dealer. For the location of the dealer nearest you, call 1-866-708-9180 or visit www.coronadopaint.com	Surface Temperature at Application – Min. 50 °F – Max. 90 °F Thin With Clean Water Clean Up Thinner Warm Soapy Water Weight Per Gallon 10.9 lbs. Storage Temperature – Min. 45 °F – Max. 95 °F Volatile Organic Compounds (VOC) 46 Grams/Liter 0.38 Lbs./Gallon

\diamond Reported values are for White. Contact dealer for values of other bases or colors.

Surface Preparation

Surface to be painted must be clean and free of dirt, chalk, mildew, wax, grease, rust or loose, flaking paint. Dirt and chalk should be removed by scrubbing with warm soapy water and thoroughly rinsed with clean water. Mildew must be removed by scrubbing with a solution of one part household bleach* and three parts water. Rinse well with clean water and allow it to dry thoroughly before painting. Wax should be removed with a commercial wax stripper or by solvent cleaning. Grease should be cleaned by using an Oil & Grease Emulsifier. Rust must be removed by hand sanding or by conscientious power tool cleaning. Remove loose paint by scraping. Feather sand rough edges to insure a smooth finish coat. Glossy surfaces must be dulled by lightly sanding. Remove sanding dust before paint application. Any exposed substrate should be spot primed with the appropriate primer.

*Follow bleach manufacturer's instructions for safe handling and use of bleach solution.

Primers: New surfaces should be fully primed. Previously painted surfaces should be primed or spot primed as necessary. There are a number of specialty primers available in our family of brands that can be used on difficult substrates such as bleeding woods, hard glossy surfaces, or other substrates where paint adhesion or stain blocking is a problem. Your dealer can recommend the right problem solving primer necessary to meet your needs.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Informational Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Application

Stir product thoroughly with a circular, lifting motion ensuring even mixing throughout.

Roller – 3/8" nap, depending on surface texture

Brush – Nylon or polyester filament

Airless Spray – Tip size and atomization pressure will vary with type of equipment, viscosity and temperature. Normally a tip size of .017 @ 2000-2500 psi will provide the most satisfactory spray pattern. If necessary product may be thinned up to 10% with clean water for spray application.

Best results are more likely obtained by using quality application tools. Do not apply directly over chalky surfaces or bleeding stains. Apply when temperature is above 50 °F and in humidity less than 85%.

Clean Up

Clean up with warm, soapy water followed by a clean water rinse.

USE COMPLETELY OR DISPOSE OF PROPERLY. Dry empty containers may be recycled in a can recycling program. **Local disposal requirements vary; consult your sanitation department or state-designated environmental agency on disposal options.**

Environmental Health & Safety Information

Use only with adequate ventilation. Do not breathe spray mist or sanding dust. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to dust and spray mist by wearing a NIOSH approved respirator during application, sanding and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling.



WARNING Cancer and Reproductive Harm—
www.P65warnings.ca.gov

FIRST AID: In case of eye contact, flush immediately with plenty of water for at least 15 minutes; for skin, wash thoroughly with soap and water. If symptoms persist, seek medical attention. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

IN CASE OF SPILL – Absorb with inert material and dispose of as specified under "Clean up".

**KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING**

**Refer to Safety Data Sheet for
additional health and safety information.**