



SUPER KOTE™ 3000

LATEX ENAMEL EGGSHELL

930 LINE

Features

- Latex Eggshell Paint
- Fast Drying
- Low Sheen
- Suitable for use in USDA inspected facilities
- Low Odor
- Washable

General Description

Super Kote™ 3000 Latex Enamel Eggshell is designed particularly for the professional contractor. The formulation provides that necessary balance between performance and value. Super Kote™ 3000 Latex Enamel Eggshell demonstrates good hide and will withstand repeated washing without damaging the film. May be used for new work or re-do, commercial or residential applications.

Recommended For

Professional grade paint for commercial and residential use on drywall, plaster, wood, metal and masonry. Provides excellent touch up and hides imperfections in new construction and repaint work.

Limitations

- Apply only when surface and air temperatures are above 50°F (10 °C).

Product Information

Colors — Standard: White	Technical Data White Vehicle Type Latex Pigment Type Titanium Dioxide Volume Solids 29.2 ± 1.0%
— Tint Bases: 930-32, Pastel Base 930-33, Tint Base	Coverage per Gallon at Recommended Film Thickness 300 – 400 Sq. Ft. Recommended Film Thickness 4.0 to 5.3 mils – Wet 1.2 to 1.6 mils – Dry
— Special Colors: Contact your dealer.	Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint.
Certification: The products supported by this data sheet contain a maximum of 50 grams per liter VOC/VOS (0.41 lbs/gal.) excluding water & exempt solvents. This product is compliant under the Ozone Transport Commission regulations as a Non-Flat Coating. This product meets the qualifications for LEED (Leadership in Energy and Environmental Design) projects as a non-flat coating.	Dry Time @ 77°F 30 Minutes – Tack Free (25°C) @ 50% RH 4 Hours – To Recoat High humidity and cool temperatures will result in longer dry, recoat and service times. Dries By Evaporation Viscosity 92 – 97 KU Flash Point N/A Gloss / Sheen Eggshell 15 - 20 units@85° Surface Temperature 50°F – Min. at Application 90°F – Max. Thin With Clean Water Clean Up Thinner Warm Soapy Water
Technical Assistance: Available through your local authorized independent dealer. For the location of the dealer nearest you, call 1-800-225-5554 or visit www.coronadopaint.com .	Weight Per Gallon 10.8 lbs. Storage Temperature 40°F – Min. – Max. 95°F Volatiles Organic Compounds (VOC) 29 Grams/Liter 0.24 Lbs./Gallon

◇ Reported values are for White, Contact dealer for values of other bases or colors.

Surface Preparation

Surfaces to be painted must be clean, dry, and free of dirt, dust, grease, oil, soap, wax, scaling paint, water soluble materials and mildew. Remove any peeling or scaling paint, and sand these areas to feather edges smooth with adjacent surfaces. Glossy areas should be dulled. Drywall surfaces must be free of sanding dust. Spot prime before and after filling nail holes, cracks, and other surface imperfections.

New plaster or masonry surfaces must be allowed to cure (30 days) before applying base coat. Cured plaster should be hard, have a slight sheen and maximum pH of 10; soft, porous or powdery plaster indicates improper cure. Remove any powder or loose particles.

Primers: New surfaces should be fully primed. Previously painted surfaces should be primed or spot primed as necessary. There are a number of specialty primers available in our family of brands that can be used on difficult substrates such as bleeding woods, hard glossy surfaces, or other substrates where paint adhesion or stain blocking is a problem. Your dealer can recommend the right problem solving primer necessary to meet your needs.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.**

Application

Stir product with a circular, lifting motion before you begin to paint. Super Kote™ 3000 Latex Eggshell Enamel may be applied by brush, roller, pad or spray techniques, at a rate of application not to exceed 400 square feet per gallon. Surface texture and porosity will affect actual yield. For best brush application results, use a quality synthetic filament brush. For roller application use a ¼" or 3/8" nap cover for smooth surfaces, a ½" nap cover for semi-rough surfaces, and a ¾" nap cover for rough surfaces. May be reduced with clean water up to 15% for spray application.

Clean up

Clean up with warm, soapy water.

USE COMPLETELY OR DISPOSE OF PROPERLY. Dry, empty containers may be recycled in a can recycling program. **Local disposal requirements vary; consult your sanitation department or state-designated environmental agency on disposal options.**

Environmental Health & Safety Information

Use only with adequate ventilation. Do not breathe spray mist or sanding dust. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to dust and spray mist by wearing a NIOSH approved respirator during application, sanding and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling.

WARNING: This product contains a chemical known to the state of California to cause cancer and birth defects, or other reproductive harm.

FIRST AID: In case of eye contact, flush immediately with plenty of water for at least 15 minutes; for skin, wash thoroughly with soap and water. If symptoms persist, seek medical attention. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

IN CASE OF SPILL – Absorb with inert material and dispose of as specified under "Clean Up".

**KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING**

**Refer to Safety Data Sheet for
additional health and safety information.**