



SUPER KOTE 3000

INTERIOR LATEX PRIMER SEALER

LINE 948

Features

- Interior Latex Primer-Sealer
- Fast Drying
- Excellent Sealing
- Water Clean Up

General Description

A high hiding, fast drying Vinyl Acrylic Primer-Sealer for interior dry wall and cured plaster. It is easy to apply and quick drying. It provides an excellent foundation for latex or oil finish coat systems.

Recommended For

For priming and sealing interior walls of plaster, drywall and masonry in commercial, institutional and residential properties. Use under latex or alkyd finishes.

Limitations

- Apply only when surface temperature is above 10 °C (50 °F).

Product Information

Product Information		White	
Colours — Standard: White	Technical Data	Vehicle Type Vinyl Acrylic	
		Pigment Type Titanium Dioxide	
		Volume Solids 32.0 ± 1.0%	
— Tint Bases: N/A		Coverage per 3.79 L at Recommended Film Thickness 41.8 sq. m. (up to 450 sq. ft.)	
		Recommended Film Thickness — Wet 3.6 to 4.6 mils — Dry 1.1 to 1.5 mils	
— Special Colours: Contact your dealer.	Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure colour uniformity and minimize the disposal of excess paint.		
Certifications & Qualifications: The products supported by this data sheet contain a maximum of 100 grams per litre VOC/VOS (0.83 lbs/gal.) excluding water & exempt solvents. This product is compliant as a Primer/Sealer/Undercoater. This product does not meet qualifications for LEED (Leadership in Energy and Environmental Design) projects.	Dry Time @ 25 °C (77 °F) @ 50% RH		— Tack Free 30 Minutes — To Recoat 4 Hours
	High humidity and cool temperatures will result in longer dry, recoat and service times.		
	Dries By		Evaporation
	Viscosity		95 – 102 KU
	Flash Point		N/A
	Gloss / Sheen		Flat
	Surface Temperature at Application		— Min. 10 °C (50 °F) — Max. 32.2 °C (90 °F)
	Thin With		Clean Water
Technical Assistance: Available through your local authorized independent dealer. For the location of the dealer nearest you, call 1-800-361-5898 or visit www.coronadopaint.ca	Clean Up Thinner		Warm, Soapy Water
	Weight Per 3.79 L		5.4 kg (11.8 lbs)
	Storage Temperature		— Min. 4.4 °C (40 °F) — Max. 35 °C (95 °F)
	Volatile Organic Compounds (VOC)		
	47 Grams/Litre	0.18 kg/3.79 L (0.39 Lbs./Gallon)	

◇ Reported values are for White. Contact dealer for values of other bases or colours.

Super Kote 3000 Interior Latex Primer Sealer 948 Line

Surface Preparation

Surfaces to be painted must be clean, dry, and free of dirt, dust, grease, oil, soap, wax, scaling paint, water soluble materials and mildew. Remove any peeling or scaling paint, and sand these areas to feather edges smooth with adjacent surfaces. Glossy areas should be dulled. Drywall surfaces must be free of sanding dust. Spot prime before and after filling nail holes, cracks, and other surface imperfections.

New plaster or masonry surfaces must be allowed to cure (30 days) before applying base coat. Cured plaster should be hard, have a slight sheen and maximum pH of 10; soft, porous or powdery plaster indicates improper cure. Never sand a plaster surface; knife off any protrusions and prime plaster before and after applying patching compound. Poured or pre-cast concrete with a very smooth surface should be etched or abraded to promote adhesion, after removing all form release agents and curing compounds. Remove any powder or loose particles.

Difficult Substrates: Super Kote 3000 primer 948-11 works well on many substrates as a primer/sealer. For difficult substrates where a specialty primer might be needed, Insl-x® offers a variety of specialty primers for use over difficult substrates such as bleeding woods, grease stains, crayon markings, hard glossy surfaces, galvanized metal or other substrates where paint adhesion or stain suppression is a particular problem. Your dealer can recommend the right Insl-x® problem-solving primer for your special needs.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @ <https://www.canada.ca/en/health-canada/services/environmental-workplace-health/environmental-contaminants/lead/lead-information-package-some-commonly-asked-questions-about-lead-human-health.html>

Primer/Finish Systems

New surfaces should be fully primed, and previously painted surfaces may be primed or spot primed as necessary.

Wood and engineered wood products:

Primer: 1 or 2 coats of Super Kote 3000 Interior Latex Primer Sealer (948 Line)

Finish: 1 or 2 coats of the appropriate Coronado® finish

Bleeding Type Woods, (Redwood and Cedar):

Primer: 1 or 2 coats Super Kote 3000 Interior Latex Primer Sealer (948 Line)

Finish: 1 or 2 coats of the appropriate Coronado® finish

Drywall:

Primer: 1 or 2 coats of Super Kote 3000 Interior Latex Primer Sealer (948 Line)

Finish: 1 or 2 coats of the appropriate Coronado® finish

Plaster:

Primer: 1 or 2 coats of Super Kote 3000 Interior Latex Primer Sealer (948 Line)

Finish: 1 or 2 coats of the appropriate Coronado® finish

Masonry; Rough or Pitted Masonry:

Primer: 1 or 2 coats of Super Kote 3000 Interior Latex Primer Sealer (948 Line)

Finish: 1 or 2 coats of the appropriate Coronado® finish

Masonry; Smooth Poured or Pre-cast Concrete:

Primer: 1 or 2 coats of Super Kote 3000 Interior Latex Primer Sealer (948 Line)

Finish: 1 or 2 coats of the appropriate Coronado® finish

Repaint, All Substrates: Prime bare areas with the primer recommended for the substrate above.

Application

Stir product with a circular, lifting motion before beginning to paint. Super Kote 3000 Interior Latex Primer Sealer may be applied by brush, roller, pad or spray, at a rate of application not to exceed 41.8 square metres per 3.79 litres (450 square feet per gallon). Surface texture and porosity will affect actual yield. For best brush results, use a quality synthetic filament brush. For roller application, use a 9.5 mm (3/8") nap cover for smooth surfaces, a 12.7 mm (1/2") nap cover for semi-rough surfaces and a 19.1 mm to 25.4 mm (3/4" to 1") nap cover for rough surfaces. For spray application this Vinyl Acrylic Primer-Sealer may be thinned with clean water.

Clean Up

Clean up with warm, soapy water.

Environmental Health & Safety Information

Use only in a well ventilated area. Keep container closed when not in use. In case of spillage, absorb with inert material and dispose of in accordance with local regulations. Wash thoroughly after handling.

**KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING**

**Refer to Safety Data Sheet for
additional health and safety information.**