



DECORATIVE ALKYD AEROSOL LACQUER AC06

Features

- High gloss sheen
- Dries quickly
- Great for furniture

General Description

Superior interior/exterior decorative lacquer enamel spray at any angle, comfort spray tip. Great for use on wood, metal and furniture. Easy to sand.

Recommended For

Interior furniture, wood, metal, tools, PVC and crafts.

Limitations

- Do not use on Styrofoam, ceramic tiles or marble

Product Information

Product Information		Technical Data	Clear						
Colors — Standard: Black, White and Clear		Vehicle Type	Genuine Lacquer						
— Tint Bases: N/A		Pigment Type	N/A						
— Special Colors: Contact your dealer.		Weight Solids	8.12 ± 1.0%						
Certification & Qualifications : Aerosol Coating Category: Clear Coating Max VOC 67% Max EPA PWR 1.50 Max CA PWMIR 0.85		Coverage in can	Approx. 8 – 9 sq. ft.						
Technical Assistance: Available through your local authorized independent dealer. For the location of the dealer nearest you, call 1-866-708-9180, or visit www.insl-x.com		Recommended Film Thickness	<table border="0"> <tr> <td>– Wet</td> <td>2 to 3 mils</td> </tr> <tr> <td>– Dry</td> <td>1 to 2 mils</td> </tr> </table>	– Wet	2 to 3 mils	– Dry	1 to 2 mils		
– Wet	2 to 3 mils								
– Dry	1 to 2 mils								
		Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint.							
		Dry Time @ 77 °F (25 °C) @ 50% RH	<table border="0"> <tr> <td>– Tack Free</td> <td>30 Minutes</td> </tr> <tr> <td>– To Recoat</td> <td>anytime</td> </tr> <tr> <td>– To Cure</td> <td>1 Days</td> </tr> </table>	– Tack Free	30 Minutes	– To Recoat	anytime	– To Cure	1 Days
– Tack Free	30 Minutes								
– To Recoat	anytime								
– To Cure	1 Days								
		High humidity and cool temperatures will result in longer dry, recoat and service times.							
		Dries By	Evaporation						
		Spray Rate	1.0 grams to 2.0 grams / second						
		Flash Point	-139 °F (-95 °C)						
		Gloss / Sheen	Gloss						
		Surface Temperature at Application	<table border="0"> <tr> <td>– Min.</td> <td>50 °F</td> </tr> <tr> <td>– Max.</td> <td>90 °F</td> </tr> </table>	– Min.	50 °F	– Max.	90 °F		
– Min.	50 °F								
– Max.	90 °F								
		Thin With	N/A						
		Clean Spray Tip with	Mineral Spirits or Toluene						
		Fill ounces	12 oz.						
		Storage Temperature	<table border="0"> <tr> <td>– Min.</td> <td>0 °F</td> </tr> <tr> <td>– Max.</td> <td>120 °F</td> </tr> </table>	– Min.	0 °F	– Max.	120 °F		
– Min.	0 °F								
– Max.	120 °F								
		Volatile Organic Compounds (VOC)							
		MAX 67%							

◇ Reported values are for Clear. Contact dealer for values of other colors.

Decorative Alkyd Aerosol Lacquer AC06

Surface Preparation

Surface to be painted must be clean and free of dirt, chalk, wax, grease, rust or loose, flaking paint. Dirt and chalk should be removed by scrubbing with warm soapy water and thoroughly rinsed with clean water. Wax should be removed with a commercial wax stripper or by solvent cleaning. Grease should be cleaned by using an oil and grease emulsifier or other surface prep degreaser. Rust must be removed by hand sanding vigorously or by conscientious power tool cleaning. Remove loose paint by scraping. Glossy surfaces should be dulled. Feather sand rough edges to insure a smooth finish coat. Remove sanding dust before paint application.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Informational Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Application

Before spraying, shake can for 2 minutes after ball within begins to rattle and occasionally during use. Hold can 10" to 16" away from the surface and apply several thin coats a few minutes apart rather than one heavy coat, slightly overlapping each stroke. Keep can in motion while spraying Recoat within one hour.

Clean Up

USE COMPLETELY OR DISPOSE OF PROPERLY. This product contains organic solvents which may cause adverse effects to the environment if handled improperly. Emptied containers may retain product residue. Follow label warnings even after container is emptied. Residual vapors may explode on ignition. Disposal of wastes containing either organic solvents or free-liquids in landfills is prohibited. **Local disposal requirements vary; consult your sanitation department or state-designated environmental agency for local disposal options.**

Environmental Health & Safety Information

DANGER!

EXTREMELY FLAMMABLE LIQUID AND VAPOR.

VAPORS MAY CAUSE FLASH FIRE.

CONTENTS UNDER PRESSURE.

Contains: acetone, propane, isobutyl acetate, butane

Vapor harmful. May affect the brain or nervous system causing dizziness, headache or nausea. Causes irritation to eyes, skin and respiratory tract. Do not puncture or incinerate (burn) container. Exposure to heat or prolonged exposure to sun may cause bursting. Do not expose to heat or store at temperatures above 120 °F.

NOTICE: Repeated or prolonged exposure to organic solvents may lead to permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling vapors may be harmful or fatal.

Vapors may ignite explosively. Keep away from heat, sparks and flame. Turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.

Use only with adequate ventilation. Do not breathe vapors, spray mist or sanding dust. Avoid contact with eyes and prolonged or repeated contact with skin. To avoid breathing vapors or spray mist open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor levels are above the applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling.



WARNING Cancer and Reproductive Harm—
www.P65warnings.ca.gov

FIRST AID: If affected by inhalation of vapors or spray mist, remove to fresh air. In case of eye contact, immediately flush with plenty of water for at least 15 minutes and get medical attention immediately; for skin, wash thoroughly with soap and water. If swallowed, do not induce vomiting. Get medical attention immediately.

IN CASE OF FIRE – Use foam, CO2, dry chemical or water fog..

IN CASE OF SPILL – Absorb with inert material and dispose of as specified under "Clean Up".

KEEP OUT OF REACH OF CHILDREN

Refer to Safety Data Sheet for additional health and safety information.