



CHALKBOARD PAINT

CHK-3078

Features

- 100% Acrylic
- Easy-to-Clean
- For interior surfaces

General Descriptions

INSL-X® Chalkboard Paint is 100% acrylic and turns virtually any interior surface into a chalkboard. Create a communication space in the kitchen for the family, turn a wall in your home office into a notepad or give your kids a place in their bedroom to get creative.

Recommended For

For interior use on previously painted surfaces. Use wherever a chalkboard finish is desired. For best results, use traditional, non-liquid chalk, in lighter colors.

Limitations

- Do not apply when air and surface temperatures are below 50 °F (10 °C).

Product Information

Colors — Standard: Black (80)	Technical Data	Black
— Tint Bases:	Vehicle Type	100% Acrylic
None	Pigment Type	Titanium Dioxide
— Special Colors:	Volume Solids	40 ± 1.0%
None	Coverage per quart at Recommended Film Thickness	100 – 110 Sq. Ft.
Certifications & Qualifications: VOC compliant in all regulated areas	Recommended Film Thickness	– Wet 3.8 mils – Dry 1.5 mils
Technical Assistance Available through your local authorized independent Benjamin Moore retailer. For the location of the retailer nearest you, call 1-866-708-9180 or visit www.benjaminmoore.com	Dry Time @ 77 °F (25 °C) @ 50% RH	– Tack Free 30 Minutes – To Recoat 4 Hours
	Allow painted area to cure for 3 days before using. Prior to initial use, rub entire surface with a piece of white chalk and then erase using a clean, damp cloth. Because of the additives used in some varieties of chalk, which can leave a residue when erased, we recommend using lighter colored chalk designed for use on chalkboards.	
	Dries By	Evaporation, Coalescence
	Viscosity	95 ± 5 KU
	Flash Point	None
	Gloss / Sheen	Eggshell (5 – 15 @ 85°)
	Surface Temperature at Application	– Min. 50 °F – Max. 90 °F
	Thin With	Do not Thin
	Clean Up Thinner	Warm Soapy Water
	Weight Per Gallon	10.6 lbs.
Storage Temperature	– Min. 40 °F – Max. 90 °F	
Volatile Organic Compounds (VOC)		
19.3 Grams/Liter 0.16 Lbs./Gallon		

Chalkboard Paint CHK-3078

Surface Preparation

Surfaces must be clean, dry and free of wax, grease, dust, mildew, water-soluble materials and scaling paint. Hard, glossy areas should be dulled with sandpaper to ensure proper adhesion.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Primer/Finish Systems

Use the appropriate INSL-X® primer if required. Follow label directions. For previously painted surfaces in good condition, apply two coats of this product. Otherwise, before and after filling in nail holes, cracks and other surface imperfections, spot prime with the appropriate INSL-X® primer. When dry, apply two finish coats of Chalkboard Paint (CHK-3078).

Application

Stir thoroughly. Apply with a quality nylon brush, short nap roller or spray gun. When brushing or rolling, apply generously using short overlapping strokes, always moving from unpainted into painted areas. Do not over apply. Let paint dry before touching up. Do not apply in temperatures below 50 °F (10 °C).

Before Using

Allow painted area to cure for 3 days before using. Prior to initial use, rub entire surface with a piece of white chalk and then erase using a clean, damp cloth. Because of the additives used in some varieties of chalk, which can leave a residue when erased, we recommend using lighter colored chalk designed for use on chalkboards.

Thinning/Cleanup

Thinning is unnecessary, but if required to obtain desired application properties, a small amount of clean water may be added. Never add other paints or solvents. Wash painting tools in warm soapy water immediately after use. Spray equipment should be given a final rinse with mineral spirits to prevent rusting.

USE COMPLETELY OR DISPOSE OF PROPERLY. Dry, empty containers may be recycled in a can recycling program. **Local disposal requirements vary, consult your sanitation department or state-designated environmental agency on disposal options.**

Environmental, Health & Safety Information

Use only with adequate ventilation. Do not breathe spray mist or sanding dust. Avoid contact with eyes and prolonged or repeated contact with skin. Wear eye protection and gloves during application or sanding. A dust/particulate respirator approved by NIOSH should be worn when sanding or spraying. Close container after each use.



WARNING Cancer and Reproductive Harm—
www.P65warnings.ca.gov

FIRST AID: If you experience difficulty in breathing, leave area to obtain fresh air. If continued difficulty is experienced, call physician immediately.

IN CASE OF: SPILL – Absorb with inert material and dispose of as specified under “THINNING/CLEAN UP”.

**KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING**

**Refer to Safety Data Sheet for additional
health and safety information**