

HP | HIGH PERFORMANCE

General Description

HP6000 Oil & Grease Emulsifier is a concentrated cleaner that is designed to convert any oil, grease, and animal by-products into a soapy solution which floats up and out of a surface during the rinsing process. It is effective for cleaning wax off tile floors and for cleaning tools and equipment.

- Concentrate for ultimate performance when mixed with water
- Biodegradable and phosphate-free
- Rinses clean with no residue

Usage

Oil & Grease Emulsifier is designed for cleaning walls, floors and equipment. It may also be used for cleaning concrete, asphalt, vinyl, metal, plastic, fiberglass, etc.; it is also very effective for cleaning equipment, tools, brushes, rollers and spray equipment.

Technical Data

| Spread Rate Per Gallon (mixed) | | 9.3 sq. m. (100 sq. ft.) |
|-----------------------------------|--------------|-----------------------------|
| Clean Up | | Water |
| Weight Per Gallon | 4 | .0 kg (8.9 lbs.) |
| Storage Temperature | Min: | 4.4 °C (40 °F) |
| | Max: | 35 °C (95 °F) |
| voc | Undiluted | 495 g/L |
| | Diluted 11:1 | 157 g/L |

Application

Shake well before using.

HP6000 Oil & Grease Emulsifier should be mixed with water before use, 11 parts water to 1 part emulsifier for heavy cleaning requirements and 15 parts water to 1 part emulsifier for light cleaning. A mixed gallon (3.79 L) will clean approximately 9.3 sq. m. (100 sq. ft.) of area. Pour the water and emulsifier mixture onto the surface to be cleaned. Allow this solution to work for 15 to 30 minutes then scrub the surface with a stiff bristled brush. Rinse thoroughly with clean water or pick up residue with a wet/dry vacuum. Repeat the cleaning procedure if necessary.

Clean Up

Clean all equipment immediately after using with soap and water. Spray equipment should be given a final rinse with mineral spirits to prevent corrosion.

USE COMPLETELY OR DISPOSE OF PROPERLY. Dry, empty containers may be recycled in a can recycling program. Local disposal requirements vary; consult your sanitation department or statedesignated environmental agency on disposal options.

Technical Assistance

Available through your local authorized independent Benjamin Moore retailer.

call 1-866-708-9180 visit www.benjaminmoore.ca

HP6000

Oil & Grease Emulsifier

Compliance & Certifications

Meets CISC/CPMA 1-73a and CISC/PMA 2-75 Specifications

Environmental Health & Safety Information

Danger Causes skin irritation Causes serious eye damage May cause an allergic skin reaction

Prevention: Wash face, hands and any exposed skin thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray. Contaminated work clothing should not be allowed out of the workplace.

Response: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash before reuse. If skin irritation or rash occurs: Get medical advice/attention.

Disposal: Dispose of contents/container to an approved waste disposal plant.

PROTECT FROM FREEZING

Refer to Safety Data Sheet for additional health and safety information.