



OIL & GREASE EMULSIFIER V600

Features

- Concentrated; must be mixed with water
- Biodegradable and phosphate-free
- Use on metal, fiberglass, vinyl, and masonry surfaces
- Rinses clean with no residue

General Description

Oil & Grease Emulsifier is designed for cleaning walls, floors and equipment. This cleaner is extremely effective in removing oil, grease, fats, blood and animal by-products. It may also be used for cleaning concrete, asphalt, vinyl, metal, plastic, fiberglass, etc.; it is also very effective for cleaning equipment, tools, brushes, rollers and spray equipment.

Recommended For

Corotech® Oil & Grease Emulsifier is designed for cleaning walls, floors and equipment. It may also be used for cleaning concrete, asphalt, vinyl, metal, plastic, fiberglass, etc.; it is also very effective for cleaning equipment, tools, brushes, rollers and spray equipment.

Limitations

Product Information																																							
Colours — Standard: N/A	Technical Data N/A <table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td>Vehicle Type</td><td>N/A</td></tr> <tr><td>Pigment Type</td><td>N/A</td></tr> <tr><td>Volume Solids</td><td>N/A</td></tr> <tr><td>Coverage per 3.79 L at Recommended Film Thickness</td><td>(Mixed) 9.3 sq. m. (100 sq. ft.)</td></tr> <tr><td>Recommended Film Thickness</td><td>– Wet N/A – Dry N/A</td></tr> <tr><td colspan="2">Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure colour uniformity and minimize the disposal of excess paint.</td></tr> <tr><td>Dry Time @ 25 °C (77 °F) @ 50% RH</td><td>– Tack Free N/A – To Recoat N/A</td></tr> <tr><td colspan="2">High humidity and cool temperatures will result in longer dry, recoat and service times.</td></tr> <tr><td>Dries By</td><td>N/A</td></tr> <tr><td>Viscosity</td><td>N/A</td></tr> <tr><td>Flash Point</td><td>N/A</td></tr> <tr><td>Gloss / Sheen</td><td>N/A</td></tr> <tr><td>Surface Temperature at Application</td><td>– Min. N/A – Max. N/A</td></tr> <tr><td>Thin With</td><td>Water</td></tr> <tr><td>Clean Up Thinner</td><td>Clean Water</td></tr> <tr><td>Weight Per 3.79 L</td><td>4.0 kg (8.9 lbs)</td></tr> <tr><td>Storage Temperature</td><td>– Min. 4.4 °C (40 °F) – Max. 35 °C (95 °F)</td></tr> <tr><td colspan="2" style="text-align: center;">Volatile Organic Compounds (VOC)</td></tr> <tr><td colspan="2" style="text-align: center;">157 Grams/Litre</td></tr> </table>	Vehicle Type	N/A	Pigment Type	N/A	Volume Solids	N/A	Coverage per 3.79 L at Recommended Film Thickness	(Mixed) 9.3 sq. m. (100 sq. ft.)	Recommended Film Thickness	– Wet N/A – Dry N/A	Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure colour uniformity and minimize the disposal of excess paint.		Dry Time @ 25 °C (77 °F) @ 50% RH	– Tack Free N/A – To Recoat N/A	High humidity and cool temperatures will result in longer dry, recoat and service times.		Dries By	N/A	Viscosity	N/A	Flash Point	N/A	Gloss / Sheen	N/A	Surface Temperature at Application	– Min. N/A – Max. N/A	Thin With	Water	Clean Up Thinner	Clean Water	Weight Per 3.79 L	4.0 kg (8.9 lbs)	Storage Temperature	– Min. 4.4 °C (40 °F) – Max. 35 °C (95 °F)	Volatile Organic Compounds (VOC)		157 Grams/Litre	
Vehicle Type	N/A																																						
Pigment Type	N/A																																						
Volume Solids	N/A																																						
Coverage per 3.79 L at Recommended Film Thickness	(Mixed) 9.3 sq. m. (100 sq. ft.)																																						
Recommended Film Thickness	– Wet N/A – Dry N/A																																						
Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure colour uniformity and minimize the disposal of excess paint.																																							
Dry Time @ 25 °C (77 °F) @ 50% RH	– Tack Free N/A – To Recoat N/A																																						
High humidity and cool temperatures will result in longer dry, recoat and service times.																																							
Dries By	N/A																																						
Viscosity	N/A																																						
Flash Point	N/A																																						
Gloss / Sheen	N/A																																						
Surface Temperature at Application	– Min. N/A – Max. N/A																																						
Thin With	Water																																						
Clean Up Thinner	Clean Water																																						
Weight Per 3.79 L	4.0 kg (8.9 lbs)																																						
Storage Temperature	– Min. 4.4 °C (40 °F) – Max. 35 °C (95 °F)																																						
Volatile Organic Compounds (VOC)																																							
157 Grams/Litre																																							
— Tint Bases: N/A																																							
— Special Colours: N/A																																							
Certifications & Qualifications: VOC compliant in Canada The product supported by this data sheet is not regulated by coatings VOC rules. Does not apply to LEED (Leadership in Energy and Environmental Design) standards.																																							
Technical Assistance: Available through your local authorized independent dealer. For the location of the dealer nearest you, call 1-800-361-5898 or visit www.benjaminmoore.ca																																							

Oil & Grease Emulsifier V600

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @ <https://www.canada.ca/en/health-canada/services/environmental-workplace-health/environmental-contaminants/lead/lead-information-package-some-commonly-asked-questions-about-lead-human-health.html>

Application

Shake well before using.

Corotech® Oil & Grease Emulsifier should be mixed with water before use, 11 parts water to 1 part emulsifier for heavy cleaning requirements and 15 parts water to 1 part emulsifier for light cleaning. A mixed 3.79 L will clean approximately 9.3 square metres/100 square feet of area. Pour the water and emulsifier mixture onto the surface to be cleaned. Allow this solution to work for 15 to 30 minutes. Then scrub the surface with a stiff bristled brush. Rinse thoroughly with clean water or pick up residue with a wet/dry vacuum. Repeat the cleaning procedure if necessary.

Clean Up

Clean up with clean water.

Environmental Health & Safety Information

Not a dangerous substance or mixture according to the Globally Harmonized System (GHS)

Keep container closed when not in use. In case of spillage, absorb with inert material and dispose of in accordance with local regulations. Wash thoroughly after handling. Refer to Safety Data Sheet for additional health and safety information.

3.32% of the mixture consists of ingredient(s) of unknown toxicity

**KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING**

**Refer to Safety Data Sheet for
additional health and safety information.**