



CITRUS CLEANER V610

Features

- Concentrated for maximum strength
- Excellent cleaner for a wide variety of surfaces
- Biodegradable and phosphate-free
- Milder and less corrosive to cleaned surfaces

General Description

Citrus Cleaner is an industrial strength, biodegradable, phosphate-free, emulsifying cleaner based on a natural citrus by-product. Cleans metals, masonry, painted surfaces, glass, upholstery, carpets, tile, plastics, and more.

Recommended For

Cleans metals, masonry, painted surfaces, glass, upholstery, carpets, tile, plastics, etc.

Limitations

- Mix or shake before adding to water.

Product Information

<p>Colors — Standard: N/A</p> <p>— Tint Bases: N/A</p> <p>— Special Colors: N/A</p> <p>Certifications & Qualifications:</p> <table border="1"> <thead> <tr> <th>VOC REGION</th> <th>COMPLIANT</th> </tr> </thead> <tbody> <tr> <td>FEDERAL</td> <td>YES</td> </tr> <tr> <td>OTC</td> <td>YES</td> </tr> <tr> <td>OTCII</td> <td>YES</td> </tr> <tr> <td>CARB</td> <td>NO</td> </tr> <tr> <td>CARB07</td> <td>NO</td> </tr> <tr> <td>UTAH</td> <td>YES</td> </tr> <tr> <td>AZMC</td> <td>YES</td> </tr> <tr> <td>SCAQMD</td> <td>NO</td> </tr> </tbody> </table> <p>Technical Assistance: Available through your local authorized independent Benjamin Moore retailer. For the location of the retailer nearest you, call 1-866-708-9180 or visit www.benjaminmoore.com</p>	VOC REGION	COMPLIANT	FEDERAL	YES	OTC	YES	OTCII	YES	CARB	NO	CARB07	NO	UTAH	YES	AZMC	YES	SCAQMD	NO	<p>Technical Data Δ</p> <table border="1"> <tr> <td>Vehicle Type</td> <td>N/A</td> </tr> <tr> <td>Pigment Type</td> <td>N/A</td> </tr> <tr> <td>Volume Solids</td> <td>N/A</td> </tr> <tr> <td>Coverage per Gallon at Recommended Film Thickness</td> <td>(Mixed) 100 Sq. Ft. (9.3 sq. m.)</td> </tr> <tr> <td>Recommended Film Thickness</td> <td>– Wet N/A – Dry N/A</td> </tr> <tr> <td colspan="2">Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint.</td> </tr> <tr> <td>Dry Time @ 77 °F (25 °C) @ 50% RH</td> <td>– Tack Free N/A – To Recoat N/A</td> </tr> <tr> <td colspan="2">High humidity and cool temperatures will result in longer dry, recoat and service times.</td> </tr> <tr> <td>Dries By</td> <td>N/A</td> </tr> <tr> <td>Dry Heat Resistance</td> <td>N/A</td> </tr> <tr> <td>Viscosity</td> <td>N/A</td> </tr> <tr> <td>Flash Point</td> <td>N/A</td> </tr> <tr> <td>Gloss / Sheen</td> <td>N/A</td> </tr> <tr> <td>Surface Temperature at Application</td> <td>– Min. N/A – Max. N/A</td> </tr> <tr> <td>Thin With</td> <td>Water</td> </tr> <tr> <td>Clean Up Thinner</td> <td>N/A</td> </tr> <tr> <td>Weight Per Gallon</td> <td>N/A</td> </tr> <tr> <td>Storage Temperature</td> <td>– Min. 40 °F (4.4 °C) – Max. 95 °F (35 °C)</td> </tr> <tr> <td colspan="2" style="text-align: center;">Volatile Organic Compounds (VOC)</td> </tr> <tr> <td colspan="2" style="text-align: center;">524 g/L 4.38 Lbs./Gallon</td> </tr> </table>	Vehicle Type	N/A	Pigment Type	N/A	Volume Solids	N/A	Coverage per Gallon at Recommended Film Thickness	(Mixed) 100 Sq. Ft. (9.3 sq. m.)	Recommended Film Thickness	– Wet N/A – Dry N/A	Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint.		Dry Time @ 77 °F (25 °C) @ 50% RH	– Tack Free N/A – To Recoat N/A	High humidity and cool temperatures will result in longer dry, recoat and service times.		Dries By	N/A	Dry Heat Resistance	N/A	Viscosity	N/A	Flash Point	N/A	Gloss / Sheen	N/A	Surface Temperature at Application	– Min. N/A – Max. N/A	Thin With	Water	Clean Up Thinner	N/A	Weight Per Gallon	N/A	Storage Temperature	– Min. 40 °F (4.4 °C) – Max. 95 °F (35 °C)	Volatile Organic Compounds (VOC)		524 g/L 4.38 Lbs./Gallon	
VOC REGION	COMPLIANT																																																										
FEDERAL	YES																																																										
OTC	YES																																																										
OTCII	YES																																																										
CARB	NO																																																										
CARB07	NO																																																										
UTAH	YES																																																										
AZMC	YES																																																										
SCAQMD	NO																																																										
Vehicle Type	N/A																																																										
Pigment Type	N/A																																																										
Volume Solids	N/A																																																										
Coverage per Gallon at Recommended Film Thickness	(Mixed) 100 Sq. Ft. (9.3 sq. m.)																																																										
Recommended Film Thickness	– Wet N/A – Dry N/A																																																										
Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint.																																																											
Dry Time @ 77 °F (25 °C) @ 50% RH	– Tack Free N/A – To Recoat N/A																																																										
High humidity and cool temperatures will result in longer dry, recoat and service times.																																																											
Dries By	N/A																																																										
Dry Heat Resistance	N/A																																																										
Viscosity	N/A																																																										
Flash Point	N/A																																																										
Gloss / Sheen	N/A																																																										
Surface Temperature at Application	– Min. N/A – Max. N/A																																																										
Thin With	Water																																																										
Clean Up Thinner	N/A																																																										
Weight Per Gallon	N/A																																																										
Storage Temperature	– Min. 40 °F (4.4 °C) – Max. 95 °F (35 °C)																																																										
Volatile Organic Compounds (VOC)																																																											
524 g/L 4.38 Lbs./Gallon																																																											

Citrus Cleaner V610

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Informational Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Application

For severe concentrations of dirt, grease, and oil, use Corotech® Citrus Cleaner full strength, allow to work ten minutes and rinse with a pressure washer. For heavy cleaning, use 1 cup (8 oz.) of Corotech® Citrus Cleaner to one gallon of water. For maintenance use one 1/2 cup (4 oz.) Corotech® Citrus Cleaner to one gallon of water. For light cleaning, 2 oz. of Corotech® Citrus Cleaner per gallon of water is adequate. Before using on carpet, fabric, upholstery, drapes, etc., try a spot test on any inconspicuous part of the item to be certain the color of the item is not affected. **Mix or shake before adding to water.**

Clean Up

Clean up with clean water.

Environmental Health & Safety Information

DANGER!

Causes skin irritation

Causes serious eye irritation

May cause an allergic skin reaction

May cause cancer

May damage fertility or the unborn child

May cause damage to organs through prolonged or repeated exposure

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wash face, hands and any exposed skin thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Do not breathe dust /fume /mist /vapors /spray. Wear protective gloves /protective clothing /eye protection /face protection.

Response: If exposed or concerned, get medical attention. If in eyes, rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical attention. If on skin, wash with plenty of soap and water. Take off contaminated clothing and wash before reuse. If skin irritation or rash occurs, get medical attention.

Storage: Store locked up.

Disposal: Dispose of contents /container to an approved waste disposal plant.



WARNING Cancer and Reproductive Harm—
www.P65warnings.ca.gov.

**KEEP OUT OF REACH OF CHILDREN
KEEP FROM FREEZING**

**Refer to Safety Data Sheet for
additional health and safety information.**