



URETHANE REDUCER V700

Features

- For use with all two-part solvent-based urethane coatings
- For effective cleaning of tools and equipment
- May be used to reduce and thin coatings up to the legal limits allowed by district

General Description

Urethane Reducer is 100% butyl acetate for use in thinning catalyzed acrylic urethanes. Effective for cleaning equipment immediately after use as well. Do not use this product for cleaning synthetic brushes or rollers, as it will dissolve them.

Recommended For

Corotech® Urethane Reducer is 100% butyl acetate for use in thinning catalyzed acrylic urethanes. Use for clean-up of equipment immediately after use.

Limitations

- Do not use this product for cleaning synthetic brushes or rollers as it will dissolve them.

Product Information

Product Information		Technical Data	Urethane Reducer
Colours — Standard:	N/A	Vehicle Type	100% Butyl Acetate
— Tint Bases:	N/A	Pigment Type	N/A
— Special Colours:	N/A	Volume Solids	N/A
Certification:	<p>The product supported by this data sheet is regulated by consumer product VOC rules, in some areas, as a paint thinner, multi-purpose solvent.</p> <p>This product is exempt under the Ozone Transport Commission regulations.</p> <p>It also does not apply to LEED (Leadership in Energy and Environmental Design) standards.</p>	Coverage per 3.79 L at Recommended Film Thickness	N/A
Technical Assistance:	<p>Available through your local authorized independent Benjamin Moore® retailer. For the location of the retailer nearest you, call 1-877-711-6830, or visit www.benjaminmoore.ca</p>	Recommended Film Thickness – Wet – Dry	N/A N/A N/A
		Dry Time @ 25 °C (77 °F) @ 50% RH	– Tack Free – To Recoat N/A N/A
		Dries By	N/A
		Viscosity	N/A
		Flash Point	27.2 °C (81 °F) (TT-P-141, Method 4293)
		Gloss / Sheen	N/A
		Surface Temperature at Application	– Min. – Max. N/A N/A
		Thin With	N/A
		Clean Up Thinner	N/A
		Weight Per 3.79 L	
		Storage Temperature	– Min. 4.4 °C (40 °F) – Max. 35 °C (95 °F)
		Volatile Organic Compounds (VOC)	
		880 Grams/Litre	

Urethane Reducer V700

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @ http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked_questions_questions_posees-eng.php

Application

Corotech® Urethane Reducer is 100% Butyl Acetate for use in thinning catalyzed acrylic urethanes. Use for clean-up of equipment immediately after use. Do not use this product for cleaning synthetic brushes or rollers as it will dissolve them.

Environmental Health & Safety Information

Warning

May cause drowsiness or dizziness

Flammable liquid and vapour

Prevention: Avoid breathing dust/fume/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/open flames/hot surfaces, no smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/protective clothing/eye protection/face protection. Keep cool.

Response: If on skin (or hair) take off immediately all contaminated clothing. Rinse skin with water. If inhaled remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. In case of fire use CO₂, dry chemical, or foam for extinction.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal: Dispose of contents/container to an approved waste disposal plant.

**KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING**

**Refer to Safety Data Sheet for
additional health and safety information.**